

allPIXA evo/neo camera | Features Reference



VERSION 6.4.0

Table of Contents

1	Introduction	10
1.1	Connection Timeouts	10
2	Feature Availability	11
3	Camera Variants	11
4	Device Control	13
4.1	Device Vendor Name	13
4.2	Device Model Name	13
4.3	Device Manufacturer Info	13
4.4	Device Version.....	14
4.5	Device User ID.....	14
4.6	Device Scan Type.....	14
4.7	Device Package Version	15
4.8	Device Package Description.....	15
4.9	Device Package Consistency	15
4.10	Device Sensor File Version	16
4.11	Device Hardware Calibration File Version.....	16
4.12	Device Firmware Version	16
4.13	Device FPGA Version.....	16
4.14	Device Product Number	17
4.15	Device Serial Number.....	17
4.16	Device SFNC Version Major.....	17
4.17	Device SFNC Version Minor.....	18
4.18	Device SFNC Version SubMinor	18
4.19	Device Manifest XML Major Version	18
4.20	Device Manifest XML Minor Version	19
4.21	Device Manifest XML Sub Minor Version	19
4.22	Device Manifest XML Extra Version	19
4.23	Device Temperature Selector	19
4.24	Device Temperature	20
4.25	Device Voltage Selector	20
4.26	Device Voltage.....	20
4.27	Device Fan Enable	21
4.28	Device Identify	21
4.29	Device Reset	22
4.30	Device Error Code	22
4.31	Device Error Message	22
4.32	Device Status.....	23
4.33	Device Log Level	23
4.34	Device TL Type.....	24
4.35	Device Link Selector	24
4.36	Device Link Connection Count	24
4.37	Device Link Speed.....	24

4.38	Device Average Resolution – Not Available for AllPIXI-EVO	25
4.39	Device TL Version Major	25
4.40	Device TL Version Minor	25
4.41	Device TL Version Sub Minor	25
4.42	Device Registers Endianness.....	25
4.43	Device Character Set	26
4.44	Device Event Channel Count	26
4.45	Device Stream Channel Count	26
4.46	Device Link Heartbeat Timeout	27
4.47	Device Stream Channel Endianness.....	27
4.48	Timestamp Reset.....	27
4.49	Timestamp Latch	27
4.50	Timestamp Latch Value	28
5	Image Format Control.....	29
5.1	Sensor Width	30
5.2	Sensor Height	30
5.3	Sensor Color Filter	30
5.4	Width Max.....	31
5.5	Height Max.....	31
5.6	Region Selector	31
5.7	Region Mode	32
5.8	Width.....	32
5.9	Height	32
5.10	Offset X.....	32
5.11	Sensor Region Offset X.....	33
5.12	Sensor Region Width.....	33
5.13	Binning Horizontal.....	33
5.14	Decimation Horizontal Float	34
5.15	Reverse X.....	34
5.16	Pixel Format.....	34
5.17	Pixel Color Filter	35
5.18	Infoblock Mode	36
5.19	Test Pattern Generator Selector.....	42
5.20	Test Pattern	42
5.21	Test Pattern Value	43
6	Acquisition Control.....	44
6.1	Acquisition Mode	44
6.2	Acquisition Start.....	44
6.3	Acquisition Stop	44
6.4	Acquisition Abort.....	45
6.5	Frame Count.....	45
6.6	Exposure Time Mode	45
6.7	Exposure Time Selector	45

6.8	Exposure Time.....	46
6.9	Acquisition Integration Time – Deprecated	46
6.10	Acquisition Integration Time Min – Deprecated.....	46
6.11	Acquisition Line Rate	47
6.12	Acquisition Line Rate Max – Deprecated	47
6.13	Acquisition Line Time	47
6.14	Acquisition Line Time Min – Deprecated	49
6.15	Acquisition Frame Rate Enable	49
6.16	Acquisition Frame Rate	49
6.17	Time Delay Integration Mode	50
6.18	Time Delay Integration	50
6.19	Master Slave Mode.....	50
6.20	Master Slave Interface - Deprecated.....	51
6.21	Master Slave Interface Enable - Deprecated	52
6.22	Master Slave Source	52
6.23	AutoSelect Source	52
6.24	Slave DelayLines	53
6.25	Acquisition Burst Frame Count.....	53
6.26	Trigger Selector	54
6.27	Trigger Mode	54
6.28	Trigger Source	54
6.29	Trigger Activation.....	55
6.30	Trigger DelayLines.....	55
6.31	Trigger Divider	56
6.32	Trigger Signal Detection Mode	57
6.33	Extend Lines	57
6.34	Line Time (Measured)	57
6.35	Line Trigger Status	58
7	Analog Control	59
7.1	Gain Selector	59
7.2	Gain	60
7.3	Gain Auto	60
7.4	Gain Auto Status.....	61
7.5	Synchronization Mode Enable.....	61
7.6	Stop Control Enable	62
7.7	Stop Factor	62
7.8	Gain Control Region Offset X	62
7.9	Gain Control Region Width.....	63
7.10	Gain Control Region Offset Y	63
7.11	Gain Control Region Height.....	63
7.12	Gain Control Region visible	63
7.13	Average Samples	64
7.14	Gain Control Region Channel Selector	64

7.15	Target value.....	65
7.16	Current value	65
7.17	Sensor Sensitivity Channel Selector	66
7.18	Sensor Sensitivity	66
7.19	Gamma	67
7.20	Brightness Contrast Enable	67
7.21	Brightness Contrast Channel Selector	67
7.22	Contrast	68
7.23	Brightness	68
8	Image Calibration Control	69
8.1	Image Calibration Mode - Deprecated	69
8.2	Dark Signal Non-Uniformity (DSNU) Selector - Deprecated	70
8.3	DSNU Dataset Information - Deprecated	70
8.4	DSNU Available Planes - Deprecated	72
8.5	First Valid Pixel - Deprecated	72
8.6	Last Valid Pixel - Deprecated	72
8.7	DSNU Display Reference Values - Deprecated	73
8.8	Photo Response Non-Uniformity (PRNU) Selector - Deprecated	73
8.9	PRNU Dataset Information - Deprecated	73
8.10	PRNU Available Planes - Deprecated	74
8.11	First Valid Pixel - Deprecated	74
8.12	Last Valid Pixel - Deprecated	74
8.13	PRNU Display Reference Values - Deprecated	75
8.14	Flat Field Correction Calibration Mode	75
8.15	Flat Field Correction Selector	76
8.16	Enable.....	76
8.17	DataSet Description.....	76
8.18	Available Planes	77
8.19	First Valid Pixel	77
8.20	Last Valid Pixel	78
8.21	Display Reference	78
8.22	Start Calibration	78
8.23	Stop Calibration	78
8.24	Calibration Status	79
8.25	Line Distance	79
8.26	Scan Direction Source	79
8.27	Scan Direction	81
8.28	Image Center Offset – Not Available for AllPIXA-EVO.....	81
9	Color Transformation Control	82
9.1	Color Transformation Selector.....	82
9.2	Color Transformation Enable.....	83
9.3	Color Transformation Value Selector	83
9.4	Color Transformation Value.....	84

10	LUT Control	85
10.1	LUT Selector.....	85
10.2	LUT Enable.....	85
10.3	LUT Dataset Name - Deprecated	86
11	User Set Control	87
11.1	Loaded User Set.....	87
11.2	User Set Selector.....	87
11.3	User Set Load.....	87
11.4	User Set Save.....	88
11.5	User Set Comment	88
12	Transport Layer Control.....	89
12.1	TLPParamsLocked.....	89
12.2	Payload Size	89
12.3	Device Tap Geometry.....	89
12.4	GigE Vision	90
12.4.1	Gev Version Major	90
12.4.2	Gev Version Minor	90
12.4.3	Gev Device Mode Is Big Endian.....	90
12.4.4	Gev Device Mode Character Set.....	90
12.4.5	Gev Interface Selector	91
12.4.6	Gev MACAddress	91
12.4.7	Gev Supported Option Selector.....	91
12.4.8	Gev Supported Option	92
12.4.9	Gev Current IP Configuration LLA.....	92
12.4.10	Gev Current IP Configuration DHCP	93
12.4.11	Gev Current IP Configuration Persistent IP.....	93
12.4.12	Gev Current IP Address	93
12.4.13	Gev Current Subnet Mask	93
12.4.14	Gev Current Default Gateway	94
12.4.15	Gev First URL	94
12.4.16	Gev Second URL.....	94
12.4.17	Gev Number of Interfaces – Deprecated.....	94
12.4.18	Gev Persistent IP Address	95
12.4.19	Gev Persistent Subnet Mask	95
12.4.20	Gev Persistent Default Gateway	95
12.4.21	Gev Persistent IP Address	95
12.4.22	GevLinkSpeed	96
12.4.23	Gev Message Channel Count	96
12.4.24	Gev Stream Channel Count	96
12.4.25	Gev Heartbeat Timeout	96
12.4.26	Gev Timestamp Tick Frequency.....	97
12.4.27	Gev Timestamp Control Latch.....	97
12.4.28	Gev Timestamp Control Reset	97

12.4.29	Gev Time stamp Value	97
12.4.30	Gev CCP.....	98
12.4.31	Gev MCPHost Port	98
12.4.32	Gev MCDA.....	98
12.4.33	Gev MCTT	98
12.4.34	Gev MCRC	99
12.4.35	Gev MCSP	99
12.4.36	Gev Stream Channel Selector	99
12.4.37	Gev SCP Interface Index	99
12.4.38	Gev SCPHost Port.....	100
12.4.39	Gev SCPSFire Test Packet	100
12.4.40	Gev SCPSTo Not Fragment.....	100
12.4.41	Gev SCPSBig Endian	100
12.4.42	Gev SCSPPacket Size	101
12.4.43	Gev SCPD	101
12.4.44	Gev SCDA	101
12.5	CoaXPress.....	102
12.5.1	Cxp Link Configuration Preferred	102
12.5.2	Cxp Link Configuration	103
12.5.3	Cxp Version Used.....	104
12.5.4	Cxp Connection Selector	104
12.5.5	Cxp Connection Test Mode	105
12.5.6	Cxp Connection Test Packet Count Tx	105
12.5.7	Cxp Connection Test Packet Count Rx	105
12.5.8	Cxp Connection Test Error Count	105
13	File Access Control.....	107
13.1	File Selector.....	107
13.2	File Operation Selector	108
13.3	File Operation Execute	109
13.4	File Open Mode	109
13.5	File Access Offset.....	109
13.6	File Access Length	110
13.7	File Operation Result	110
13.8	File Operation Status	110
13.9	File Size	111
13.10	File Checksum	111
13.11	File Access Buffer.....	112
14	Digital IO Control	113
14.1	Functional scope.....	113
14.1.1	allPIXA evo	113
14.1.2	allPIXA neo	114
14.2	Line Selector.....	115
14.3	Line Mode	116

14.4	Line Inverter.....	116
14.5	Line Status.....	116
14.6	Line Source.....	117
14.7	Line Format.....	118
14.8	UserOutput Selector.....	118
14.9	UserOutput Value.....	119
14.10	Trigger Activation.....	119
14.11	Source Channel A.....	120
14.12	Source Channel B.....	120
14.13	Start Sampling.....	121
14.14	Stop Sampling.....	121
14.15	Sample Rate Reduction.....	121
14.16	Sample Rate.....	122
14.17	Trigger Position.....	122
14.18	IO Analyzer State.....	122
14.19	IO Analyzer State.....	123
14.20	IO Analyzer Status.....	123
14.21	Event Count.....	123
15	Encoder Control.....	124
15.1	Encoder Selector.....	124
15.2	Encoder Source A.....	124
15.3	Encoder Source B.....	125
15.4	Encoder Mode.....	125
15.5	Encoder Output Mode.....	126
15.6	Encoder Divider Float.....	126
15.7	Encoder Average.....	126
15.8	Encoder Value.....	127
16	Led Flash Control.....	128
16.1	Led Flash Enable.....	128
16.2	Led Flash Number of Pattern.....	128
16.3	Led Flash Pattern Selector.....	128
16.4	Out1 OnTime.....	129
16.5	Out2 OnTime.....	129
16.6	Out3 OnTime.....	129
16.7	Out4 OnTime.....	130
16.8	Pattern Off Delay.....	130
16.9	Pattern duration.....	130
16.10	Led Flash Frame Control.....	131
16.11	Led Flash Sequence Time.....	131
17	Lighting Control – Not Available for AIPIX-A-EVO.....	132
17.1	Light Controller Set Load.....	132
17.2	Light Controller Set Save.....	132
17.3	Light Controller Scan Devices.....	132

17.4	Light Controller Scan Status	133
17.5	Light Controller Detected Devices	133
17.6	Light Controller General Error	133
17.7	Light Controller Selector	134
17.8	Light Connection Status	135
17.9	Light Controller Reset.....	135
17.10	Light Controller Assign ID	135
17.11	Light Controller Input Voltage	135
17.12	Light Controller Detailed Error Information	136
17.13	Light Controller Serial Number	136
17.14	Light Controller Channel Selector.....	136
17.15	Light Current Rating.....	137
17.16	Light Enable.....	137
17.17	Light Controller Driver Temperature	137
17.18	Light Controller Luminant Temperature.....	137
18	Device Error Code	138
18.1	Error Category (Upper 2 bytes)	138
18.2	Specific Error (Lower 2 bytes)	139
18.2.1	Image Format Control (IMF_ERROR_CATEGORY).....	139
18.2.2	Analog Control (ALG_CTRL_ERROR_CATEGORY)	140
18.2.3	Acquisition Control (ACQ_CTRL_ERROR_CATEGORY).....	141
18.2.4	Digital IO Control (DIG_IO_CTRL_ERROR_CATEGORY).....	143
18.2.5	Encoder Control (ENC_CTRL_ERROR_CATEGORY).....	143
18.2.6	User Set Control (USER_SET_CTRL_ERROR_CATEGORY).....	144
18.2.7	Image Calibration Control (ICC_ERROR_CATEGORY).....	144
18.2.8	LUT Control (LUT_CTRL_ERROR_CATEGORY)	144
18.2.9	Color Transformation Control (CT_CTRL_ERROR_CATEGORY)	144
18.2.10	Device Control (DEV_CTRL_ERROR_CATEGORY)	145
18.2.11	File Access Control (FAC_ERROR_CATEGORY).....	145
18.2.12	Led Flash Control (LED_FLASH_CTRL_ERROR_CATEGORY)	146
18.2.13	IO Analyzer (IO_ANALYZER_ERROR_CATEGORY)	146
19	Device Status Code	147
19.1	Device Status Category (Upper 2 bytes)	147
19.2	Specific status (Lower 2 bytes).....	147
20	Debug Control.....	148
20.1	Full-Flag.....	148
21	Document History	149

1 Introduction

The **Features Reference Guide** describes the features for Chromasens allPIXA evo cameras using the GenICam SFNC (Standard Feature Naming Convention).

In addition, the error codes of the camera are documented here.

1.1 Connection Timeouts

Reading and writing different features leads to different execution times on the camera and therefore to shorter or longer response times. To establish communication without getting timeouts the timeout parameters must be configured in a way to be within the execution time of all feature read/write requests.

Parameter	Value
Control Channel timeout (<i>CC_timeout</i>)	3000ms
Control Channel retry count	3
Device Link Heartbeat Timeout	9000ms

Special note for sphinx lib users. In *SphinxLib HeartbeatRate* corresponds to [Device Link Heartbeat Timeout](#). The *cc_heartbeat_timeout* of sphinx lib should be set to a third of [Device Link Heartbeat Timeout](#).

2 Feature Availability

The following table illustrates the availability of features for several camera variants.

Feature	ax_dxge	ax_dsxge	ax_cxp	g8_dxge	g8_cxp	p6_nxge	p16_cxp
Trigger Control	A	A	A	A	A	A	A
Encoder Control	A	A	A	A	A	A	A
Scan Direction Source	A	NA	A	A	A	A	A
Master/Slave Mode	A	A	E	A	E	NA	A
Led Flash Control	A	E	A	A	A	NA	A
Single ROI support	A	A	A	A	A	A	A
Multi ROI support	NA	A	NA	NA	NA	NA	NA
Reverse X	A	A	A	A	A	A	A
Binning Horizontal	A	A	A	A	A	A	A
Decimation Horizontal	A	NA	A	A	A	NA	NA
Gain Auto	A	A	A	A	A	A	A
Sensor Sensitivity	A	A	A	A	A	A	A
Internal DSNU/PRNU capturing	A	NA	A	A	A	A	A
Color Transformation Control	A	A	A	A	A	A	A
Gamma	A	A	A	A	A	A	A
Brightness Contrast	A	A	A	A	A	A	A
User Set Control	A	A	A	A	A	A	A
File Access Control	A	A	A	A	A	A	A
Four Color Mode (RGB+NIR)	NA	NA	NA	A	A	A	NA
IOAnalyzer	A	A	A	A	A	NA	A

A: Available NA: Not Available E: Experimental

3 Camera Variants

The following table shows the different camera variants available:

Variant	Types
ALL	ax_dxge ax_dsxge ax_cxp g8_dxge g8_cxp p6_nxge
EVO	ax_dxge ax_dsxge ax_cxp g8_dxge g8_cxp p16_cxp
NEO	p6_nxge
ax_X	ax_dxge ax_dsxge ax_cxp
g8_X	g8_dxge g8_cxp
X_dxge	ax_dxge g8_dxge

X_cxp	ax_cxp g8_cxp p16_cxp
ax_dsxge	ax_dsxge
p6_nxge	p6_nxge
p16_cxp	p16_cxp

The following table shows the different camera types with the model names:

Types	Model Name
ax_dxge	allPIXA evo 10K DXGE allPIXA evo 10K DXGE mono allPIXA evo 15K DXGE allPIXA evo 15K DXGE mono
ax_dsxge	allPIXA evo 10K DXGE allPIXA evo 10K DXGE mono allPIXA evo 15K DXGE allPIXA evo 15K DXGE mono
ax_cxp	allPIXA evo 10K CXP allPIXA evo 10K CXP mono allPIXA evo 15K CXP allPIXA evo 15K CXP mono
g8_dxge	allPIXA evo 8K DXGE allPIXA evo 8K DXGE mono
g8_cxp	allPIXA evo 8K CXP allPIXA evo 8K CXP mono
p6_nxge	allPIXA neo 6K NXGE allPIXA neo 6K NXGE mono
p16_cxp	allPIXA evo 16K CXP

4 Device Control

4.1 Device Vendor Name

Name	DeviceVendorName	Standard
Description	Name of the manufacturer of the device.	
Interface	String	
String length	32	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	Chromasens GmbH	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.2 Device Model Name

Name	DeviceModelName	Standard
Description	Model of the device.	
Interface	String	
String length	32	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.3 Device Manufacturer Info

Name	DeviceManufacturerInfo	Standard
Description	Manufacturer information about the device.	
Interface	String	
String length	48	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	Currently not visible.	
Error behavior	-	

4.4 Device Version

Name	DeviceVersion	Standard
Description	Version of the device.	
Interface	String	
String length	32	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	Currently not visible.	
Error behavior	-	

4.5 Device User ID

Name	DeviceUserID	Standard
Description	User-programmable device identifier.	
Interface	String	
String length	16	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	-	
Default value	Empty String	
Availability	ALL	
Notes	-	
Error behavior	-	

4.6 Device Scan Type

Name	DeviceScanType	Standard
Description	Scan type of the sensor.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entry table below.	
Default value	-	
Availability	ALL	
Notes	Even though the camera is a line scan device, this feature is set to Areascan. The camera supports frame trigger.	
Error behavior	-	

Device Scan Type Enum Entries:

Name	Description
Areascan	The camera is operating in area scan mode
Linescan	The camera is operating in line scan mode

4.7 Device Package Version

Name	DevicePackageVersion	Custom
Description	Version of the software package of the camera. The version is defined in the package description file. By querying the DevicePackageConsistency feature you can check whether a package is consistent.	
Interface	String	
String length	16	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.8 Device Package Description

Name	DevicePackageDescription	Custom
Description	Description of the device's software package.	
Interface	String	
String length	64	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.9 Device Package Consistency

Name	DevicePackageConsistency	Custom
Description	Executes a package consistency check. Is set to True if the package is consistent otherwise it is set to False . A package is consistent if the files on the camera correspond to the files in the package description file.	
Interface	Boolean	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	False : Package is not consistent True : Package is consistent	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.10 Device Sensor File Version

Name	DeviceSensorFileVersion	Custom
Description	Version of the sensor file in the device.	
Interface	String	
String length	40	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.11 Device Hardware Calibration File Version

Name	DeviceHWCaliFileVersion	Custom
Description	Version of the Hardware Calibration File in the device.	
Interface	String	
String length	16	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	Returns -NA- if the file is not available in the camera.	
Error behavior	-	

4.12 Device Firmware Version

Name	DeviceFirmwareVersion	Standard
Description	Version of the firmware in the device.	
Interface	String	
String length	64	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.13 Device FPGA Version

Name	DeviceFPGAVersion	Custom
Description	Version of the FPGA in the device.	
Interface	String	
String length	16	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.14 Device Product Number

Name	DeviceProductNumber	Custom
Description	Product number of the device.	
Interface	String	
String length	32	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.15 Device Serial Number

Name	DeviceSerialNumber	Standard
Description	Serial number of the device.	
Interface	String	
String length	32	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.16 Device SFNC Version Major

Name	DeviceSFNCVersionMajor	Standard
Description	Major version of the Standard Features Naming Convention that was used to create the device's GenICam XML.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	>0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.17 Device SFNC Version Minor

Name	DeviceSFNCVersionMinor	Standard
Description	Minor version of the Standard Features Naming Convention that was used to create the device's GenICam XML.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	

4.18 Device SFNC Version SubMinor

Name	DeviceSFNCVersionSubMinor	Standard
Description	Sub-minor version of the Standard Features Naming Convention that was used to create the device's GenICam XML.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	

4.19 Device Manifest XML Major Version

Name	DeviceManifestXMLMajorVersion	Standard
Description	Indicates the major version number of the GenICam XML file of the selected manifest entry.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	≥ 0	
Availability	ALL	
Notes	-	
Error behavior	The XML version should match the DeviceFirmwareVersion .	

4.20 Device Manifest XML Minor Version

Name	DeviceManifestXMLMinorVersion	Standard
Description	Indicates the minor version number of the GenICam XML file of the selected manifest entry.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥0	
Default value	-	
Availability	ALL	
Notes	The XML version should match the DeviceFirmwareVersion .	

4.21 Device Manifest XML Sub Minor Version

Name	DeviceManifestXMLSubMinorVersion	Standard
Description	Indicates the sub-minor version number of the GenICam XML file of the selected manifest entry.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥0	
Default value	-	
Availability	ALL	
Notes	The XML version should match the DeviceFirmwareVersion .	

4.22 Device Manifest XML Extra Version

Name	DeviceManifestXMLExtraVersion	Standard
Description	Indicates the extra version (pre-release/build metadata) of the GenICam XML file of the selected manifest entry.	
Interface	String	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	String	
Default value	-	
Availability	ALL	
Notes	The XML version should match the DeviceFirmwareVersion .	

4.23 Device Temperature Selector

Name	DeviceTemperatureSelector	Standard
Description	Selects the location within the device, where the temperature will be measured.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	See enum entry table below.	
Default value	Mainboard	
Availability	ALL	
Notes	-	
Error behavior	-	

Device Temperature Selector Enum Entries:

Name	Description
Mainboard	Temperature of the mainboard
Power1	Temperature of the power module 1
Power2	Temperature of the power module 2
Sensor	Temperature of the sensor

4.24 Device Temperature

Name	DeviceTemperature[DeviceTemperatureSelector]	Standard
Description	Device temperature in degrees Celsius.	
Interface	Float	
Access mode	Read only	
Adjustable while grabbing	-	
Value range		
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.25 Device Voltage Selector

Name	DeviceVoltageSelector	Custom
Description	Selects a voltage source.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	See enum entry table below.	
Default value	Channel1	
Availability	ALL	
Notes	-	
Error behavior	-	

Device Voltage Selector Enum Entries:

Name	Description
<i>Channel1</i>	Selects Channel 1
<i>Channel2</i>	Selects Channel 2
<i>Channel3</i>	Selects Channel 3
<i>Channel4</i>	Selects Channel 4
<i>Channel5</i>	Selects Channel 5
<i>Channel6</i>	Selects Channel 6
<i>Channel7</i>	Selects Channel 7
<i>Channel8</i>	Selects Channel 8

4.26 Device Voltage

Name	DeviceVoltage[DeviceVoltageSelector]	Custom
Description	Displays the voltage for the selected element.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	The unit of this feature is mV.	
Error behavior	-	

4.27 Device Fan Enable

Name	DeviceFanEnable	Custom
Description	Enables the camera's fan.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – Enables the output of an IO to activate a fan connected to the device. False – Disables the output of an IO to disable a fan connected to the device.	
Default value	False	
Availability	ALL	
Notes	-	
Error behavior	-	

4.28 Device Identify

Name	DeviceIdentify	Custom
Description	Increases heartbeat speed for a short time to identify the camera.	
Interface	Command	
Access mode	Write only	
Adjustable while grabbing	Yes	
Value range	1	
Default value	1	
Availability	ALL	
Notes	While grabbing images you will not see the heartbeat. Therefore, this only takes effect if the acquisition is not active.	
Error behavior	-	

4.29 Device Reset

Name	DeviceReset	Standard
Description	Resets the device to its power-up state.	
Interface	Command	
Access mode	Write only	
Adjustable while grabbing	Yes	
Value range	1	
Default value	1	
Availability	ALL	
Notes	<p>This command always returns success.</p> <p>If you execute this command, the camera performs a power cycle. Afterwards you must reconnect to the camera.</p>	
Error behavior	-	

4.30 Device Error Code

Name	DeviceErrorCode	Custom
Description	Most recent error status of the camera.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See Device Error Code section for possible values.	
Default value	0x00000000	
Availability	ALL	
Notes	<p>Reads the most recent error. Zero indicates no error. Any other value indicates an error. If a write access to any register is performed (except bootstrap registers), the device error code is cleared.</p> <p>The DeviceErrorMessage feature holds the corresponding error description.</p>	
Error behavior	-	

4.31 Device Error Message

Name	DeviceErrorMessage	Custom
Description	Device error messages to the corresponding device error codes .	
Interface	Enumeration	
Access mode	Read Only	
Adjustable while grabbing	-	
Value range	See enum entry table below.	
Default value	Success	
Availability	ALL	
Notes	<p>This feature is "Invisible"</p> <p>The device error message consists of the tool tip and display name of the enum entry. Please check section Device Error Code too. There you will find the description of the enum entries.</p>	
Error behavior	-	

4.32 Device Status

Name	DeviceStatus	Custom
Description	Device status to the corresponding device status codes .	
Interface	Enumeration	
Access mode	Read Only	
Adjustable while grabbing	-	
Value range	See enum entry table below.	
Default value	OK	
Availability	ALL	
Notes	-	
Error behavior	-	

Device Status Enum Entries:

Name	Description
DEV_STATUS_WARNING_TEMPERATURE_TOO_HIGH	Warning: Device temperature high.
DEV_STATUS_ERROR_TEMPERATURE_TOO_HIGH	Error: Device temperature too high.
DEV_STATUS_ERROR_ILLUM_TEMPERATURE_TOO_HIGH	Error: Illumination temperature too high.
DEV_STATUS_ERROR_ILLUM_LED_ERROR	Error: Illumination Error.
SENSOR_STATUS_G8_PGOOD_ERROR	Error: G8 sensor PGOOD error.
SENSOR_STATUS_G8_TRAINING_DONE_ERROR	Error: G8 sensor training done error.
TL_STATUS_WARNING_CXP_LINK_CONFIGURATION	Warning: Cxp link configuration invalid.

4.33 Device Log Level

Name	DeviceLogLevel	Standard
Description	Selects the current log level.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	See enum entry table below.	
Default value	Info	
Availability	ALL	
Notes	-	
Error behavior	-	

Device Log Level Enum Entries:

Name	Description
Error	Only Error logging will be shown.
Warning	Only Warning logging will be shown.
Info	Only Info logging will be shown.
Verbose	Only Verbose logging will be shown.
Debug	Only Debug logging will be shown.

4.34 Device TL Type

Name	DeviceTLType	Standard
Description	Transport Layer type of the device.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entry table below.	
Default value	GigEVision	
Availability	ALL	
Notes	-	
Error behavior	-	

Device TL Type Enum Entries:

Name	Description
GigEVision	GigE Vision

4.35 Device Link Selector

Name	DeviceLinkSelector	Standard
Description	Selects which link of the device to control.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	0	
Default value	0	
Availability	ALL	
Notes	-	
Error behavior	-	

4.36 Device Link Connection Count

Name	DeviceLinkConnectionCount[DeviceLinkSelector]	Standard
Description	Returns the number of physical connections of the device used by a particular Link.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.37 Device Link Speed

Name	DeviceLinkSpeed[DeviceLinkSelector]	Standard
Description	Indicates the speed of transmission negotiated on the specified link.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.38 Device Average Resolution – Not Available for AllPIXA-EVO

Name	DeviceAverageResolution	Custom
Description	Returns the average resolution in DPI (Dots Per Inch).	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Notes	Average resolution of the system in sensor direction. It is measured in factory and programmed to the device.	
Error behavior	-	

4.39 Device TL Version Major

Name	DeviceTLVersionMajor	Standard
Description	Major version of the Transport Layer of the device.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.40 Device TL Version Minor

Name	DeviceTLVersionMinor	Standard
Description	Minor version of the Transport Layer of the device.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.41 Device TL Version Sub Minor

Name	DeviceTLVersionSubMinor	Standard
Description	Sub-minor version of the Transport Layer of the device.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.42 Device Registers Endianness

Name	DeviceRegistersEndianness	Standard
Description	Endianness of the registers of the device.	
Interface	Enumeration	

Access mode	Read only
Adjustable while grabbing	-
Value range	See enum entry table below.
Default value	Big
Availability	ALL
Notes	-
Error behavior	-

Device Registers Endianness Enum Entries:

Name	Description
<i>Little</i>	Device's registers are little Endian
<i>Big</i>	Device's registers are big Endian

4.43 Device Character Set

Name	DeviceCharacterSet	Standard
Description	Character set used by the strings of the device's bootstrap registers.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entry table below.	
Default value	UTF8	
Availability	ALL	
Notes	-	
Error behavior	-	

Device Character Set Enum Entries:

Name	Description
<i>UTF8</i>	UTF 8

4.44 Device Event Channel Count

Name	DeviceEventChannelCount	Standard
Description	Indicates the number of event channels supported by the device.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.45 Device Stream Channel Count

Name	DeviceStreamChannelCount	Standard
Description	Indicates the number of streaming channels supported by the device.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

4.46 Device Link Heartbeat Timeout

Name	DeviceLinkHeartbeatTimeout	Standard
Description	Controls the current heartbeat timeout of the specific Link.	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥ 500000.0	
Default value	-	
Availability	ALL	
Notes	The unit is micro-seconds (μ s)	
Error behavior	-	

4.47 Device Stream Channel Endianness

Name	DeviceStreamChannelEndianness	Standard
Description	Endianness of multi-pixel data for this stream.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entry table below.	
Default value	Little	
Availability	ALL	
Notes	-	
Error behavior	-	

Device Stream Channel Endianness Enum Entries:

Name	Description
<i>Little</i>	Stream channel data is little Endian.
<i>Big</i>	Stream channel data is big Endian.

4.48 Timestamp Reset

Name	TimestampReset	Standard
Description	Resets the current value of the device timestamp counter.	
Interface	Command	
Access mode	Write only	
Adjustable while grabbing	Yes	
Value range	1	
Default value	1	
Availability	ALL	
Notes	-	
Error behavior	-	

4.49 Timestamp Latch

Name	TimestampLatch	Standard
Description	Latches current timestamp counter into TimestampLatchValue .	
Interface	Command	
Access mode	Write only	
Adjustable while grabbing	Yes	
Value range	1	
Default value	1	
Availability	ALL	
Notes	-	
Error behavior	-	

4.50 Timestamp Latch Value

Name	TimestampLatchValue	Standard
Description	Returns the latched value of the timestamp counter.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

5 Image Format Control

The parameters of this group describe how to influence and determine the image size and format. It also provides the necessary information to acquire and to display the image data. It assumes that the device has a source of data that generates a single rectangular image. This image can be entirely or partially streamed out of the device using one or many Region of interest (ROI).




Image is taken from SFNC 2.4 p. 109

The sensor provides **Sensor Width** pixels.

The parameters **ReverseX** can be used to flip the image along the X-axis. The flipping is done before the Region of interest is applied.

Within the shrunk image the user can set a Region of interest using the parameters **OffsetX**, **Width**, and **Height**. The resulting image has **Width** time **Height** pixels. **OffsetX** refers to the upper left corner of the image which has the coordinate (0, 0).

The parameters **Region Selector** and **Region Mode** can be used to select and control each Region individually. All measures are given in pixel. As a result, the values should not change if the **Pixel Format** changes. For monochrome cameras, each pixel corresponds to a single gray value.

For color cameras in RGB mode each pixel corresponds to one RGB triplet.

The parameter **Height** describes the height of the image in lines.

5.1 Sensor Width

Name	SensorWidth	Standard
Description	Effective width of the sensor in pixels.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	Depends on the built-in sensor.	
Default value	1	
Availability	ALL	
Notes	-	
Error behavior	-	

5.2 Sensor Height

Name	SensorHeight	Standard
Description	Effective height of the sensor in pixels.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	1	
Default value	1	
Availability	ALL	
Notes	-	
Error behavior	-	

5.3 Sensor Color Filter

Name	SensorColorType	Custom
Description	Specifies the sensor color filter.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entry table below.	
Default value	-	
Availability	-	
Notes	Only the display name is changed to sensor color filter for backward compatibility.	
Error behavior	-	

Sensor Color Filter Enum Entries:

Name	Description
White	White
RGBW	Red, Green, Blue and White
RGBWIr	Red, Green, Blue, White and Infrared
RGBIr	Red, Green, Blue and Infrared

5.4 Width Max

Name	WidthMax	Standard
Description	Maximum width of the image (in pixels). The dimension is calculated after horizontal binning, decimation or any other function changing the horizontal dimensions of the image.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	>0	
Default value	SensorWidth	
Availability	ALL	
Notes	-	
Error behavior	-	

5.5 Height Max

Name	HeightMax	Standard
Description	Maximum height of the image (in pixels). This dimension is calculated after vertical binning, decimation or any other function changing the vertical dimensions of the image.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	>0	
Default value	-	
Availability	ALL	
Notes	The maximum height is 1015811 lines.	
Error behavior	-	

5.6 Region Selector

Name	RegionSelector	Standard
Description	Selects the Region of interest to control.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	See enum entry table below.	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

Region Selector Enum Entries:

Name	Description
Region1	Selected feature will control the region 1
Region2	Selected feature will control the region 2. <i>For ax_dsxge only.</i>

5.7 Region Mode

Name	RegionMode[RegionSelector]	Standard
Description	Controls whether the selected Region of interest is active and streaming.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entry table below.	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Region Mode Enum Entries:

Name	Description
Off	Disable usage of the Region. For ax_dsxge only
On	Enable usage of the Region.

5.8 Width

Name	Width[RegionSelector]	Standard
Description	Width of the Image provided by the device (in pixels).	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[128 , Width Max]	
Default value	WidthMax	
Availability	ALL	
Notes	The width value must be a multiple of eight for RGB.	
Error behavior	See the device error code documentation.	

5.9 Height

Name	Height[RegionSelector]	Standard
Description	Height of the Image provided by the device (in pixels).	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[16 , Height Max]	
Default value	1024	
Availability	ALL	
Notes	This parameter influences the value range of AcquisitionFrameRate . Please read the AcquisitionFrameRate feature documentation for further details.	
Error behavior	See the device error code documentation.	

5.10 Offset X

Name	OffsetX[RegionSelector]	Standard
Description	Horizontal offset from the origin to the region of interest (in pixels).	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	≥0	
Default value	0	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

5.11 Sensor Region Offset X

Name	SensorRegionOffsetX[RegionSelector]	Custom
Description	Horizontal offset from the origin to the region of interest in sensor coordinates (pixels).	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	No	
Value range	≥ 0	
Default value	0	
Availability	ALL	
Notes	The display name is just Sensor Offset X.	
Error behavior	See the device error code documentation.	

5.12 Sensor Region Width

Name	SensorRegionWidth[RegionSelector]	Custom
Description	Width of the selected region of interest in sensor coordinates (in pixels).	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	No	
Value range	≥ 0	
Default value	0	
Availability	ALL	
Notes	The display name is just Sensor Width. The feature resides below the Region Selector. There is a SensorWidth feature defining the sensor's full width which resides in the top level of the image format control category.	
Error behavior	See the device error code documentation.	

5.13 Binning Horizontal

Name	BinningHorizontal	Standard
Description	Number of horizontal photo-sensitive cells to combine. This increases the intensity (or signal-to-noise ratio) of the pixels and reduces the horizontal resolution (width) of the image.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	Variant	Value Range
	ax_X	1,2,4,8,16
	g8_X	1,2,4,8,16
Default value	1 – Indicates that no horizontal binning is performed by the camera.	
Availability	ALL	
Notes	<p>If you change this parameter, the Region OffsetX and Width is scaled according to the binning value.</p> <p>Please check these parameters after adapting Binning Horizontal.</p> <p>When Width is changed, the maximum BinningHorizontal value may be reduced and limited to that value. This is done to ensure that Width value doesn't go below the minimum width value.</p>	
Error behavior	See the device error code documentation.	

5.14 Decimation Horizontal Float

Name	DecimationHorizontalFloat	Custom
Description	<p>This is the same feature as DecimationHorizontal as defined in the SFNC. However, it supports float values for decimation.</p> <p>Horizontal sub-sampling of the image. This reduces the horizontal resolution (width) of the image by the specified horizontal decimation factor.</p>	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[0.5 , 3.999]	
Default value	1.0	
Availability	g8_X	
Notes	<p>A value of 1 indicates that the camera performs no horizontal decimation. If you change this parameter, the Region OffsetX and Width are scaled according to the decimation value. Please check these parameters after adapting Decimation Horizontal.</p> <p>When Width is changed, the maximum DecimationHorizontalFloat value may be reduced and limited to that value. This is done to ensure that Width value doesn't go below the minimum width value.</p>	
Error behavior	See the device error code documentation.	

5.15 Reverse X

Name	ReverseX	Standard
Description	Flip the image sent by the device horizontally.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	True – Horizontally flipped image False – Normal Image	
Default value	False	
Availability	ALL	
Notes	This feature is effective only if Test Pattern is set to Off .	
Error behavior	-	

5.16 Pixel Format

Name	PixelFormat	Standard
Description	Format of the pixels provided by the device. It represents all the information provided by PixelFormatSize , PixelFormatColorFilter combined in a single feature.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entry table below.	
Default value	Variant	Value
	Color Camera	RGB8
	Mono Camera	Mono8
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Pixel Format Enum Entries:

Name	Availability	Description
Mono8	ALL	8 bits per pixel Mono

Mono10	X_cxp , X_dxge , p6_nxge	10 bits per pixel Mono unpacked
Mono12	X_cxp , X_dxge , p6_nxge	12 bits per pixel Mono unpacked
RGB8	ALL	24 bits per pixel RGB linear memory
RGB10	X_cxp , X_dxge , p6_nxge	RGB at 10bit unpacked
RGB12	X_cxp , X_dxge , p6_nxge	RGB at 12bit unpacked
RGB10p32	-	32-bits per pixel RGB format. The bit depth is 10-bits. Please check the PFNC (Pixel Format Naming Convention) for more details – Not available for g8_dxge packages!
BGR8	X_dxge ax_dsxge	24 bits per pixel BGR linear memory
RGBa8	g8_X , p6_nxge	32 bits per pixel RGBa linear memory. Component 'a' contains Infrared (Ir) or White(W).
RGBa10	g8_X , p6_nxge	RGBa at 10bit unpacked. Component 'a' contains Infrared (Ir) or White(W).
RGBa12	g8_X , p6_nxge	RGBa at 12bit unpacked. Component 'a' contains Infrared (Ir) or White(W).

5.17 Pixel Color Filter

Name	PixelColorFilter	Standard
Description	Selects the type of color filter that is applied to an image.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entry table below.	
Default value	Variant	Value
	ax_X	RGB
	g8_X	RGBIr
	p6_nxge	RGBIr
	p16_cxp	RGBIr
	ALL (Mono Camera)	White
Availability	ALL	
Notes	For mono cameras the pixel color filter will be White only.	
Error behavior	See the device error code documentation.	

Pixel Color Filter Enum Entries:

Name	Availability	Description
RGB	ax_X	Three color planes RGB at the sensor is selected
RGBIr	g8_X , p6_nxge , p16_cxp	Four color planes RGB and Infrared at the sensor is selected. Infrared is transmitted as component 'a' in the pixel format RGBa8, RGBa10 and RGBa12.
RGBW	p6_nxge , p16_cxp	Four color planes RGB and White at the sensor is selected. White is transmitted as component 'a' in the pixel format RGBa8, RGBa10 and RGBa12.
White	g8_X	Only White plane at the sensor is selected

5.18 Infoblock Mode

Name	InfoBlockMode	Standard
Description	The info block can be enabled for the first line, for each line or for first and each line.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	Enum entries table below.	
Default value	Infoblock off	
Availability	ALL	
Notes	So far not all entries are working. There may be even differences between variants of allPIXAevo.	
Error behavior	none	

Info block Mode Entries:

Name	Description
Off	No info block is displayed in the image.
Firstline	First line Info block which is in line 0 of each transmitted image is displayed.
Eachline	In each line from line 0 of each transmitted image the Each line info block is displayed.
FirstandEachLine	First and each line info block are displayed in each image. In case both FirstlineandEach line info block are active, Eachline info block is always displayed from line 1 in every transmitted image!

First line info block format

Not in time block format																								
Pixel	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
Line 0	MARKER	SERIAL NUMBER				MARKER	IMAGE COUNT		EXPOSURE TIME		MARKER	LINE TIME			ENCODER CLOCKS			ERROR CODE		TIME STAMP			MARKER	

Information	Channel Content ¹	Description												
MARKER	DIVERSE	Markers are used to mark the info block with red pixels. <table><tr><th>Color</th><th>Red</th><th>Green</th><th>Blue</th></tr><tr><th>Value</th><td>255@8bit</td><td>0@8bit</td><td>0@8bit</td></tr></table>	Color	Red	Green	Blue	Value	255@8bit	0@8bit	0@8bit				
Color	Red	Green	Blue											
Value	255@8bit	0@8bit	0@8bit											
SERIAL NUMBER	SAME	These pixels encode the serial number of the camera. <table><tr><th>Byte₃</th><th>Byte₂</th><th>Byte₁</th><th>Byte₀</th></tr><tr><td>P_{X1}</td><td>P_{X2}</td><td>P_{X3}</td><td>P_{X4}</td></tr><tr><td colspan="2">SN 1ST PART</td><td colspan="2">SN 2ND PART</td></tr></table>	Byte ₃	Byte ₂	Byte ₁	Byte ₀	P _{X1}	P _{X2}	P _{X3}	P _{X4}	SN 1 ST PART		SN 2 ND PART	
Byte ₃	Byte ₂	Byte ₁	Byte ₀											
P _{X1}	P _{X2}	P _{X3}	P _{X4}											
SN 1 ST PART		SN 2 ND PART												
IMAGE COUNT	SAME	These pixels encode the image count of the camera. <table><tr><th>Byte₁</th><th>Byte₀</th></tr><tr><td>P_{X6}</td><td>P_{X7}</td></tr><tr><td colspan="2">IMAGE COUNT</td></tr></table>	Byte ₁	Byte ₀	P _{X6}	P _{X7}	IMAGE COUNT							
Byte ₁	Byte ₀													
P _{X6}	P _{X7}													
IMAGE COUNT														

EXPOSURE TIME	SAME	<p>This is the current Exposure Time in camera internal clock cycles.</p> <table><tr><td>Byte₁</td><td>Byte₀</td></tr><tr><td>PX₈</td><td>PX₉</td></tr><tr><td colspan="2">EXPOSURE TIME CLOCKS</td></tr></table> <p>To decode the exposure time, use the following formula:</p> $ExposureTime = \frac{EXPOURE_TIME_CLOCKS}{f_a}$ <table><tr><td>Camera Variant</td><td>f_a in MHz</td></tr><tr><td>ax_X</td><td>50</td></tr><tr><td>g8_X</td><td>80</td></tr></table>	Byte ₁	Byte ₀	PX ₈	PX ₉	EXPOSURE TIME CLOCKS		Camera Variant	f _a in MHz	ax_X	50	g8_X	80							
Byte ₁	Byte ₀																				
PX ₈	PX ₉																				
EXPOSURE TIME CLOCKS																					
Camera Variant	f _a in MHz																				
ax_X	50																				
g8_X	80																				
LINE TIME	SAME	<p>This is the current line time in camera internal clock cycles.</p> <table><tr><td>Byte₂</td><td>Byte₁</td><td>Byte₀</td></tr><tr><td>PX₁₁</td><td>PX₁₂</td><td>PX₁₃</td></tr><tr><td colspan="3">LINE TIME CLOCKS</td></tr></table> <p>To decode the line time, use the following formula:</p> $LineTime = \frac{LINE_TIME_CLOCKS}{f_t}$ <p>Up to package 2.1.1</p> <table><tr><td>Camera Variant</td><td>f_t in MHz</td></tr><tr><td>ax_X</td><td>75</td></tr><tr><td>g8_X</td><td>80</td></tr></table> <p>Package 2.1.2 and later:</p> <table><tr><td>Camera Variant</td><td>f_t in MHz</td></tr><tr><td>ALL</td><td>100</td></tr></table>	Byte ₂	Byte ₁	Byte ₀	PX ₁₁	PX ₁₂	PX ₁₃	LINE TIME CLOCKS			Camera Variant	f _t in MHz	ax_X	75	g8_X	80	Camera Variant	f _t in MHz	ALL	100
Byte ₂	Byte ₁	Byte ₀																			
PX ₁₁	PX ₁₂	PX ₁₃																			
LINE TIME CLOCKS																					
Camera Variant	f _t in MHz																				
ax_X	75																				
g8_X	80																				
Camera Variant	f _t in MHz																				
ALL	100																				
ENCODER CLOCKS	SAME	<p>This is a 32-bit counter starting at power on with 0. These counts either the line trigger (LineStart) or Encoder pulses depending on the selected mode.</p> <table><tr><td>Byte₃</td><td>Byte₂</td><td>Byte₁</td><td>Byte₀</td></tr><tr><td>PX₁₄</td><td>PX₁₅</td><td>PX₁₆</td><td>PX₁₇</td></tr><tr><td colspan="4">ENCODER CLOCKS</td></tr></table>	Byte ₃	Byte ₂	Byte ₁	Byte ₀	PX ₁₄	PX ₁₅	PX ₁₆	PX ₁₇	ENCODER CLOCKS										
Byte ₃	Byte ₂	Byte ₁	Byte ₀																		
PX ₁₄	PX ₁₅	PX ₁₆	PX ₁₇																		
ENCODER CLOCKS																					
ERROR CODE	UNUSED	CURRENTLY UNUSED PRESET WITH ZERO																			
TIMESTAMP	SAME	<p>Timestamp starts counting from boot.</p> <table><tr><td>Byte₂</td><td>Byte₁</td><td>Byte₀</td></tr><tr><td>PX₁₉</td><td>PX₂₀</td><td>PX₂₁</td></tr><tr><td colspan="2">SECONDS</td><td>$\frac{Ms^1}{4}$</td></tr></table> <p>¹MS= Milliseconds</p> <p>To achieve the milliseconds part of the timestamp the Content of PX₂₁ must be multiplied by four.</p>	Byte ₂	Byte ₁	Byte ₀	PX ₁₉	PX ₂₀	PX ₂₁	SECONDS		$\frac{Ms^1}{4}$										
Byte ₂	Byte ₁	Byte ₀																			
PX ₁₉	PX ₂₀	PX ₂₁																			
SECONDS		$\frac{Ms^1}{4}$																			

¹ **SAME** indicates that all color channels contain the same value. It is sufficient to evaluate a single color component.

DIVERSE indicates different values for individual color channels which should be taken into account when composing the information.

Each Line info block format

Pixel	0	1	2	3	4	5	6	7	8	9
RED	MARKER	ERROR CODE	SPEED2 HIGH	ENCODER CLOCKS	NEXT LINE POSITION	TIME STAMP	UNSUPPORTED	UNSUPPORTED	LINE STATUS/SCAN-DIR	MARKER
GREEN	CONTINUOUS LINE COUNT	LINE COUNT	LINE TIME							
BLUE										

Information	Channel Content ¹	Description												
CONTINUOUS LINE COUNT	DIVERSE	<p>This is the continuous line count across image boundaries.</p> <table><tr><td>-</td><td>Byte₁</td><td>Byte₀</td></tr><tr><td>PX₀Red</td><td>PX₀Green</td><td>PX₀Blue</td></tr><tr><td></td><td colspan="2">CONT LINE COUNT</td></tr></table>	-	Byte ₁	Byte ₀	PX ₀ Red	PX ₀ Green	PX ₀ Blue		CONT LINE COUNT				
-	Byte ₁	Byte ₀												
PX ₀ Red	PX ₀ Green	PX ₀ Blue												
	CONT LINE COUNT													
ERROR CODE	DIVERSE	<p>This is an error code. <i>Currently not used!</i></p> <table><tr><td>Byte₀</td><td>-</td><td>-</td></tr><tr><td>PX₁Red</td><td>PX₁Green</td><td>PX₁Blue</td></tr><tr><td>ERROR CODE</td><td colspan="2"></td></tr></table>	Byte ₀	-	-	PX ₁ Red	PX ₁ Green	PX ₁ Blue	ERROR CODE					
Byte ₀	-	-												
PX ₁ Red	PX ₁ Green	PX ₁ Blue												
ERROR CODE														
LINE COUNT	DIVERSE	<p>This is a line counter starting from image start.</p> <table><tr><td>-</td><td>Byte₁</td><td>Byte₀</td></tr><tr><td>PX₁Red</td><td>PX₁Green</td><td>PX₁Blue</td></tr><tr><td></td><td colspan="2">LINE COUNT</td></tr></table>	-	Byte ₁	Byte ₀	PX ₁ Red	PX ₁ Green	PX ₁ Blue		LINE COUNT				
-	Byte ₁	Byte ₀												
PX ₁ Red	PX ₁ Green	PX ₁ Blue												
	LINE COUNT													
SPEED2HIGH	DIVERSE	<p>This bit is set if the line trigger exceeds the cameras maximum line rate. This is Bit7 of PX₁Red.</p> <table><tr><td>BIT7</td><td>BIT6</td><td>...</td><td>BIT0</td></tr><tr><td colspan="4">PX₂Red</td></tr><tr><td>SPEED2HIGH</td><td colspan="3">-</td></tr></table>	BIT7	BIT6	...	BIT0	PX ₂ Red				SPEED2HIGH	-		
BIT7	BIT6	...	BIT0											
PX ₂ Red														
SPEED2HIGH	-													

LINE TIME	DIVERSE	<p>This is the current measured line time in camera internal clock cycles.</p> <table><tr><td>BIT7...4</td><td>BIT3...0</td><td>Byte₁</td><td>Byte₀</td></tr><tr><td colspan="2">PX2Red</td><td>PX2Green</td><td>PX2Blue</td></tr><tr><td colspan="4">LINE TIME CLOCKS</td></tr></table> <p>To decode the line time, use the following formula:</p> $LineTime = \frac{LINE_TIME_CLOCKS}{f_t}$ <p>Up to package 2.1.1</p> <table><tr><td>Camera Variant</td><td>f_t in MHz</td></tr><tr><td>ax X</td><td>75</td></tr><tr><td>g8 X</td><td>80</td></tr></table> <p>Package 2.1.2 and later:</p> <table><tr><td>Camera Variant</td><td>f_t in MHz</td></tr><tr><td>ALL</td><td>100</td></tr></table>	BIT7...4	BIT3...0	Byte ₁	Byte ₀	PX2Red		PX2Green	PX2Blue	LINE TIME CLOCKS				Camera Variant	f _t in MHz	ax X	75	g8 X	80	Camera Variant	f _t in MHz	ALL	100
BIT7...4	BIT3...0	Byte ₁	Byte ₀																					
PX2Red		PX2Green	PX2Blue																					
LINE TIME CLOCKS																								
Camera Variant	f _t in MHz																							
ax X	75																							
g8 X	80																							
Camera Variant	f _t in MHz																							
ALL	100																							
ENCODER CLOCKS	DIVERSE	<p>This is a 24-bit counter starting at power on with 0. These counts either the line trigger (LineStart) or Encoder pulses depending on the selected mode.</p> <table><tr><td>Byte₂</td><td>Byte₁</td><td>Byte₀</td></tr><tr><td>PX3Red</td><td>PX3Green</td><td>PX3Blue</td></tr><tr><td colspan="3">ENCODER CLOCKS</td></tr></table>	Byte ₂	Byte ₁	Byte ₀	PX3Red	PX3Green	PX3Blue	ENCODER CLOCKS															
Byte ₂	Byte ₁	Byte ₀																						
PX3Red	PX3Green	PX3Blue																						
ENCODER CLOCKS																								
NEXT LINE TRIGGER POSITION	DIVERSE	<p>Information of the next line trigger position in encoder pulses (only at encoder mode). The calculated position is shown in a 16.8b value. If encoder averaging is used, the value is divided by the average size. At a slave camera, this field has the value zero.</p> <table><tr><td>Byte₂</td><td>Byte₁</td><td>Byte₀</td></tr><tr><td>PX4Red</td><td>PX4Green</td><td>PX4Blue</td></tr><tr><td colspan="3">NEXT LT POS RAW</td></tr></table> <p>To achieve the actual value, follow this formula:</p> $NextLTPos = \frac{NEXT_LT_POS_RAW}{256}$	Byte ₂	Byte ₁	Byte ₀	PX4Red	PX4Green	PX4Blue	NEXT LT POS RAW															
Byte ₂	Byte ₁	Byte ₀																						
PX4Red	PX4Green	PX4Blue																						
NEXT LT POS RAW																								
TIMESTAMP	SAME	<p>Timestamp starts counting from boot.</p> <table><tr><td>Byte₂</td><td>Byte₁</td><td>Byte₀</td></tr><tr><td>PX5Red</td><td>PX5Green</td><td>PX5Blue</td></tr><tr><td colspan="2">SECONDS</td><td>$\frac{MS^1}{4}$</td></tr></table> <p>¹MS= Milliseconds</p> <p>To achieve the milliseconds part of the timestamp the Content of <i>Px5Blue</i> must be multiplied by four.</p>	Byte ₂	Byte ₁	Byte ₀	PX5Red	PX5Green	PX5Blue	SECONDS		$\frac{MS^1}{4}$													
Byte ₂	Byte ₁	Byte ₀																						
PX5Red	PX5Green	PX5Blue																						
SECONDS		$\frac{MS^1}{4}$																						

LINE STATUS	DIVERSE	<p>This entry reflects the logical level of the input lines before LineInverter. If LineInverter is enabled the value reflected by the Line Status feature is inverse.</p> <table><tr><th>Line</th><th>Pixel Bit</th></tr><tr><td>Line1</td><td>Px8Green0</td></tr><tr><td>Line2</td><td>Px8Green1</td></tr><tr><td>Line3</td><td>Px8Green2</td></tr><tr><td>Line4</td><td>Px8Green4</td></tr><tr><td>Line5</td><td>Px8Green5</td></tr><tr><td>Line6</td><td>Px8Green6</td></tr><tr><td>Line7</td><td>Px8Green7</td></tr><tr><td>Line9</td><td>Px8Red0</td></tr><tr><td>Line10</td><td>-</td></tr></table>	Line	Pixel Bit	Line1	Px8Green0	Line2	Px8Green1	Line3	Px8Green2	Line4	Px8Green4	Line5	Px8Green5	Line6	Px8Green6	Line7	Px8Green7	Line9	Px8Red0	Line10	-
Line	Pixel Bit																					
Line1	Px8Green0																					
Line2	Px8Green1																					
Line3	Px8Green2																					
Line4	Px8Green4																					
Line5	Px8Green5																					
Line6	Px8Green6																					
Line7	Px8Green7																					
Line9	Px8Red0																					
Line10	-																					
SCAN-DIR	DIVERSE	<p>The scan direction</p> <table><tr><th>Direction</th><th>Value</th></tr><tr><td>Forward</td><td>0</td></tr><tr><td>Backward</td><td>1</td></tr></table> <table><tr><th>Entry</th><th>Pixel Bit</th></tr><tr><td>Scan Direction</td><td>Px8Blue6</td></tr></table>	Direction	Value	Forward	0	Backward	1	Entry	Pixel Bit	Scan Direction	Px8Blue6										
Direction	Value																					
Forward	0																					
Backward	1																					
Entry	Pixel Bit																					
Scan Direction	Px8Blue6																					

SAME indicates that all color channels contain the same value. It is sufficient to evaluate a single color component.

DIVERSE indicates different values for individual color channels which should be taken into account when composing the information.

5.19 Test Pattern Generator Selector

Name	TestPatternGeneratorSelector	Standard
Description	Selects which test pattern generator is controlled by the TestPattern feature.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entry table below.	
Default value	ImageProcessing	
Availability	ALL	
Notes	-	
Error behavior	-	

Test Pattern Generator Selector Enum Entries:

Name	Description
ImageProcessing	TestPattern feature controls the Image Processing test pattern generator.

5.20 Test Pattern

Name	TestPattern[TestPatternGeneratorSelector]	Standard
Description	Selects the type of test pattern that is generated by the device as image source.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entry table below.	
Default value	Off	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Test Pattern Generator Selector Enum Entries:

Name	Description
Off	Image is coming from the sensor.
GreyHorizontalRamp	Image is filled horizontally with pixels that go from the darkest possible value to the brightest.
GreyVerticalRamp	Image is filled vertically with pixels that go from the darkest possible value to the brightest.
GreyHorizontalRampMoving	Image is filled horizontally with pixels that go from the darkest possible value to the brightest and that move horizontally from left to right at each frame.
GreyVerticalRampMoving	Image is filled vertically with lines that go from the darkest possible value to the brightest and that move vertically from top to bottom at each frame.
ColorRamps	Horizontal ramp in red color channel. Vertical and horizontal ramp in green color channel. Vertical ramp in blue color channel.
TogglingPixels	Vertically and horizontally neighbored pixels have the inverse intensity value from each other.
PinStripes	Fixed pin stripe pattern with configurable background. The background is configurable with the test pattern value feature.

5.21 Test Pattern Value

Name	TestPatternValue [TestPatternGeneratorSelector]	Custom
Description	Test-Pattern-specific value that influences the appearance of the generated image.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[0 – 4095]	
Default value	64	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

6 Acquisition Control

6.1 Acquisition Mode

Name	AcquisitionMode	Standard
Description	Sets the acquisition mode of the device. It defines mainly the number of frames to capture during an acquisition and the way the acquisition stops.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	Continuous	
Availability	ALL	
Notes	-	
Error behavior	-	

Acquisition Mode Enum Entries:

Name	Description
Continuous	Frames are captured continuously until stopped with the AcquisitionStop command.
SingleFrame	One Frame is captured.

6.2 Acquisition Start

Name	AcquisitionStart	Standard
Description	Starts the Acquisition of the device. The number of frames captured is specified by AcquisitionMode .	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	1	
Default value	1	
Availability	ALL	
Notes	-	
Error behavior	Success is returned on successful start otherwise some error code. See the device error code documentation.	

6.3 Acquisition Stop

Name	AcquisitionStop	Standard
Description	Stops the Acquisition of the device at the end of the current Frame.	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[0, 1] For writing only command value 1 is supported.	
Default value	1	
Availability	ALL	
Notes	The command will return immediately however it is not finished and will continue execution in background. As soon as the command value changes from 1 to 0 the command has finished. Features locked by TLPParamsLocked can be modified first after AcquisitionStop has finished execution completely.	
Error behavior	See the device error code documentation.	

6.4 Acquisition Abort

Name	AcquisitionAbort	Standard
Description	Aborts the Acquisition immediately.	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[0, 1] For writing only command value 1 is supported.	
Default value	1	
Availability	ALL	
Notes	When command is executed, it aborts the current frame immediately without completing the current frame.	
Error behavior	See the device error code documentation.	

6.5 Frame Count

Name	FrameCount	Standard
Description	Indicates the number of frames captured during an acquisition period.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	[0, 65535]	
Default value	1	
Availability	ALL	
Notes	This feature value will be resetted during an UserSet load.	
Error behavior	-	

6.6 Exposure Time Mode

Name	ExposureTimeMode	Standard
Description	Sets the configuration mode of the Exposure Time feature.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	Common	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Exposure Time Mode Enum Entries:

Name	Availability	Description
Common	ALL	The exposure time is common to all the color components.
Individual	g8_X	The exposure time is individual for each color component.

6.7 Exposure Time Selector

Name	ExposureTimeSelector	Standard
Description	Selects which exposure time is controlled by the Exposure Time feature. This allows for independent control over the exposure components.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	Common	

Availability	ALL
Notes	-
Error behavior	See the device error code documentation.

Exposure Time Selector Enum Entries:

Name	Availability	Description
Common	ALL	Selects the common ExposureTime.
White	g8_X	Selects the White ExposureTime.
Infrared	g8_X	Selects the Infrared ExposureTime.
Red	g8_X	Selects the Red ExposureTime.
Green	g8_X	Selects the Green ExposureTime.
Blue	g8_X	Selects the Blue ExposureTime.

6.8 Exposure Time

Name	ExposureTime[ExposureTimeSelector]	Standard
Description	This controls the duration during which the photosensitive cells are exposed to light.	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	Freerun: The exposure time must be smaller than the Acquisition Line Time plus an offset. LineTrigger On or Salve camera (MSMode is set to Slave): The exposure time must be smaller than the maximum exposure time. The minimum difference of Acquisition Line Time and ExposureTime are camera variant specific. Therefore, query the min and max entries of this feature.	
Default value	30	
Availability	ALL	
Notes	The unit is micro-seconds.	
Error behavior	See the device error code documentation.	

6.9 Acquisition Integration Time – Deprecated

Name	AcquisitionIntegrationTime	Custom
Description	Controls the integration time. (unit: micro-seconds)	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	See the value range of Exposure Time	
Default value	-	
Notes	This feature is deprecated please use Exposure Time instead.	
Error behavior	See the device error code documentation.	

6.10 Acquisition Integration Time Min – Deprecated

Name	AcquisitionIntegrationTimeMin	Custom
Description	Displays the minimum integration time. (unit: micro-seconds)	
Interface	Float	
Access mode	Read only	
Adjustable while grabbing	-	
Value range		
Default value	-	
Notes	This feature is deprecated; query the min and max values from Exposure Time instead.	

Error behavior	-
----------------	---

6.11 Acquisition Line Rate

Name	AcquisitionLineRate	Standard
Description	Controls the rate (in Hertz) at which the Lines in a Frame are captured.	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[(1 / Acquisition Line Time .Max), (1 / Acquisition Line Time .Min)]	
Default value	18.18 KHz	
Availability	ALL	
Notes	<p>This is the inverse of the Acquisition Line Time</p> <p>This feature is not available if MasterSlaveMode is configured as Slave or LedFlashEnable is enabled.</p>	
Error behavior	See the device error code documentation.	

6.12 Acquisition Line Rate Max – Deprecated

Name	AcquisitionLineRateMax	Custom
Description	This value is calculated by the camera. It limits the AcquisitionLineRate . The unit is Hertz.	
Interface	Float	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Notes	Please use the min and max node entries of the Acquisition Line Rate feature.	
Error behavior	-	

6.13 Acquisition Line Time

Name	AcquisitionLineTime	Custom
Description	Controls the processing time per scan line.	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	<p>The value range depends on:</p> <ul style="list-style-type: none"> - The transport layer configuration (Link configuration, packet size) - The region width - The Exposure Time - Reduction parameters Binning Horizontal , Decimation Horizontal Float <p>Query the min and max values of the acquisition line time feature to get the valid range for current setting.</p> <p>The exposure time always must be smaller than the line time: Range defined by exposure time: [Exposure Time + gap μs, 27900 μs]</p> <p>Gap = {ax_X = 1.5 ; g8_X = 2.0}</p> <p>Example range for gige-vision with one and two physical links connected.</p> <ol style="list-style-type: none"> 1. [37.431 μs, 13981 μs] – For single link (10Gbps) + ax_X 2. [30.881 μs, 13981 μs] – For dual link (20Gbps) + ax_X 3. [37.431 μs, 13107.1875 μs] – For single link (10Gbps) + g8_X 4. [30.881 μs, 13107.1875 μs] – For dual link (20Gbps) + g8_X 	

	¹ For Region Width : 15360, GevSCPSPacketSize : 8240 and AcquisitionFrameRate disabled.
Default value	55
Availability	ALL
Notes	<p>This is the inverse of the Acquisition Line Rate .</p> <p>If AcquisitionLineTime is set for higher values, then make sure to adopt image timeout to avoid timeout issues while grabbing.</p> <p>This parameter influences the value range of AcquisitionFrameRate. Please read the AcquisitionFrameRate feature documentation for further details.</p> <p>This feature is not available if MasterSlaveMode is configured as Slave or LedFlashEnable is enabled.</p>
Error behavior	See the device error code documentation.

6.14 Acquisition Line Time Min – Deprecated

Name	AcquisitionLineTimeMin	Custom
Description	Displays the minimum processing time per scan line in μs .	
Interface	Float	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	Exposure Time + 1.5 μs	
Default value	-	
Notes	Please query the min and max values of the Acquisition Line Time feature instead of using this feature.	
Error behavior	-	

6.15 Acquisition Frame Rate Enable

Name	AcquisitionFrameRateEnable	Standard
Description	Controls whether the AcquisitionFrameRate feature is writable and used to control the acquisition rate. Otherwise, the acquisition rate is implicitly controlled by the combination of other features such as AcquisitionLineTime .	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	True, False	
Default value	False	
Availability	ALL	
Notes	<p>The FrameActive and FrameStart triggers must be set to Off to enable this feature.</p> <p>This feature is not available if MasterSlaveMode is configured as Slave or LedFlashEnable is enabled.</p>	
Error behavior	See the device error code documentation.	

6.16 Acquisition Frame Rate

Name	AcquisitionFrameRate	Standard
Description	Controls the acquisition rate (in Hertz) at which the frames are captured.	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	<p>The value range depends on the line time as well as on the image height:</p> <p><i>Min Acquisition Frame Rate:</i></p> $Min = \frac{1}{AcquisitionLineTime * (ImageHeight + 32764)}$ <p><i>Max Acquisition Frame Rate:</i></p> $Max = \frac{1}{AcquisitionLineTime * ImageHeight}$	
Default value	10	
Availability	ALL	
Notes	<p>The Acquisition Frame Rate is based on the given AcquisitionLineTime even if a line trigger is used. Therefore, the real frame rate depends on the line trigger if this is used. The accuracy of this feature is limited.</p> <p>This feature is writeable only if AcquisitionFrameRateEnable is set to True.</p>	

	<p>Changing the image height or the acquisition line time influences the value range of the AcquisitionFrameRate. It may be that while these parameters are changed. The current value for the AcquisitionFrameRate gets out of range. In this case the real acquisition frame rate is clamped internally to the maximum possible frame rate.</p> <p>This feature is not available if MasterSlaveMode is configured as Slave or LedFlashEnable is enabled.</p>
Error behavior	See the device error code documentation.

6.17 Time Delay Integration Mode

Name	TimeDelayIntegrationMode	Custom
Description	Selects the Time Delay Integration Mode. This is not enabling or disabling the TDI, but choosing if high sensitivity or a high dynamic range is desired.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	HighSensitivity	
Availability	ALL	
Notes	<ul style="list-style-type: none"> - Enabling the TDI will be done by setting the TimeDelayIntegration feature to a value greater than 1 - The DSNU and PRNU data sets must be created with the desired TDI Mode. When changing the mode, the DSNU/PRNU references must be recreated. 	
Error behavior	See the device error code documentation.	

Exposure Time Mode Enum Entries:

Name	Availability	Description
HighSensitivity	ALL	The sensitivity will be increased in this TDI mode. This is achieved by summing up the lines.
HighSNR	ALL	Opposed to HighSensitivity this mode leads to a higher dynamic range. The SNR will be greater. This is achieved by averaging the lines.

6.18 Time Delay Integration

Name	TimeDelayIntegration	Custom
Description	Selects the number of photo-sensitive cells combined (average).	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[1, 3]	
Default value	1	
Availability	ALL	
Notes	This feature is valid and available for the Mono Camera only.	
Error behavior	See the device error code documentation.	

6.19 Master Slave Mode

Name	MasterSlaveMode	Custom
Description	Specifies the master slave mode of the camera.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	

Default value	Off
Availability	ALL
Notes	<p>Whenever the Master and Slave camera maximum operating line frequency differs make sure to configure the Master to operate in the lower speed. Otherwise, the images delivered by Slave may be corrupt.</p> <p>The camera's maximum line frequency may differ e.g., by different Width, Pixel Format, Decimation Horizontal Float, Binning Horizontal or Exposure Time parameter.</p> <p>To be sure about the setting check the maximum value of Acquisition Line Rate by querying it from the camera.</p> <p>The following features are not available if the mode is set to Slave or AutoSelect (Slave):</p> <ul style="list-style-type: none"> - TriggerSelector, TriggerMode, TriggerSource, TriggerActivation, TriggerDelayLines, TriggerDivider, TriggerSignalDetectionMode, ExtendLines, LineTime(Measured), LineTriggerStatus - AcquisitionLineTime - EncoderControl - LedFlashControl
Error behavior	See the device error code documentation.

Master Slave Mode Enum Entries:

Name	Description
Off	No master slave is selected.
Master	Selects the camera to be Master.
Slave	Selects the camera to be Slave.
AutoSelect	Automatically selects the camera to be either Master or Slave.
AutoSelect (Master)	This is available if AutoSelect is selected. If Line3 is in low level, then AutoSelect in Master mode.
AutoSelect (Slave)	This is available if AutoSelect is selected. If Line3 via pull-up(high level), then AutoSelect in Slave Mode.

6.20 Master Slave Interface - Deprecated

Name	MasterSlaveInterface MasterSlaveMode	Custom
Description	Specifies the interface type to be used for master/slave.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	External	
Availability	ALL	
Notes	<p>This feature is deprecated, use MasterSlaveSource, MasterSlaveAutoSelectSource and Digital IO configuration. It will be removed from package 3.0.0</p> <p>For External interface, Master – Line9 as output Slave – Line4 as input and Line9 as output</p>	
Error behavior	See the device error code documentation.	

Master Slave Interface Enum Entries:

Name	Description
External	Interface between master and slave camera is external(physical)
Internal	Interface between master and slave camera is internal

6.21 Master Slave Interface Enable - Deprecated

Name	MasterSlaveInterfaceEnable[MasterSlaveInterface]	Custom
Description	Enables the selected master/slave interface.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	True – Enables selected master/slave interface. False – Disables selected master/slave interface.	
Default value	False	
Availability	ALL	
Notes	This feature is deprecated, use MasterSlaveSource, MasterSlaveAutoSelectSource and Digital IO configuration. It will be removed from package 3.0.0	
Error behavior	See the device error code documentation.	

6.22 Master Slave Source

Name	MasterSlaveSource	Custom
Description	Specifies the source to be used for master/slave.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	Off	
Availability	ALL	
Notes	Only Line4 and Line11 are available for allPIXAEvo	
Error behavior	See the device error code documentation.	

Master Slave Source Enum Entries:

Name	Description
Line1	Specifies physical line (or pin) Line1 to use as source for the master slave signal.
Line2	Specifies physical line (or pin) Line2 to use as source for the master slave signal.
Line3	Specifies physical line (or pin) Line3 to use as source for the master slave signal.
Line4	Specifies physical line (or pin) Line4 to use as source for the master slave signal.
Line5	Specifies physical line (or pin) Line5 to use as source for the master slave signal.
Line6	Specifies physical line (or pin) Line6 to use as source for the master slave signal.
Line7	Specifies physical line (or pin) Line7 to use as source for the master slave signal.
Line8	Specifies physical line (or pin) Line8 to use as source for the master slave signal.
Line9	Specifies physical line (or pin) Line9 to use as source for the master slave signal.
Line10	Specifies physical line (or pin) Line10 to use as source for the master slave signal.
Line11	Specifies physical line (or pin) Line11 to use as source for the master slave signal.

6.23 AutoSelect Source

Name	MasterSlaveAutoSelectSource	Custom
Description	Specifies the source to be used for AutoSelect.	
Interface	Enumeration	

Access mode	Read/Write
Adjustable while grabbing	No
Value range	See enum entries table below.
Default value	Off
Availability	ALL
Notes	Only Line3 is available for allPIXAEvo
Error behavior	See the device error code documentation.

AutoSelect Source Enum Entries:

Name	Description
Line1	Specifies physical line (or pin) Line1 to use as source for the autoselect signal.
Line2	Specifies physical line (or pin) Line2 to use as source for the autoselect signal.
Line3	Specifies physical line (or pin) Line3 to use as source for the autoselect signal.
Line4	Specifies physical line (or pin) Line4 to use as source for the autoselect signal.
Line5	Specifies physical line (or pin) Line5 to use as source for the autoselect signal.
Line6	Specifies physical line (or pin) Line6 to use as source for the autoselect signal.
Line7	Specifies physical line (or pin) Line7 to use as source for the autoselect signal.
Line8	Specifies physical line (or pin) Line8 to use as source for the autoselect signal.
Line9	Specifies physical line (or pin) Line9 to use as source for the autoselect signal.

6.24 Slave DelayLines

Name	MasterSlaveDelayLines	Custom
Description	Specifies the delay in number of lines for the slave camera.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	The value range varies when led flash is enabled depending on the number of patterns. <ol style="list-style-type: none"> 1. [0 , 32764] – LedFlashEnable is disabled 2. [0, 32764] – LedFlashEnable is enabled and NumberOfPattern=1 3. [0, 16382] – LedFlashEnable is enabled and NumberOfPattern=2 4. [0, 10921] – LedFlashEnable is enabled and NumberOfPattern=3 5. [0, 8191] – LedFlashEnable is enabled and NumberOfPattern=4 	
Default value	0	
Availability	ALL	
Notes	This feature is valid and available only for the Slave Camera .	
Error behavior	See the device error code documentation.	

6.25 Acquisition Burst Frame Count

Name	AcquisitionBurstFrameCount	Standard
Description	Specifies the number of frames to acquire for each FrameBurstStart trigger	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[1 , AcquisitionBurstFrameCount Max]	
Default value	1	
Availability	ALL	

Notes	This feature is valid and available only for FrameBurstStart and if MasterSlaveMode is not configured as Slave.
Error behavior	See the device error code documentation.

6.26 Trigger Selector

Name	TriggerSelector	Standard
Description	Selects the type of trigger to configure.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	FrameStart	
Availability	ALL	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

Trigger Selector Enum Entries:

Name	Description
FrameStart	Selects a trigger starting the capture of one frame.
FrameActive	Selects a trigger controlling the duration of one frame.
FrameBurstStart	Selects a trigger starting of the bursts of frames in an acquisition.
LineStart	Selects a trigger starting the capture of one Line of a Frame.

6.27 Trigger Mode

Name	TriggerMode[TriggerSelector]	Standard
Description	Controls whether the selected trigger is active.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	Off	
Availability	ALL	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

Trigger Mode Enum Entries:

Name	Description
Off	Disables the selected trigger.
On	Enables the selected trigger.

6.28 Trigger Source

Name	TriggerSource[TriggerSelector]	Standard
Description	Specifies the internal signal or physical input Line to use as the trigger source.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See the enum entries for more information.	
Default value	-	
Availability	ALL	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

Trigger Source Enum Entries:

Name	Description	Notes
Encoder0	Specifies Encoder0 signal to use as internal source for the trigger.	This enum entry is valid and available only for LineStart
Line1	Specifies physical line (or pin) Line1 and associated I/O control block to use as external source for the trigger signal.	This enum entry is valid and available only for LineStart
Line2	Specifies physical line (or pin) Line2 and associated I/O control block to use as external source for the trigger signal.	This enum entry is valid and available only for Frame Trigger
Line3	Specifies physical line (or pin) Line3 and associated I/O control block to use as external source for the trigger signal.	This enum entry is valid and available for Frame or Line trigger
Line4	Specifies physical line (or pin) Line4 and associated I/O control block to use as external source for the trigger signal.	This enum entry is valid and available for Frame or Line trigger

6.29 Trigger Activation

Name	TriggerActivation[TriggerSelector]	Standard
Description	Specifies the activation mode of the trigger.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	-	
Availability	ALL	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

Trigger Activation Enum Entries:

Name	Description	Notes
RisingEdge	Specifies that the trigger is considered valid on the rising edge of the source signal.	This enum entry is valid and available only for LineStart or FrameStart or FrameBurstStart
FallingEdge	Specifies that the trigger is considered valid on the falling edge of the source signal.	This enum entry is valid and available only for FrameStart or FrameBurstStart
LevelHigh	Specifies that the trigger is considered valid if the level of the source signal is high.	This enum entry is valid and available only for FrameActive
LevelLow	Specifies that the trigger is considered valid if the level of the source signal is low.	This enum entry is valid and available only for FrameActive

6.30 Trigger DelayLines

Name	TriggerDelayLines[TriggerSelector]	Custom
Description	Specifies the delay in number of lines to apply after the trigger reception before activating it	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	The value range varies when led flash is enabled depending on the number of patterns. 1. [0 , 32764] – LedFlashEnable is disabled	

	2. [0, 32764] – LedFlashEnable is enabled and NumberOfPattern =1 3. [0, 16382] – LedFlashEnable is enabled and NumberOfPattern =2 4. [0, 10921] – LedFlashEnable is enabled and NumberOfPattern =3 [0, 8191] – LedFlashEnable is enabled and NumberOfPattern =4
Default value	0
Availability	ALL
Notes	This feature is valid and available only for FrameStart , FrameBurstStart and FrameActive . This feature is not available if MasterSlaveMode is configured as Slave.
Error behavior	See the device error code documentation.

6.31 Trigger Divider

Name	TriggerDivider[TriggerSelector]	Standard
Description	Specifies a division factor for the incoming line trigger pulses	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[1 , 256]	
Default value	1	
Availability	ALL	
Notes	This feature is valid and available only for LineStart and if MasterSlaveMode is not configured as Slave.	
Error behavior	See the device error code documentation.	

6.32 Trigger Signal Detection Mode

Name	TriggerSignalDetectionMode[TriggerSelector]	Custom
Description	Specifies the debounce type to be evaluated.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	FrameStart - PeakholderDetection FrameBurstStart - PeakholderDetection FrameActive – Debouncing4Lines	
Availability	ALL	
Notes	This feature is valid and available only for FrameStart , FrameBurstStart and FrameActive and if MasterSlaveMode is not configured as Slave.	
Error behavior	See the device error code documentation.	

Trigger Signal Detection Mode Enum Entries:

Name	Description
PeakholderDetection	Peakholder 15 lines
Debouncing4Clocks	Debouncing 4 clocks
Debouncing4Lines	Debouncing 4 lines
Debouncing60Lines	Debouncing 60 lines

6.33 Extend Lines

Name	FrameActiveExtendLines[TriggerSelector]	Custom
Description	Specifies the number of additional output lines for FrameActive .	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[0, 65535]	
Default value	0	
Availability	ALL	
Notes	This feature is valid and available only for FrameActive and if MasterSlaveMode is not configured as Slave.	
Error behavior	See the device error code documentation.	

6.34 Line Time (Measured)

Name	MeasuredLineTime[TriggerSelector]	Custom
Description	Measure the processing time per scan line during line/encoder trigger in us.	
Interface	Float	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	In freerun this feature holds the same value as AcquisitionLineTime . During LineStart mode 'ON', it displays the actual line trigger speed. But in both cases the maximum line time it can display is 13,107 us .	
Default value	-	
Availability	ALL	
Notes	This feature is valid and available only for LineStart and if MasterSlaveMode is not configured as Slave.	
Error behavior		

6.35 Line Trigger Status

Name	LineTriggerStatus[TriggerSelector]	Custom
Description	Display the line trigger status.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	-	
Availability	ALL	
Notes	This feature is valid and available only for LineStart and if MasterSlaveMode is not configured as Slave.	
Error behavior	-	

Line Trigger Status Enum Entries:

Name	Description
OK	OK
SpeedToHigh	Speed to high

7 Analog Control

7.1 Gain Selector

Name	GainSelector	Standard
Description	Selects which Gain is controlled by the Gain features.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	All – For color camera White – For mono camera	
Availability	ALL	
Notes	<p>The linear gain reflects the product of the analog and digital gain. Setting the linear gain will adapt the analog (if available) as well as the digital gain.</p> <p>The analog gain is not supported for all products. If the analog gain is not available, the digital gain is not displayed separately. In this case the linear gain reflects the digital gain value.</p> <p>If the gain is read while All/AnalogAll/DigitalAll is selected, an average of all available color channels depending on PixelFormat is returned. If the gain is written, the value is written to all color channels defined in PixelFormat. In case of using ColorToGrey the PixelFormat will be Mono but the color channels for reading and writing the gain value will be Red, Green and Blue.</p>	
Error behavior	See the device error code documentation.	

Gain Selector Enum Entries:

Name	Description
All	Selects linear gain of all available color channels.
Red	Selects linear gain red
Green	Selects linear gain green
Blue	Selects linear gain blue
White	Selects linear gain white
Infrared	Selects linear gain infrared
AnalogAll	Selects analog gain of all available color channels.
AnalogRed	Selects analog gain red
AnalogGreen	Selects analog gain green
AnalogBlue	Selects analog gain blue
AnalogWhite	Selects analog gain white
DigitalAll	Selects digital gain of all available color channels.
DigitalRed	Selects digital gain red
DigitalGreen	Selects digital gain green
DigitalBlue	Selects digital gain blue
DigitalWhite	Selects digital gain white

7.2 Gain

Name	Gain[GainSelector]	Standard
Description	This is an amplification factor applied to the video signal.	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	<p>The value range varies for different camera variants. Therefore, query the value range from the feature parameters (min/max entries)</p> <p>However, for the digital gain the value range is the same for all camera variants.</p> <p>LinearGain = [DigitalMin * AnalogMin, DigitalMax * AnalogMax] AnalogGain = <i>camera dependent</i> DigitalGain = [1.0 , 3.999]</p>	
Default value	1.0	
Availability	ALL	
Notes	<p>This feature is available for Gain Selector</p> <p>You should create new DSNU reference when changing analog gain.</p>	
Error behavior	See the device error code documentation.	

7.3 Gain Auto

Name	GainAuto[GainSelector]	Standard
Description	Sets the automatic gain control (AGC) mode. The exact algorithm used to implement AGC is device-specific.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Off	
Availability	ALL	
Notes	<p>This feature is available only if Gain Selector is All or White (White for Mono cameras)</p> <p>The status of automatic gain control is reflected in GainAutoStatus feature.</p> <p>When the GainAuto feature has changed its value to Off after performing the "Once" or "AdjustTargetValueToMaxVideo" calibration, please query GainAutoStatus to check whether the automatic gain control was successful.</p>	
Error behavior	See the device error code documentation.	

Gain Auto Enum Entries:

Name	Description
Off	Gain is user-controlled using Gain .
Once	Gain is automatically adjusted once by the device. Once it has converged, it automatically returns to the Off state.
Continuous	Gain is constantly adjusted by the device.
AdjustTargetValueToMaxVideo	<p>This process adjusts "Target value" for "GainControlRegion" that the resulting maximum video level fits to given "Target value". (see feature "Target value")</p> <p>Therefore, the Target value feature defines the target value for AdjustTargetValueToMaxVideo command but at the same time the command will adapt the same Target value feature.</p> <p>The adapted Target value will be the base for further GainAuto commands.</p> <p>Next to adapting the target values this command will perform <i>GainAuto Once</i> command implicitly.</p>

	After process has finished it automatically return to Off state.
--	-------------------------------------------------------------------------

7.4 Gain Auto Status

Name	GainAutoStatus	Standard
Description	Returns the state of the automatic gain control	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	Control off	
Availability	ALL	
Notes	-	
Error behavior	-	

Gain Auto Enum Entries:

Name	Description
ControlOff	No automatic gain control in progress.
ControlSuccessful	The automatic gain control was successfully performed.
ControlInProgress	The automatic gain control is in progress.
ControlStopped	Continuous gain control temporarily stopped. Gain stop control enabled; gain stop condition reached!
ReferenceTimeout	No reference data from the gain control region available! Camera might be in triggered mode. Probably there are no trigger pulses.
LowerGainLimit	Warning! The automatic gain control has reached lower gain limit!
UpperGainLimit	Warning! The automatic gain control has reached upper gain limit!
VideoLevelLowerLimit	Warning! Process " AdjustTargetValueToMaxVideo ", video level too low for target value adjustment
VideoLevelUpperLimit	Warning! Process " AdjustTargetValueToMaxVideo ", video level too high for target value adjustment
TargetValueOutOfRange	Warning! Process " AdjustTargetValueToMaxVideo ", adjusted target values are out of range

7.5 Synchronization Mode Enable

Name	GainAutoSyncModeEnable	Custom
Description	Controls whether the gain control reference values are taken synchronous to frame start or independent of frame start. In case of synchronous mode is activated only one reference per frame will be captured. In case of asynchronous mode is inactive the reference values are taken continuously from image data stream.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – Enables synchronization mode False – Disables synchronization mode	
Default value	False	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

7.6 Stop Control Enable

Name	GainAutoStopControlEnable	Custom
Description	Controls whether the gain auto continuous mode is limited according to the gain stop factor.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – Enables Gain Auto Stop Control False – Disables Gain Auto Stop Control	
Default value	False	
Availability	ALL	
Notes	-	
Error behavior	-	

7.7 Stop Factor

Name	GainAutoStopFactor	Custom
Description	The stop factor is used to limit the continuous gain control. The factor is multiplied with the target reference values. The result defines a threshold for the current reference values. Whenever the current reference values are equal or fall below the threshold, the continuous gain control is not performed till the current reference values are again larger than the threshold.	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[0.0 , 1.0]	
Default value	0.8	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

7.8 Gain Control Region Offset X

Name	GainControlRegionOffsetX	Custom
Description	Sets the offset x of the gain control region. (in pixel)	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[2 , (SensorWidth - GainControlRegionWidth)]	
Default value	(SensorWidth / 2) - 48	
Availability	ALL	
Notes	The minimal step of the value is one.	
Error behavior	See the device error code documentation.	

7.9 Gain Control Region Width

Name	GainControlRegionWidth	Custom
Description	Sets the width of the gain control region. (in pixels)	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[8 , 240]	
Default value	48	
Availability	ALL	
Notes	The step of the width is two.	
Error behavior	See the device error code documentation.	

7.10 Gain Control Region Offset Y

Name	GainControlRegionOffsetY	Custom
Description	Sets the offset y of the gain control region. (in pixels)	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	Frame trigger off: [3, Height – GainControlRegionHeight] Frame trigger on: [3 - TriggerDelayLines , 32767]	
Default value	3	
Availability	ALL	
Notes	This feature only takes effect if the Synchronization Mode Enable is set true!	
Error behavior	See the device error code documentation.	

7.11 Gain Control Region Height

Name	GainControlRegionHeight	Custom
Description	Sets the height of the gain control region. (in pixel)	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[2 , 240]	
Default value	32	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

7.12 Gain Control Region visible

Name	GainControlRegionVisible	Custom
Description	The borders of the gain control region are drawn into the image if enabled.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – Displays the borders of the gain control region False – Does not display the borders of the gain control region	
Default value	False	
Availability	ALL	
Notes	-	
Error behavior	-	

7.13 Average Samples

Name	GainAutoAverageSamples	Custom
Description	The number of reference samples which are averaged before doing a gain control step.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[1 , 32]	
Default value	4	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

7.14 Gain Control Region Channel Selector

Name	GainControlRegionChannelSelector	Custom
Description	Selects the color channel to define the target intensity value or to read the current intensity value of the gain control region.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Red	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Gain Control Region Channel Selector Enum Entries:

Name	Description
All	<p>Selects all available channels for the actual PixelFormat to set the target value to same number.</p> <p>Reading the target value will return the average of all available channels for the current PixelFormat.</p> <p>Reading the current value will return the average of all available channels for the current PixelFormat.</p>
Red	Selects red channel to define the target intensity value or to read the current intensity value of the gain control region.
Green	Selects green channel to define the target intensity value or to read the current intensity value of the gain control region.
Blue	Selects blue channel to define the target intensity value or to read the current intensity value of the gain control region.
White	Selects white channel to define the target intensity value or to read the current intensity value of the gain control region.
Infrared	Selects InfraRed channel to define the target intensity value or to read the current intensity value of the gain control region.

7.15 Target value

Name	GainControlRegionTargetValue[GainControlRegionChannelSelector]	Custom
Description	The target luminance intensity value of the selected channel in the gain control region. The bit depth of the value is 10-bit.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[0 , 1023]	
Default value	700	
Availability	ALL	
Notes	<p>Gain Auto “Once” or “Continuous”: Internal Gain Control adjusts gain values until current value of GainControlRegion have reached target values.</p> <p>Gain Auto “AdjustTargetValueToMaxVideo”: Target value determines the maximum video level which the raw image (without PRNU correction) should reach when doing gain adjustment with GainAuto (Once or Continuous). For that the camera adapts the Target value, until that criterion is fulfilled.</p>	
Error behavior	See the device error code documentation.	

7.16 Current value

Name	GainControlRegionCurrentValue[GainControlRegionChannelSelector]	Custom
Description	The current luminance intensity value of the selected channel in the gain control region. The bit depth of the value is 10-bit.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

7.17 Sensor Sensitivity Channel Selector

Name	SensorSensitivityChannelSelector	Custom
Description	Selects the color to be controlled for the sensor sensitivity.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Red	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Sensor Sensitivity Channel Selector Enum Entries:

Name	Availability	Description
All	ALL	Selects all color channels to control sensor sensitivity. If the sensor sensitivity is modified, the specified value is applied to all color channels. If you read the sensor sensitivity, the lastly set value is returned in this case. After a boot-up, 0 is returned.
White	ax_X	Selects white channel to control sensor sensitivity.
Red	ax_X	Selects red channel to control sensor sensitivity.
Green	ax_X	Selects green channel to control sensor sensitivity.
Blue	ax_X	Selects blue channel to control sensor sensitivity.

7.18 Sensor Sensitivity

Name	SensorSensitivity[SensorSensitivityChannelSelector]			Custom
Description	Controls the sensor sensitivity of the specified selector .			
Interface	Integer			
Access mode	Read/Write			
Adjustable while grabbing	Yes			
Value range	Variant	Min Value	Max Value	
	ax_X	0	2	
	g8_X	0	7	
Default value	Variant	Default Value		
	ax_X	2		
	g8_X	4		
Availability	ALL			
Notes	<p>You should create new DSNU/PRNU reference when changing this parameter.</p> <p>g8_X: <i>At sensitivity value 0 the FullWell of the pixels can be exhausted and the maximum SNR of the sensor can be reached, but an analog signal limitation can be expected at ~168dn@8bit. This can be brought back to the full digital range of 0...255 by the PRNU or DigGain.</i></p>			
Error behavior	See the device error code documentation.			

7.19 Gamma

Name	Gamma	Standard
Description	Controls the gamma correction of pixel intensity. This is typically used to compensate for non-linearity of the display system (such as CRT).	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[0.1 – 2.5]	
Default value	1.0	
Availability	ALL	
Notes	The gamma values 0.2 – 2.5 behave corresponding to the standard gamma definition. The gamma value 0.1 enables a special sRGB gamma table. The gamma feature is effective only if the Gamma LUT is enabled.	
Error behavior	See the device error code documentation.	

7.20 Brightness Contrast Enable

Name	BrightnessContrastEnable	Custom
Description	Enable brightness and contrast image processing unit.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – Enables brightness and contrast image processing unit. False – Disables brightness and contrast image processing unit.	
Default value	False	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

7.21 Brightness Contrast Channel Selector

Name	BrightnessContrastChannelSelector	Custom
Description	Selects the color channel to control the brightness and contrast.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Red	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Brightness Contrast Channel Selector Enum Entries:

Name	Description
Red	Brightness or Contrast will be applicable to the red channel.
Green	Brightness or Contrast will be applicable to the green channel.
Blue	Brightness or Contrast will be applicable to the blue channel.
White	Brightness or Contrast will be applicable to the white channel.
Infrared	Brightness or Contrast will be applicable to the infrared channel.

7.22 Contrast

Name	BrightnessContrastGain [BrightnessContrastChannelSelector]	Custom
Description	Controls the contrast (gain) value for the selected color channel.	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[0.0 , 1.999]	
Default value	1.0	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

7.23 Brightness

Name	BrightnessContrastOffset [BrightnessContrastChannelSelector]	Custom
Description	Controls the brightness (offset) value for the selected color channel.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[-0.25 , 0.25]	
Default value	0.0	
Availability	ALL	
Notes	<p>The resulting brightness (offset) is defined by the features value multiplied with the maximum value of a pixel defined by the pixel formats bit-depth.</p> <p>Example:</p> <p>The maximum value of a pixel using the pixel format RGB8 (bit-depth 8-bit) is 255.</p> <p>Brightness value of 0.1 would increase the output pixel value by:</p> <p>Offset= 0.1x 255 = 25dn's</p>	
Error behavior	See the device error code documentation.	

8 Image Calibration Control

8.1 Image Calibration Mode - Deprecated

Name	ImageCalibrationMode	Custom
Description	Sets internal camera parameter for calibration DSNU or PRNU or even directly perform internal calibration .	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	Off	
Availability	ALL	
Notes	<p>Mode = ImageCalibrationModeDSNU / ImageCalibrationModePRNU: Features are set internally, so that raw, un-scaled and un-transformed image data is generated. With that image data DRNU or PRNU references can be generated. If an affected feature is read, the modified value is returned. While ImageCalibrationMode is active, the internally changed features cannot be modified. When ImageCalibrationMode is set to Off, features are restored to their previous values.</p> <p>The following features are read-only when ImageCalibrationMode is enabled:</p> <ul style="list-style-type: none"> - ColorTransformationSelector - ColorTransformationEnable - BrightnessContrastEnable - DarkSignalNonUniformityReferenceOutput - PhotoResponseNonUniformityReferenceOutput - DecimationHorizontalFloat - BinningHorizontal - ReverseX - LutEnable - GainControlRegionVisible - UserSetLoad <p>The Image Calibration Mode for DSNU-creation will additionally disable digital gain. This is not reflected by the features.</p> <p>Mode = CalibrateDSNUInternal / CalibratePRNUInternal: Internal DSNU or PRNU calibration is done. All internal parameters are adapted automatically. Calibration data is written to LUT selected by Dark Signal Non-Uniformity (DSNU) Selector or Photo Response Non-Uniformity (PRNU) Selector.</p> <p>CalibrateDSNUInternal or CalibratePRNUInternal can directly be started from Mode=Off. ImageCalibrationModeDSNU or ImageCalibrationModePRNU is not required to be set before.</p> <p>After calibration has finished ImageCalibrationMode returns to previous state.</p> <p>The ImageCalibrationMode feature should be polled to check the status of reference generation. Once the feature value changes from Calibrate<DSNU PRNU>Internal to the previous state e.g., Off the process has finished. To cancel the current process set the value to Off.</p>	
Error behavior	See the device error code documentation.	

Image Calibration Mode Enum Entries:

Name	Description
Off	
ImageCalibrationModeDSNU	Image from camera is prepared for DSNU calibration. Former <i>CalibrateDarkSignalNonUniformity</i>
ImageCalibrationModePRNU	Image from camera is prepared for PRNU calibration Former <i>CalibratePhotoResponseNonUniformity</i>
CalibrateDSNUInternal	Camera performs internal DSNU calibration (This feature is deprecated, use FlatFieldCorrectionStartCalibration. It will be removed from package 3.0.0)
CalibratePRNUInternal	Camera performs internal PRNU calibration (This feature is deprecated, use FlatFieldCorrectionStartCalibration. It will be removed from package 3.0.0)

8.2 Dark Signal Non-Uniformity (DSNU) Selector - Deprecated

Name	DarkSignalNonUniformitySelector	Custom
Description	Selects a DSNU LUT.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	LUT1	
Availability	ALL	
Notes	This feature is deprecated, use FlatFieldCorrectionSelector. It will be removed from package 3.0.0	
Error behavior	See the device error code documentation.	

Dark Signal Non-Uniformity (DSNU) Selector Enum Entries:

Name	Description
LUT1	Look-Up-Table 1
LUT2	Look-Up-Table 2

8.3 DSNU Dataset Information - Deprecated

Name	DarkSignalNonUniformityDataSetInformation [DarkSignalNonUniformitySelector]	Custom
Description	Gives information of the selected DSNU LUT state.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	-	
Availability	ALL	
Notes	This feature is deprecated. It will be removed from package 3.0.0	
Error behavior	-	

Dark Signal Non-Uniformity (DSNU) Selector Enum Entries:

Name	Description
InactiveUnconfigured	The selected DSNU correction dataset is not used in the image processing pipeline of the camera and does not contain valid DSNU correction values.
InactiveConfigured	The selected DSNU correction dataset is not used in the image processing pipeline of the camera but contains valid DSNU correction values.

ActiveConfigured	The selected DSNU correction dataset is used in the image processing pipeline of the camera and contains valid DSNU correction values.
------------------	----------------------------------------------------------------------------------------------------------------------------------------

8.4 DSNU Available Planes - Deprecated

Name	DarkSignalNonUniformityAvailablePlains	Custom
Description	Indicates which color planes are available.	
Interface	Enumeration	
Access mode	Read Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Red	
Availability	ALL	
Notes	This feature is deprecated, use FlatFieldCorrectionAvailablePlanes It will be removed from package 3.0.0	
Error behavior	See the device error code documentation.	

DSNU Available Planes Enum Entries:

Name	Description
Red	Selects red channel to read the first and last valid pixel values.
Green	Selects green channel to read the first and last valid pixel values.
Blue	Selects blue channel to read the first and last valid pixel values.
White	Selects white channel to read the first and last valid pixel values.
Infrared	Selects Infrared channel to read the first and last valid pixel values.

8.5 First Valid Pixel - Deprecated

Name	DarkSignalNonUniformityFirstPixelReg [DarkSignalNonUniformityAvailablePlains]	Custom
Description	Indicates first valid pixel.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	This feature is deprecated, use FlatFieldCorrectionFirstPixel It will be removed from package 3.0.0	
Error behavior	-	

8.6 Last Valid Pixel - Deprecated

Name	DarkSignalNonUniformityLastPixelReg [DarkSignalNonUniformityAvailablePlains]	Custom
Description	Indicates last valid pixel.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	This feature is deprecated, use FlatFieldCorrectionLastPixel It will be removed from package 3.0.0	
Availability	ALL	
Notes	-	
Error behavior	-	

8.7 DSNU Display Reference Values - Deprecated

Name	DarkSignalNonUniformityReferenceOutput	Custom
Description	Displays the DSNU reference as a static output video.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – Displays the DSNU reference values False – Does not display the DSNU reference values	
Default value	False	
Availability	ALL	
Notes	This feature is deprecated, use FlatFieldCorrectionDisplayReference. It will be removed from package 3.0.0 This feature is available only if DSNU LUT is active and configured. This parameter is not stored in user set.	
Error behavior	See the device error code documentation.	

8.8 Photo Response Non-Uniformity (PRNU) Selector - Deprecated

Name	PhotoResponseNonUniformitySelector	Custom
Description	Selects a PRNU LUT.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	LUT1	
Availability	ALL	
Notes	This feature is deprecated, use FlatFieldCorrectionSelector. It will be removed from package 3.0.0	
Error behavior	See the device error code documentation.	

Photo Response Non-Uniformity (PRNU) Selector Enum Entries:

Name	Description
LUT1	Look-Up-Table 1
LUT2	Look-Up-Table 2

8.9 PRNU Dataset Information - Deprecated

Name	PhotoResponseNonUniformityDataSetInformation [PhotoResponseNonUniformitySelector]	Custom
Description	Gives information of the selected PRNU LUT state.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	-	
Availability	ALL	
Notes	This feature is deprecated. It will be removed from package 3.0.0	
Error behavior	-	

Photo Response Non-Uniformity (DSNU) Selector Enum Entries:

Name	Description
InactiveUnconfigured	The selected PRNU correction dataset is not used in the image processing pipeline of the camera and does not contain valid PRNU correction values.

InactiveConfigured	The selected PRNU correction dataset is not used in the image processing pipeline of the camera but contains valid PRNU correction values.
ActiveConfigured	The selected PRNU correction dataset is used in the image processing pipeline of the camera and contains valid PRNU correction values.

8.10 PRNU Available Planes - Deprecated

Name	PhotoResponseNonUniformityAvailablePlains	Custom
Description	Indicates first valid pixel.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range		
Default value	Red	
Availability	ALL	
Notes	This feature is deprecated, use FlatFieldCorrectionAvailablePlanes It will be removed from package 3.0.0	
Error behavior	See the device error code documentation.	

PRNU Available Planes Enum Entries:

Name	Description
Red	Selects red channel to read the first and last valid pixel values.
Green	Selects green channel to read the first and last valid pixel values.
Blue	Selects blue channel to read the first and last valid pixel values.
White	Selects red channel to read the first and last valid pixel values.
Infrared	Selects Infrared channel to read the first and last valid pixel values.

8.11 First Valid Pixel - Deprecated

Name	PhotoResponseNonUniformityFirstPixelReg [PhotoResponseNonUniformityAvailablePlains]	Custom
Description	Indicates first valid pixel.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	This feature is deprecated, use FlatFieldCorrectionFirstPixel It will be removed from package 3.0.0	
Error behavior	-	

8.12 Last Valid Pixel - Deprecated

Name	PhotoResponseNonUniformityLastPixelReg [PhotoResponseNonUniformityAvailablePlains]	Custom
Description	Indicates last valid pixel.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	This feature is deprecated, use FlatFieldCorrectionLastPixel It will be removed from package 3.0.0	

Error behavior	-
----------------	---

8.13 PRNU Display Reference Values - Deprecated

Name	PhotoResponseNonUniformityReferenceOutput	Custom
Description	Displays the PRNU reference as a static output video.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – Display the PRNU reference values False – Do not display the PRNU reference values	
Default value	False	
Availability	ALL	
Notes	<p>This feature is deprecated, use FlatFieldCorrectionDisplayReference It will be removed from package 3.0.0</p> <p>This feature is valid and available only if PRNU LUT is active and configured. This parameter is not stored in user set.</p>	
Error behavior	See the device error code documentation.	

8.14 Flat Field Correction Calibration Mode

Name	FlatFieldCorrectionCalibrationMode	Custom
Description	Sets camera into mode for calibration of DSNU or PRNU..	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	Off	
Availability	ALL	
Notes	<p>Mode = DSNU / PRNU: Features are set internally, so that raw, un-scaled and un-transformed image data is generated. With that image data DRNU or PRNU references can be generated. If an affected feature is read, the modified value is returned. While FlatFieldCorrectionCalibrationMode is active, the internally changed features cannot be modified. When FlatFieldCorrectionCalibrationMode is set to Off, features are restored to their previous values.</p> <p>The following features are read-only when FlatFieldCorrectionCalibrationMode is enabled:</p> <ul style="list-style-type: none"> - ColorTransformationSelector - ColorTransformationEnable - BrightnessContrastEnable - DarkSignalNonUniformityReferenceOutput - PhotoResponseNonUniformityReferenceOutput - DecimationHorizontalFloat - BinningHorizontal - ReverseX - LutEnable - GainControlRegionVisible - UserSetLoad <p>The Flat Field Correction Calibration Mode for DSNU-creation will additionally disable digital gain. This is not reflected by the features.</p> <p>DSNU or PRNU is not required to be set before.</p>	

	<p>After calibration has finished FlatFieldCorrectionCalibrationMode returns to previous state.</p> <p>The FlatFieldCorrectionCalibrationMode feature should be polled to check the status of reference generation. To cancel the current process set the value to Off.</p>
Error behavior	See the device error code documentation.

Flat Field Correction Calibration Mode Enum Entries:

Name	Description
Off	
DSNU	Image from camera is prepared for DSNU calibration. Former <i>ImageCalibrationModeDSNU</i>
PRNU	Image from camera is prepared for PRNU calibration Former <i>ImageCalibrationModePRNUy</i>

8.15 Flat Field Correction Selector

Name	FlatFieldCorrectionSelector	Custom
Description	Specifies the flat field correction type DSNU or PRNU data set.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	DSNU DataSet 1	
Availability	ALL	
Notes		
Error behavior	See the device error code documentation.	

Flat Field Correction Selector Enum Entries:

Name	Description
DSNU DataSet 1	Selects the DSNU DataSet1
DSNU DataSet 2	Selects the DSNU DataSet 2
PRNU DataSet 1	Selects the PRNU DataSet 1
PRNU DataSet 2	Selects the PRNU DataSet 2

8.16 Enable

Name	FlatFieldCorrectionEnable[FlatFieldCorrectionSelector]	Custom
Description	Enable/Disable the selected DataSet.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – Activates the selected DataSet False – Deactivates the selected DataSet	
Default value	False	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

8.17 DataSet Description

Name	FlatFieldCorrectionDataSetDescription[FlatFieldCorrectionSelector]	Custom
Description	Leave the description to describe the chosen flat field correction selector.	
Interface	String	
String length	32	
Access mode	Read/Write	

Adjustable while grabbing	Yes
Value range	-
Default value	-
Availability	ALL
Notes	-
Error behavior	-

8.18 Available Planes

Name	FlatFieldCorrectionAvailablePlanes [FlatFieldCorrectionSelector]	Custom
Description	Indicates which color planes are available.	
Interface	Enumeration	
Access mode	Read Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Red	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Flat Field Correction Available Planes Enum Entries:

Name	Description
Red	Selects red channel to read the first and last valid pixel values.
Green	Selects green channel to read the first and last valid pixel values.
Blue	Selects blue channel to read the first and last valid pixel values.
White	Selects white channel to read the first and last valid pixel values.
Infrared	Selects Infrared channel to read the first and last valid pixel values.

8.19 First Valid Pixel

Name	FlatFieldCorrectionFirstPixel [FlatFieldCorrectionSelector] [FFCAvailablePlains]	Custom
Description	Indicates first valid pixel.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

8.20 Last Valid Pixel

Name	FlatFieldCorrectionLastPixel [FlatFieldCorrectionSelector] [FFCAvailablePlains]	Custom
Description	Indicates last valid pixel.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

8.21 Display Reference

Name	FlatFieldCorrectionDisplayReference [FlatFieldCorrectionSelector]	Custom
Description	Displays the selected flat field correction reference as a static output video.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – Displays the selected flat field correction selector reference values False – Does not display the selected flat field correction selector reference values	
Default value	False	
Availability	ALL	
Notes	This feature is available only if the selected data set is active and configured. This parameter is not stored in user set.	
Error behavior	See the device error code documentation.	

8.22 Start Calibration

Name	FlatFieldCorrectionStartCalibration [FlatFieldCorrectionSelector]	Custom
Description	Camera performs internal calibration for the selected flat field correction.	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	1 When command is executed, 0 is returned	
Default value	1	
Availability	ALL	
Notes	When command is executed, Internal selected flat field correction calibration is done. All internal parameters are adapted automatically. Calibration data is written to the selected FlatFieldCorrectionSelector .	
Error behavior	See the device error code documentation.	

8.23 Stop Calibration

Name	FlatFieldCorrectionStopCalibration [FlatFieldCorrectionSelector]	Custom
Description	Camera stops performing internal calibration for the selected flat field correction.	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	Yes	

Value range	1 When command is executed, 0 is returned
Default value	1
Availability	ALL
Notes	
Error behavior	See the device error code documentation.

8.24 Calibration Status

Name	FlatFieldCorrectionCalibrationStatus[FlatFieldCorrectionSelector]	Custom
Description	Displays the calibration status.	
Interface	Enumeration	
Access mode	Read Only	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	Off	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Calibration Status Enum Entries:

Name	Description
Off	No Calibration is performed
Success	Internal flat field correction calibration success
DSNUWarning	Enable DSNU to perform internal flat field correction calibration (PRNU)
Error	Internal flat field correction calibration error
CalibrationInProgress	Internal flat field correction calibration in progress

8.25 Line Distance

Name	ImageCalibrationLineDistance			Custom
Description	This feature is used to compensate the line distance of the sensors color channels.			
Interface	Float			
Access mode	Read/Write			
Adjustable while grabbing	Yes			
Value range	Package	Min Value	Max Value	
	Up to 2.3.0	0.0	3.0	
	2.4.0 and above	0.0	3.0 – For 4 channel pixel format 6.0 – For 3 or 1 channel pixel format	
Default value	2.0			
Availability	ALL			
Notes	-			
Error behavior	See the device error code documentation.			

8.26 Scan Direction Source

Name	ScanDirectionSource	Custom
Description	Selects the scan direction source.	
Interface	Enumeration	
Access mode	Read Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Internal	
Availability	ALL	

Notes	This feature is not available if MasterSlaveMode is configured as Slave.
Error behavior	See the device error code documentation.

Scan Direction Source Enum Entries:

Name	Description
Internal	Specifies internal scanning direction source
Line3	Specifies scanning direction source by the level of Line3
Encoder0	Specifies scanning direction source by Encoder0 <i>Currently only for EncoderSourceB=Line2</i>

8.27 Scan Direction

Name	ImageCalibrationScanDirection[ScanDirectionSource]	Custom
Description	Controls scan direction processing.	
Interface	Enumeration	
Access mode	Read Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Forward	
Availability	ALL	
Notes	<p>This feature is not available if MasterSlaveMode is configured as Slave.</p> <p>This feature is writable only if ScanDirectionSource is Internal otherwise Read only.</p>	
Error behavior	See the device error code documentation.	

Scan Direction Enum Entries:

Name	Description
Forward	Specifies forward scanning direction of the camera (RGB).
Backward	Specifies backward scanning direction of the camera (BGR).

8.28 Image Center Offset – Not Available for AllPIXA-EVO

Name	ImageCenterOffset	Custom
Description	Displays the pixel offset between sensor center and scan target center.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ -15000	
Default value	-	
Notes	-	
Error behavior	-	

9 Color Transformation Control

9.1 Color Transformation Selector

Name	ColorTransformationSelector	Standard
Description	Selects which Color Transformation module is controlled by the various color transformation features.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	ColortoColor	
Availability	ALL (Not available for mono cameras)	
Notes	<p>The transformations are defined as follows:</p> <p>Color to Color</p> $\begin{pmatrix} R_{out} \\ G_{out} \\ B_{out} \\ A_{out} \end{pmatrix} = \begin{pmatrix} Gain_{00} & Gain_{01} & Gain_{02} & Gain_{03} \\ Gain_{10} & Gain_{11} & Gain_{12} & Gain_{13} \\ Gain_{20} & Gain_{21} & Gain_{22} & Gain_{23} \\ Gain_{30} & Gain_{31} & Gain_{32} & Gain_{33} \end{pmatrix} \begin{pmatrix} R_{in} \\ G_{in} \\ B_{in} \\ A_{in} \end{pmatrix} + \begin{pmatrix} Offset_0 \\ Offset_1 \\ Offset_2 \\ Offset_3 \end{pmatrix}$ <p>In case of RGB pixel format the fourth entry <i>A</i> has no meaning. <i>A</i> could contain <i>Ir</i> color component for some camera variants.</p> <p>Color to Grey</p> $M_{out} = (Gain_0 \quad Gain_1 \quad Gain_2 \quad Gain_3) \begin{pmatrix} R_{in} \\ G_{in} \\ B_{in} \\ A_{in} \end{pmatrix}$ <p>Attention: For current implementation color to grey is supported only for RGB. So the formula reduces to $Gain_{0-2}$ and RGB!</p> <p>Use Color Transformation Value Selector and Color Transformation Value to set the coefficients.</p>	
Error behavior	See the device error code documentation.	

Color Transformation Selector Enum Entries:

Name	Description
ColortoColor	Color to color
ColortoGrey	Color to grey

9.2 Color Transformation Enable

Name	ColorTransformationEnable[ColorTransformationSelector]	Standard
Description	Activates the selected Color Transformation module.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	True – Enables the selected color transformation module False – Disables the selected color transformation module	
Default value	False	
Availability	ALL (Not available for mono cameras)	
Notes	If the ColortoGrey module is disabled, the pixel format internally is changed to RGB8.	
Error behavior	See the device error code documentation.	

9.3 Color Transformation Value Selector

Name	ColorTransformationValueSelector	Standard
Description	Selects the Gain factor or Offset of the transformation matrix to access in the selected color transformation module.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Gain00 – For ColortoColor module Gain0 – For ColortoGrey module	
Availability	ALL (Not available for mono cameras)	
Notes	-	
Error behavior	See the device error code documentation.	

Color Transformation Value Selector Enum Entries:

Color to Color

Name	Description
Gain00	Gain 0, 0 of the transformation matrix.
Gain01	Gain 0, 1 of the transformation matrix.
Gain02	Gain 0, 2 of the transformation matrix.
Gain03	Gain 0, 3 of the transformation matrix.
Gain10	Gain 1, 0 of the transformation matrix.
Gain11	Gain 1, 1 of the transformation matrix.
Gain12	Gain 1, 2 of the transformation matrix.
Gain13	Gain 1, 3 of the transformation matrix.
Gain20	Gain 2, 0 of the transformation matrix.
Gain21	Gain 2, 1 of the transformation matrix.
Gain22	Gain 2, 2 of the transformation matrix.
Gain23	Gain 2, 3 of the transformation matrix.
Gain30	Gain 3, 0 of the transformation matrix.
Gain31	Gain 3, 1 of the transformation matrix.
Gain32	Gain 3, 2 of the transformation matrix.
Gain33	Gain 3, 3 of the transformation matrix.
Offset0	Offset 0 of the transformation matrix.
Offset1	Offset 1 of the transformation matrix.
Offset2	Offset 2 of the transformation matrix.
Offset3	Offset 3 of the transformation matrix.

Color to Grey

Name	Description
Gain0	Gain 1, 0 of the transformation matrix.
Gain1	Gain 1, 1 of the transformation matrix.

Gain2	Gain 1, 2 of the transformation matrix
Gain3	Gain 1, 2 of the transformation matrix.

9.4 Color Transformation Value

Name	ColorTransformationValue[ColorTransformationValueSelector]	Standard
Description	Represents the value of the selected Gain factor or Offset inside the transformation matrix.	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[-2.0 , 2.0] – For Gain selector [-0.5, 0.5] – For Offset selector	
Default value	-	
Availability	ALL (Not available for mono cameras)	
Notes	-	
Error behavior	See the device error code documentation.	

10 LUT Control

10.1 LUT Selector

Name	LUTSelector	Standard
Description	Selects which LUT to control.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See the enum entries table below.	
Default value	Gamma	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

LUT Selector Enum Entries:

Name	Description
Gamma	Selects the Gamma LUT
DarkSignalNonUniformityLUT1	Selects the DSNU LUT 1(This feature is deprecated, use FlatFieldCorrectionSelector. It will be removed from package 3.0.0)
DarkSignalNonUniformityLUT2	Selects the DSNU LUT2(This feature is deprecated, use FlatFieldCorrectionSelector. It will be removed from package 3.0.0)
PhotoResponseNonUniformityLUT1	Selects the PRNU LUT1(This feature is deprecated, use FlatFieldCorrectionSelector. It will be removed from package 3.0.0)
PhotoResponseNonUniformityLUT2	Selects the PRNU LUT2(This feature is deprecated, use FlatFieldCorrectionSelector. It will be removed from package 3.0.0)

10.2 LUT Enable

Name	LUTEnable[LUTSelector]	Standard
Description	Activates/Deactivates the selected LUT.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – Activates the selected LUT False – Deactivates the selected LUT	
Default value	False	
Availability	ALL	
Notes	This feature is deprecated, use FlatFieldCorrectionEnable. It will be removed from package 3.0.0	
Error behavior	See the device error code documentation.	

10.3 LUT Dataset Name - Deprecated

Name	LUTDatasetNameReg[LUTSelector]	Custom
Description	Leave a comment here to describe the chosen LUT.	
Interface	String	
String length	32	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	-	
Default value	-	
Availability	ALL	
Notes	<p>This feature is deprecated, use FlatFieldCorrectionEnable. It will be removed from package 3.0.0</p> <p>This feature is not available for Gamma.</p>	
Error behavior	-	

11 User Set Control

11.1 Loaded User Set

Name	LoadedUserSet	Custom
Description	Specifies the last loaded user set.	
Interface	String	
String length	32	
Access mode	Read Only	
Adjustable while grabbing	Yes	
Value range	-	
Default value	Default	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

11.2 User Set Selector

Name	UserSetSelector	Standard
Description	Selects the feature User Set to load, save or configure.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	UserSet1	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

User Set Selector Enum Entries:

Name	Description
UserSet1	Selects the UserSet 1
UserSet2	Selects the UserSet 2
UserSet3	Selects the UserSet 3
UserSet4	Selects the UserSet 4
UserSet5	Selects the UserSet 5
UserSet6	Selects the UserSet 6
UserSet7	Selects the UserSet 7
UserSet8	Selects the UserSet 8
Default	Selects the Default

11.3 User Set Load

Name	UserSetLoad [UserSetSelector]	Standard
Description	Loads the User Set specified by UserSetSelector to the device and activates it.	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	1	
Default value	1	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

11.4 User Set Save

Name	UserSetSave[UserSetSelector]	Standard
Description	Save the current user settings to the selected user set in the non-volatile memory of the device.	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	1	
Default value	1	
Availability	ALL	
Notes	Default is Read only.	
Error behavior	See the device error code documentation.	

11.5 User Set Comment

Name	UserSetComment[UserSetSelector]	Custom
Description	Leave a comment here to describe the chosen setting.	
Interface	String	
String length	32	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	-	
Default value	Default	
Availability	ALL	
Notes	Default user set is Read only. When executing User Set Save the comment of the active user set is stored to flash.	
Error behavior	See the device error code documentation.	

12 Transport Layer Control

12.1 TLParamsLocked

Name	TLParamsLocked	Standard
Description	This feature is used to lock critical features from changing during acquisition.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[0, 1] 0 – No features are locked 1 – Critical features are locked and cannot be changed	
Default value	0	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

12.2 Payload Size

Name	PayloadSize	Standard
Description	Provides the number of bytes transferred for each image or chunk on the stream channel.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥0	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

12.3 Device Tap Geometry

Name	DeviceTapGeometry	Standard
Description	This describes the geometrical properties characterizing the taps of a camera as presented at the output of the device.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entries below.	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	-	

Device Tap Geometry Enum Entries:

Name	Description
Geometry_1X_1Y	1X 1Y tap geometry

12.4 GigE Vision

12.4.1 Gev Version Major

Name	GevVersionMajor	Standard
Description	Major version of the specification.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	>0	
Default value	-	
Notes	This feature is deprecated (See DeviceTLVersionMajor).	
Error behavior	-	

12.4.2 Gev Version Minor

Name	GevVersionMinor	Standard
Description	Minor version of the specification.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥0	
Default value	-	
Notes	This feature is deprecated (See DeviceTLVersionMinor).	
Error behavior	-	

12.4.3 Gev Device Mode Is Big Endian

Name	GevDeviceModelsBigEndian	Standard
Description	Endianness of the device registers.	
Interface	Boolean	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	True – Represents the endianness of the device registers False – Does not represents the Endianness of the device registers	
Default value	-	
Notes	This feature is deprecated (See DeviceRegistersEndianness).	
Error behavior	-	

12.4.4 Gev Device Mode Character Set

Name	GevDeviceModeCharacterSet	Standard
Description	Character set used by all the strings of the bootstrap registers.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	UTF8	
Notes	This feature is deprecated (See DeviceCharacterSet).	
Error behavior	-	

Gev Device Mode Character Set Enum Entries:

Name	Description
UTF8	UTF 8

12.4.5 Gev Interface Selector

Name	GevInterfaceSelector	Standard
Description	Selects which physical network interface to control.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	0	
Default value	0	
Availability	X_dxge , ax_dsxge	
Notes	-	
Error behavior	-	

12.4.6 Gev MACAddress

Name	GevMACAddress [GevInterfaceSelector]	Standard
Description	MAC address of the network interface.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥0	
Default value	-	
Availability	X_dxge , ax_dsxge	
Notes	-	
Error behavior	-	

12.4.7 Gev Supported Option Selector

Name	GevSupportedOptionSelector	Standard
Description	Selects the GEV option to interrogate for existing support.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	-	
Availability	X_dxge , ax_dsxge	
Notes	-	
Error behavior	-	

Gev Supported Option Selector Enum Entries:

Name	Description
UserDefinedName	Indicates if the Userdefined name register is supported.
SerialNumber	Indicates if the Serial number register is supported.
HeartbeatDisable	Indicates if the Heartbeat can be disabled.
LinkSpeed	Indicates if the Link Speed registers are supported.
CCPApplicationSocket	Indicates if the CCP Application Port and IP address registers are supported.
ManifestTable	Indicates if the Manifest Table is supported.
TestData	Indicates if the test packet is filled with data from the LFSR generator.
DiscoveryAckDelay	When Discovery ACK Delay register is supported, this bit indicates that the application can write it. If this bit is 0, the register is read-only.
DiscoveryAckDelayWritable	Indicates if the Discovery ACK Delay register is supported.
ExtendedStatusCodes	It indicates if the generation of extended status codes is supported.

PrimaryApplicationSwitchover	It indicates if the authenticate primary application switchover requests are supported.
Action	It indicates if Actions are supported.
PendingAck	It indicates if the generation of PENDING_ACK is supported.
EventData	It indicates if the EVENTDATA_CMD and EVENTDATA_ACK are supported.
Event	It indicates if the EVENT_CMD and EVENT_ACK are supported.
PacketResend	It indicates if the PACKETRESEND_CMD is supported.
WriteMem	It indicates if the WRITEMEM_CMD and WRITEMEM_ACK are supported.
CommandsConcatenation	It indicates if the Multiple operations in a single message are supported.
IPConfigurationLLA	It indicates if Link Local Address IP configuration scheme is supported.
IPConfigurationDHCP	It indicates if DHCP IP configuration scheme is supported.
IPConfigurationPersistentIP	It indicates if PersistentIP configuration scheme is supported.
StreamChannelSourceSocket	Indicates the SCSP register (stream channel source port) is available.
MessageChannelSourceSocket	Indicates the MCSP register (message channel source port) is available.
StreamChannel0BigAndLittleEndian	Stream Channel0 Big And Little Endian.
StreamChannel0IPReassembly	Stream Channel0 IP Reassembly
StreamChannel0UnconditionalStreaming	Stream Channel0 Unconditional Streaming.
StreamChannel0ExtendedChunkData	Stream Channel0 Extended Chunk Data.

12.4.8 Gev Supported Option

Name	GevSupportedOption[GevSupportedOptionSelector]	Standard
Description	Returns if the selected GEV option is supported.	
Interface	Boolean	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	True – Selected GEV option is supported False – Selected GEV option is not supported	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.9 Gev Current IP Configuration LLA

Name	GevCurrentIPConfigurationLLA[GevInterfaceSelector]	Standard
Description	Indicates if Link Local Address IP configuration scheme is activated on the given network interface.	
Interface	Boolean	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	True – Link Local Address IP configuration scheme is activated on the given logical link. False – Link Local Address IP configuration scheme is not activated on the given logical link.	
Default value	True	
Availability	X dxge , ax dsxge	

Notes	-
Error behavior	-

12.4.10 Gev Current IP Configuration DHCP

Name	GevCurrentIPConfigurationDHCP[GevInterfaceSelector]	Standard
Description	Indicates if DHCP IP configuration scheme is activated on the given network interface.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – DHCP IP configuration scheme is activated on the given logical link. False – DHCP IP configuration scheme is not activated on the given logical link.	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.11 Gev Current IP Configuration Persistent IP

Name	GevCurrentIPConfigurationPersistentIP[GevInterfaceSelector]	Standard
Description	Indicates if PersistentIP configuration scheme is activated on the given network interface.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – PersistentIP configuration scheme is activated on the given logical link. False – PersistentIP configuration scheme is not activated on the given logical link.	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.12 Gev Current IP Address

Name	GevCurrentIPAddress[GevInterfaceSelector]	Standard
Description	Reports the IP address for the given network interface.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.13 Gev Current Subnet Mask

Name	GevCurrentSubnetMask[GevInterfaceSelector]	Standard
Description	Provides the subnet mask of the given interface.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥0	

Default value	-
Availability	X dxge , ax dsxge
Notes	-
Error behavior	-

12.4.14 Gev Current Default Gateway

Name	GevCurrentDefaultGateway [GevInterfaceSelector]	Standard
Description	Indicates the default gateway IP address to be used on the given network interface.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.15 Gev First URL

Name	GevFirstURL	Standard
Description	Indicates the first URL to the XML device description file. The First URL is used as the first choice by the application to retrieve the XML device description file.	
Interface	String	
String Length	512	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Notes	This feature is deprecated.	
Error behavior	-	

12.4.16 Gev Second URL

Name	GevSecondURL	Standard
Description	Indicates the second URL to the XML device description file. This URL is an alternative if the application was unsuccessful to retrieve the device description file using the first URL.	
Interface	String	
String Length	512	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Notes	This feature is deprecated.	
Error behavior	-	

12.4.17 Gev Number of Interfaces – Deprecated

Name	GevNumberOfInterfaces	Standard
Description	Indicates the number of physical network interfaces supported by this device.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	> 0	

Default value	-
Notes	This feature is deprecated (See DeviceLinkSelector).
Error behavior	-

12.4.18 **Gev Persistent IP Address**

Name	GevPersistentIPAddress	Standard
Description	Indicates the Persistent IP address for this network interface. It is only used when the device boots with the Persistent IP configuration scheme.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.19 **Gev Persistent Subnet Mask**

Name	GevPersistentSubnetMask	Standard
Description	Indicates the Persistent subnet mask associated with the Persistent IP address on this network interface. It is only used when the device boots with the Persistent IP configuration scheme.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.20 **Gev Persistent Default Gateway**

Name	GevPersistentDefaultGateway	Standard
Description	Indicates the persistent default gateway for this network interface. It is only used if the device boots with the Persistent IP configuration scheme.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.21 **Gev Persistent IP Address**

Name	GevPersistentIPAddress	Standard
Description	Indicates the Persistent IP address for this network interface. It is only used when the device boots with the Persistent IP configuration scheme.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	

Default value	-
Availability	X dxge , ax dsxge
Notes	-
Error behavior	-

12.4.22 GevLinkSpeed

Name	GevLinkSpeed	Standard
Description	Indicates the speed of transmission negotiated by the given network interface.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	>0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	The unit is Mbs.	
Error behavior	-	

12.4.23 Gev Message Channel Count

Name	GevMessageChannelCount	Standard
Description	Indicates the number of message channels supported by this device.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥0	
Default value	-	
Notes	This feature is deprecated (See DeviceEventChannelCount).	
Error behavior	-	

12.4.24 Gev Stream Channel Count

Name	GevStreamChannelCount	Standard
Description	Indicates the number of stream channels supported by this device.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥0	
Default value	-	
Notes	This feature is deprecated (See Device Stream Channel Count).	
Error behavior	-	

12.4.25 Gev Heartbeat Timeout

Name	GevHeartbeatTimeout	Standard
Description	Indicates the current heartbeat timeout in milliseconds.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥500	
Default value	-	
Notes	This feature is deprecated (See Device Link Heartbeat Timeout).	
Error behavior	-	

12.4.26 Gev Timestamp Tick Frequency

Name	GevTimestampTickFrequency	Standard
Description	Indicates the number of timestamp ticks during 1 second (frequency in Hz).	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Notes	This feature is deprecated (See increment of the Timestamp Latch Value feature).	
Error behavior	-	

12.4.27 Gev Timestamp Control Latch

Name	GevTimestampControlLatch	Standard
Description	Latches current timestamp counter into GevTimestampValue .	
Interface	Command	
Access mode	Write only	
Adjustable while grabbing	Yes	
Value range	1	
Default value	1	
Notes	This feature is deprecated (See Timestamp Latch).	
Error behavior	-	

12.4.28 Gev Timestamp Control Reset

Name	GevTimestampControlReset	Standard
Description	Resets the Timestamp counter to 0.	
Interface	Command	
Access mode	Write only	
Adjustable while grabbing	Yes	
Value range	1	
Default value	1	
Notes	This feature is deprecated (See Timestamp Reset).	
Error behavior	-	

12.4.29 Gev Time stamp Value

Name	GevTimestampValue	Standard
Description	Returns the latched 64-bit value of the timestamp counter.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Notes	This feature is deprecated (See Timestamp Latch Value).	
Error behavior	-	

12.4.30 Gev CCP

Name	GevCCP	Standard
Description	Controls the device access privilege of an application.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

Gev CCP Enum Entries:

Name	Description
OpenAccess	Open access
ExclusiveAccess	Exclusive access
ControlAccess	Control access

12.4.31 Gev MCPHost Port

Name	GevMCPHostPort	Standard
Description	Indicates the port to which the device must send messages. Setting this value to 0 closes the message channel.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.32 Gev MCDA

Name	GevMCDA	Standard
Description	Indicates the destination IP address for the message channel.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.33 Gev MCTT

Name	GevMCTT	Standard
Description	Provides the transmission timeout value in milliseconds.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	
Default value	0	
Availability	X dxge , ax dsxge	

Notes	-
Error behavior	-

12.4.34 **Gev MCRC**

Name	GevMCRC	Standard
Description	Indicates the number of retransmissions allowed if a message channel message times out.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥ 0	
Default value	0	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.35 **Gev MCSP**

Name	GevMCSP	Standard
Description	This feature indicates the source port for the message channel.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.36 **Gev Stream Channel Selector**

Name	GevStreamChannelSelector	Standard
Description	Selects the stream channel to control.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥ 0	
Default value	0	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.37 **Gev SCP Interface Index**

Name	GevSCPInterfaceIndex[GevStreamChannelSelector]	Standard
Description	Index of network interface to use.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	0	
Default value	0	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.38 Gev SCPHost Port

Name	GevSCPHostPort[GevStreamChannelSelector]	Standard
Description	Indicates the port to which the device must send data stream. Setting this value to 0 closes the stream channel.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.39 Gev SCPSFire Test Packet

Name	GevSCPSFireTestPacket[GevStreamChannelSelector]	Standard
Description	Sends a test packet. If this feature is set, the device fires one test packet.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – The device will fire one test packet. False – The device will not send a test packet.	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.40 Gev SCPSTo Not Fragment

Name	GevSCPSToNotFragment[GevStreamChannelSelector]	Standard
Description	The state of this feature is copied into the “do not fragment” bit of IP header of each stream packet. It can be used by the application to prevent IP fragmentation of packets on the stream channel.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True False	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.41 Gev SCPSBig Endian

Name	GevSCPSBigEndian	Standard
Description	Endianess of multi-byte pixel data for this stream.	
Interface	Boolean	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	True False	
Default value	-	
Notes	This feature is deprecated (See Device Stream Channel Endianness).	
Error behavior	-	

12.4.42 Gev SCPSPacket Size

Name	GevSCPSPacketSize[GevStreamChannelSelector]	Standard
Description	Specifies the stream packet size in bytes to send on this channel.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	>0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.43 Gev SCPD

Name	GevSCPD[GevStreamChannelSelector]	Standard
Description	Indicates the delay (in timestamp counter unit) to insert between each packet for this stream channel. This can be used as a crude flow-control mechanism if the application or the network infrastructure cannot keep up with the packets coming from the device.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.4.44 Gev SCDA

Name	GevSCDA[GevStreamChannelSelector]	Standard
Description	Indicates the destination IP address for this stream channel.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	
Default value	-	
Availability	X dxge , ax dsxge	
Notes	-	
Error behavior	-	

12.5 CoaXPress

12.5.1 Cxp Link Configuration Preferred

Name	CxpLinkConfigurationPreferred	Standard
Description	This feature provides the default link configuration.	
Interface	Enumeration	
Access mode	Read Only	
Adjustable while grabbing	-	
Value range	See enum entries below.	
Default value	-	
Availability	X_cxp	
Notes	-	
Error behavior	-	

Cxp Link Configuration Preferred Enum Entries:

Name	Description
CXP1_X1	Force the Link to 1 Connections operating at CXP-1 speed (1.250 Gbps)
CXP1_X2	Force the Link to 2 Connections operating at CXP-1 speed (1.250 Gbps)
CXP1_X3	Force the Link to 3 Connections operating at CXP-1 speed (1.250 Gbps)
CXP1_X4	Force the Link to 4 Connections operating at CXP-1 speed (1.250 Gbps)
CXP2_X1	Force the Link to 1 Connections operating at CXP-2 speed (2.500 Gbps)
CXP2_X2	Force the Link to 2 Connections operating at CXP-2 speed (2.500 Gbps)
CXP2_X3	Force the Link to 3 Connections operating at CXP-2 speed (2.500 Gbps)
CXP2_X4	Force the Link to 4 Connections operating at CXP-2 speed (2.500 Gbps)
CXP3_X1	Force the Link to 1 Connections operating at CXP-3 speed (3.125 Gbps)
CXP3_X2	Force the Link to 2 Connections operating at CXP-3 speed (3.125 Gbps)
CXP3_X3	Force the Link to 3 Connections operating at CXP-3 speed (3.125 Gbps)
CXP3_X4	Force the Link to 4 Connections operating at CXP-3 speed (3.125 Gbps)
CXP5_X1	Force the Link to 1 Connections operating at CXP-5 speed (5.000 Gbps)
CXP5_X2	Force the Link to 2 Connections operating at CXP-5 speed (5.000 Gbps)
CXP5_X3	Force the Link to 3 Connections operating at CXP-5 speed (5.000 Gbps)
CXP5_X4	Force the Link to 4 Connections operating at CXP-5 speed (5.000 Gbps)
CXP6_X1	Force the Link to 1 Connections operating at CXP-6 speed (6.250 Gbps)
CXP6_X2	Force the Link to 2 Connections operating at CXP-6 speed (6.250 Gbps)
CXP6_X3	Force the Link to 3 Connections operating at CXP-6 speed (6.250 Gbps)
CXP6_X4	Force the Link to 4 Connections operating at CXP-6 speed (6.250 Gbps)
CXP10_X1	Force the Link to 1 Connections operating at CXP-10 speed (10.000 Gbps)

CXP10_X2	Force the Link to 2 Connections operating at CXP-10 speed (10.000 Gbps)
CXP10_X3	Force the Link to 3 Connections operating at CXP-10 speed (10.000 Gbps)
CXP10_X4	Force the Link to 4 Connections operating at CXP-10 speed (10.000 Gbps)
CXP12_X1	Force the Link to 1 Connections operating at CXP-12 speed (12.500 Gbps)
CXP12_X2	Force the Link to 2 Connections operating at CXP-12 speed (12.500 Gbps)
CXP12_X3	Force the Link to 3 Connections operating at CXP-12 speed (12.500 Gbps)
CXP12_X4	Force the Link to 4 Connections operating at CXP-12 speed (12.500 Gbps)

12.5.2 Cxp Link Configuration

Name	CxpLinkConfiguration	Standard
Description	This feature allows specifying the Link configuration for the communication between the Receiver and Transmitter Device.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	See enum entries below.	
Default value	-	
Availability	X_cxp	
Notes	-	
Error behavior	-	

Cxp Link Configuration Enum Entries:

Name	Description
CXP1_X1	Force the Link to 1 Connections operating at CXP-1 speed (1.250 Gbps)
CXP1_X2	Force the Link to 2 Connections operating at CXP-1 speed (1.250 Gbps)
CXP1_X3	Force the Link to 3 Connections operating at CXP-1 speed (1.250 Gbps)
CXP1_X4	Force the Link to 4 Connections operating at CXP-1 speed (1.250 Gbps)
CXP2_X1	Force the Link to 1 Connections operating at CXP-2 speed (2.500 Gbps)
CXP2_X2	Force the Link to 2 Connections operating at CXP-2 speed (2.500 Gbps)
CXP2_X3	Force the Link to 3 Connections operating at CXP-2 speed (2.500 Gbps)
CXP2_X4	Force the Link to 4 Connections operating at CXP-2 speed (2.500 Gbps)
CXP3_X1	Force the Link to 1 Connections operating at CXP-3 speed (3.125 Gbps)
CXP3_X2	Force the Link to 2 Connections operating at CXP-3 speed (3.125 Gbps)
CXP3_X3	Force the Link to 3 Connections operating at CXP-3 speed (3.125 Gbps)
CXP3_X4	Force the Link to 4 Connections operating at CXP-3 speed (3.125 Gbps)
CXP5_X1	Force the Link to 1 Connections operating at CXP-5 speed (5.000 Gbps)
CXP5_X2	Force the Link to 2 Connections operating at CXP-5 speed (5.000 Gbps)

CXP5_X3	Force the Link to 3 Connections operating at CXP-5 speed (5.000 Gbps)
CXP5_X4	Force the Link to 4 Connections operating at CXP-5 speed (5.000 Gbps)
CXP6_X1	Force the Link to 1 Connections operating at CXP-6 speed (6.250 Gbps)
CXP6_X2	Force the Link to 2 Connections operating at CXP-6 speed (6.250 Gbps)
CXP6_X3	Force the Link to 3 Connections operating at CXP-6 speed (6.250 Gbps)
CXP6_X4	Force the Link to 4 Connections operating at CXP-6 speed (6.250 Gbps)
CXP10_X1	Force the Link to 1 Connections operating at CXP-10 speed (10.000 Gbps)
CXP10_X2	Force the Link to 2 Connections operating at CXP-10 speed (10.000 Gbps)
CXP10_X3	Force the Link to 3 Connections operating at CXP-10 speed (10.000 Gbps)
CXP10_X4	Force the Link to 4 Connections operating at CXP-10 speed (10.000 Gbps)
CXP12_X1	Force the Link to 1 Connections operating at CXP-12 speed (12.500 Gbps)
CXP12_X2	Force the Link to 2 Connections operating at CXP-12 speed (12.500 Gbps)
CXP12_X3	Force the Link to 3 Connections operating at CXP-12 speed (12.500 Gbps)
CXP12_X4	Force the Link to 4 Connections operating at CXP-12 speed (12.500 Gbps)

12.5.3 Cxp Version Used

Name	CxpVersionUsed	Custom
Description	Version of the CoaXPress specification used for communication between Device and Host.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	-	
Availability	X_cxp	
Notes	-	
Error behavior	See the device error code documentation.	

Cxp Version Used Enum Entries:

Name	Description
CXP_Version_1_1	Cxp Version 1.1
CXP_Version_2_0	Cxp Version 2.0

12.5.4 Cxp Connection Selector

Name	CxpConnectionSelector	Standard
Description	Selects the coaxpress physical connection to control.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	
Default value	-	
Availability	X_cxp	

Notes	-
Error behavior	-

12.5.5 Cxp Connection Test Mode

Name	CxpConnectionTestMode[CxpConnectionSelector]	Standard
Description	Enables the test mode for an individual physical connection of the device.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	See enum entries below.	
Default value	Off	
Availability	X_cxp	
Notes	-	
Error behavior	-	

Cxp Connection Test Mode Enum Entries:

Name	Description
Off	Test mode disabled
Mode1	Test mode enabled

12.5.6 Cxp Connection Test Packet Count Tx

Name	CxpConnectionTestPacketCountTx[CxpConnectionSelector]	Custom
Description	Reports the current count for the test packets sent on selected physical connection.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	≥ 0	
Default value	-	
Availability	X_cxp	
Notes	-	
Error behavior	-	

12.5.7 Cxp Connection Test Packet Count Rx

Name	CxpConnectionTestPacketCountRx[CxpConnectionSelector]	Custom
Description	Reports the current count for the test packets received on selected physical connection.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	≥ 0	
Default value	-	
Availability	X_cxp	
Notes	-	
Error behavior	-	

12.5.8 Cxp Connection Test Error Count

Name	CxpConnectionTestErrorCount[CxpConnectionSelector]	Standard
Description	Reads the current connection error count for the test packets received by the device on the selected connector.	
Interface	Integer	
Access mode	Read/Write	
Adjustable	No	

while grabbing	
Value range	≥ 0
Default value	-
Availability	X_cxp
Notes	-
Error behavior	-

13 File Access Control

In general, make sure to always use consistent packages as delivered by Chromasens and do not mix files from different packages!

13.1 File Selector

Name	FileSelector	Standard
Description	Select a file to read/write.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	NoFile	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

File Selector Enum Entries:

Name	Description
NoFile	No file selected
Bitstream	Enables bitstream access
Application	Enables application access
Xml	Enables GenICam XML access
DSNULUT1	Enables DSNU LUT 1 access ¹
DSNULUT2	Enables DSNU LUT 2 access ¹
PRNULUT1	Enables PRNU LUT 1 access ¹
PRNULUT2	Enables PRNU LUT 2 access ¹
SensorFile	Enables Sensor File access
GammaLUT	Enables Gamma LUT access
UserSet1	Enables User set 1 access
UserSet2	Enables User set 2 access
UserSet3	Enables User set 3 access
UserSet4	Enables User set 4 access
UserSet5	Enables User set 5 access
UserSet6	Enables User set 6 access
UserSet7	Enables User set 7 access
UserSet8	Enables User set 8 access
LightCtrlSet1	Enables Light controller set 1 access (Not for allPIXA Evo)
PackageDescriptionFile	Enables Package Description File access
MemoryFile	Enables memory file access
IOAnalyzerEventFile	Enables IO Analyzer Event File access

¹ If the LUT is enabled in the image processing unit, it will be updated with the newly downloaded file.

13.2 File Operation Selector

Name	FileOperationSelector[FileSelector]	Standard
Description	Select an operation which shall be performed on a file.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	NoOperation	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

File Operation Selector Enum Entries:

Name	Description	Notes
NoOperation	Selects no operation	-
Open	Open a file	Fails if a file is already opened.
Close	Close a file	<p>When this command is executed, the file is verified and internally copied. This is a time-consuming process.</p> <p>A file is always closed, even if an error occurs.</p> <p>The File Operation Status is set appropriately. Therefore Success indicates a successful file update and Failure an erroneous update.</p> <p>If a Fatal Error occurs, the File Operation Status is set to Fatal Error. In this case you must not switch off the camera if the file type is one of the following:</p> <ul style="list-style-type: none"> - Bitstream - Application - XML - Bootfile (sensorfile) <p>For these files, please try to download the file again to avoid damage!</p> <p>For other files you may switch off the camera.</p> <p><i>In general, make sure to always use consistent packages as delivered by chromasens and do not mix files from different packages!</i></p>
Read	Read a file	-
Write	Write a file	-

13.3 File Operation Execute

Name	FileOperationExecute[FileOperationSelector]	Standard
Description	Executes the selected file operation.	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	{0,1}	
Default value	1	
Availability	ALL	
Notes	To check whether the operation is finished, read the value of the FileOperationExecute command periodically. If the value is not equal to the commands value of the node in the xml, the command has finished execution.	
Error behavior	See the device error code documentation.	

13.4 File Open Mode

Name	FileOpenMode	Standard
Description	Select an open mode.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	NoOpenMode	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

File Open Mode Enum Entries:

Name	Description	Notes
NoOpenMode	No open mode selected	-
Read	Open a file in read-only mode	-
Write	Open a file in write-only mode	With this open mode no read command is permitted. In addition, if the FileAccessOffset is set after a write command occurred, the new value of the FileAccessOffset must be at least new_ FileAccessOffset = (old_ FileAccessOffset + old_ FileAccessLength).

13.5 File Access Offset

Name	FileAccessOffset[FileOperationSelector]	Standard
Description	Controls the starting position of the access in the file.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥0	
Default value	0	
Availability	ALL	
Notes	The unit is Byte. Please see Write for restrictions.	
Error behavior	See the device error code documentation.	

13.6 File Access Length

Name	FileAccessLength[FileOperationSelector]	Standard
Description	Controls the length of the mapping between the device file storage and the FileAccessBuffer.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥ 0	
Default value	0	
Availability	ALL	
Notes	The unit is Byte. Please see Write for restrictions.	
Error behavior	See the device error code documentation.	

13.7 File Operation Result

Name	FileOperationResult[FileOperationSelector]	Standard
Description	The number of the successfully read/written bytes of the last file operation.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	0	
Availability	ALL	
Notes	-	
Error behavior	-	

13.8 File Operation Status

Name	FileOperationStatus[FileOperationSelector]	Standard
Description	Status of recent operation.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	Success	
Availability	ALL	
Notes	-	
Error behavior	-	

File Operation Status Enum Entries:

Name	Description	Notes
Success	The last operation succeeded	-
Failure	The last operation failed	-
FatalError	If this error occurs, do not switch off the device and repeat the update immediately! Otherwise, the system may refuse to boot next time!	A fatal error occurred during the last operation. Please see the Close command for more information.

13.9 File Size

Name	FileSize[FileSelector]	Standard
Description	Represents the size of the selected file in bytes.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	0	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

13.10 File Checksum

Name	FileChecksum[FileSelector]	Custom
Description	The checksum of a file.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	≥ 0	
Default value	0	
Availability	ALL	
Notes	<p>This feature must be set by the user after the file is opened and before the file is closed if a file is uploaded to the camera. Only if the checksum feature corresponds to the checksum calculated internally by the camera, the file download succeeds. For reading operations there is no need to set the checksum feature.</p> <p>Calculation: The checksum is an unsigned 32-bit value. It is the sum of all 4-Byte words (Little Endian) of the file. If a files size is not a multiple of four, the “missing” bytes are interpreted as zero.</p> <p><i>Pseudo code for calculation:</i> <pre> u32 file[N] u32 checksum = 0 checksum += file[0] checksum += file[1] ... checksum += file[N-1] </pre> </p>	
Error behavior	See the device error code documentation.	

13.11 File Access Buffer

Name	FileAccessBuffer	Standard
Description	This buffer is used for the GenICam file update mechanism.	
Interface	Register	
Size	65536	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	-	
Availability	ALL	
Default value	-	
Notes	See the device error code documentation.	

14 Digital IO Control

14.1 Functional scope

This section shows the capabilities of digital IO lines.

14.1.1 allPIXA evo

This table contains the supported LineMode and LineFormat entries for each supported line.

Line	LineMode	LineFormat	Comment
Line1	Input	RS422	
Line1	Output	Not Supported	Output mode not supported
Line2	Input	RS422	
Line2	Output	Not Supported	Output mode not supported
Line3	Input	SingleEnded_3V3	
Line3	Output	SingleEnded_3V3	
Line4	Input	SingleEnded_3V3	
Line4	Output	SingleEnded_3V3	
Line5	Input	SingleEnded_3V3	
Line5	Output	SingleEnded_3V3	
Line6	Input	SingleEnded_3V3	
Line6	Output	SingleEnded_3V3	
Line7	Input	SingleEnded_3V3	
Line7	Output	SingleEnded_3V3	
Line8	Input	SingleEnded_3V3	
Line8	Output	SingleEnded_3V3	
Line9	Input	SingleEnded_3V3	
Line9	Output	SingleEnded_3V3	
Line10	Input	Not Supported	Input mode not supported
Line10	Output	Misc	
Line11	Input	SingleEnded_3V3	
Line11	Output	SingleEnded_3V3	

This table contains the supported LineSource entries for each supported line.

Line	LineSource
Line1	Not Supported
Line2	Not Supported
Line3	Off FrameActive LineActive
Line4	Off FrameActive LineActive
Line5	Off FrameActive LineActive FlashOut1
Line6	Off FrameActive LineActive FlashOut2
Line7	Off FrameActive LineActive FlashOut3
Line8	Off FrameActive LineActive FlashOut4

Line9	Off FrameActive LineActive MSOut
Line10	Fan
Line11	Off MSOut

14.1.2 allPIXA neo

This table contains the supported LineMode and LineFormat entries for each supported line.

Line	LineMode	LineFormat	Comment
Line1	Input	RS422 RS422_NoTerm SingleEnded_3V3 SingleEnded_5V SingleEnded_12V SingleEnded_24V	
Line1	Output	Not Supported	Output mode not supported.
Line2	Input	RS422 RS422_NoTerm SingleEnded_3V3 SingleEnded_5V SingleEnded_12V SingleEnded_24V	
Line2	Output	Not Supported	Output mode not supported.
Line3	Input	RS422 RS422_NoTerm SingleEnded_3V3 SingleEnded_5V SingleEnded_12V SingleEnded_24V	
Line3	Output	RS422 SingleEnded_3V3	
Line4	Input	RS422 RS422_NoTerm SingleEnded_3V3 SingleEnded_5V SingleEnded_12V SingleEnded_24V	
Line4	Output	RS422 SingleEnded_3V3	
Line5	Input	NoConnect SingleEnded_3V3	
Line5	Output	NoConnect SingleEnded_3V3 RS422	
Line6	Input	NoConnect SingleEnded_3V3	
Line6	Output	NoConnect SingleEnded_3V3 RS422	
Line7	Input	NoConnect SingleEnded_3V3	If Line5 format is configured as RS422 then Line7 is not available.
Line7	Output	NoConnect SingleEnded_3V3	
Line8	Input	NoConnect SingleEnded_3V3	If Line6 format is configured as RS422 then Line8 is not available.
Line8	Output	NoConnect SingleEnded_3V3	
Line9	Input	Not Supported	Input mode not supported
Line9	Output	Misc	

This table contains the supported LineSource entries for each supported line.

Line	LineSource
Line1	Not Supported
Line2	Not Supported
Line3	Off FrameActive LineActive UserOutput3
Line4	Off FrameActive LineActive UserOutput4
Line5	Off FrameActive LineActive UserOutput5
Line6	Off FrameActive LineActive UserOutput6
Line7	Off FrameActive LineActive UserOutput7
Line8	Off FrameActive LineActive UserOutput7
Line9	Fan UART0

14.2 Line Selector

Name	LineSelector	Standard
Description	Selects the physical line (or pin) of the external device connector.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Line1	
Availability	See enum entries table below.	
Notes	Also check allPIXA evo and allPIXA neo for availability.	
Error behavior	See the device error code documentation.	

Line Selector Enum Entries:

Name	Availability	Description
Line1	ALL	Selects Line1
Line2	ALL	Selects Line2
Line3	ALL	Selects Line3
Line4	ALL	Selects Line4

Line5	ALL	Selects Line5
Line6	ALL	Selects Line6
Line7	ALL	Selects Line7
Line8	ALL	Selects Line8
Line9	EVO	Selects Line9
Line10	ALL	Selects Line10
Line11	EVO	Selects Line11

14.3 Line Mode

Name	LineMode[LineSelector]	Standard
Description	Controls whether the physical line is used to input or output a signal.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Input	
Notes	-	
Error behavior	See the device error code documentation.	

Line Mode Enum Entries:

Name	Description
Input	The selected physical line is used to Input an electrical signal
Output	The selected physical line is used to Output an electrical signal

14.4 Line Inverter

Name	LineInverter[LineSelector]	Standard
Description	Controls the inversion of the signal of the selected input or output Line.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – The Line signal is inverted False – The Line signal is not inverted	
Default value	False	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

14.5 Line Status

Name	LineStatus[LineSelector]	Standard
Description	Returns the current status of the selected input or output Line.	
Interface	Boolean	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	True – The level of the Line signal is High False – The level of the Line signal is low	
Availability	ALL	
Notes	-	
Error behavior	-	

14.6 Line Source

Name	LineSource[LineSelector]	Standard
Description	Selects which internal acquisition or I/O source signal to output on the selected Line. LineMode must be output.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Off	
Availability	See enum entries table below.	
Notes	Also check allPIXA evo and allPIXA neo for availability.	
Error behavior	See the device error code documentation.	

Line Source Enum Entries:

Name	Availability	Description
Off	ALL	Line output is disabled
FlashOut1	EVO	Line output is Flash out 1 state.
FlashOut2	EVO	Line output is Flash out 2 state.
FlashOut3	EVO	Line output is Flash out 3 state.
FlashOut4	EVO	Line output is Flash out 4 state.
FrameActive	ALL	Line output is Frame active state.
LineActive	ALL	Line output is Line active state.
MSOut	EVO	Line output is MasterSlave out state.
UserOutput3	NEO	The UserOutput3 bit state as defined by its current UserOutputValue.
UserOutput4	NEO	The UserOutput4 bit state as defined by its current UserOutputValue.
UserOutput5	NEO	The UserOutput5 bit state as defined by its current UserOutputValue.
UserOutput6	NEO	The UserOutput6 bit state as defined by its current UserOutputValue.
UserOutput7	NEO	The UserOutput7 bit state as defined by its current UserOutputValue.
UserOutput8	NEO	The UserOutput8 bit state as defined by its current UserOutputValue.
Fan	ALL	Line output is Fan
UART0	NEO	Line output is UART

14.7 Line Format

Name	LineFormat[LineSelector]	Standard
Description	Controls the current electrical format of the selected physical input or output line.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	It depends on the LineSelector and the variant.	
Availability	See enum entries table below.	
Notes	Also check allPIXA evo and allPIXA neo for availability.	
Error behavior	See the device error code documentation.	

Line Format Enum Entries:

Name	Availability	Description
NoConnect	NEO	The line is not connected.
SingleEnded_3V3	ALL	The line is single ended input or output for 3.3V. Input signals less than 1.5V are considered as level low, signals higher than 1.5V as level high.
SingleEnded_5V	NEO	The line is single ended input for 5.0V or output for 3.3V. Input signals less than 2.5V are considered as level low, signals higher than 2.5V as level high.
SingleEnded_12V	NEO	The line is single ended input for 12.0V or output for 3.3V. Input signals less than 5.0V are considered as level low, signals higher than 5.0V as level high.
SingleEnded_24V	NEO	The line is single ended input for 24.0V or output for 3.3V. Input signals less than 5.0V are considered as level low, signals higher than 5.0V as level high.
RS422_NoTerm	NEO	The line is currently accepting or sending RS422 level signals with no electrical termination.
RS422	ALL	The line is currently accepting or sending RS422 level signals.
Misc	ALL	The line is a special one

14.8 UserOutput Selector

Name	UserOutputSelector	Standard
Description	Selects which bit of the User Output register will be set by UserOutputValue.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	UserOutput3	
Availability	NEO	
Notes	-	
Error behavior	See the device error code documentation.	

UserOutput Selector Enum Entries:

Name	Description
UserOutput3	Select the bit 3 of the User Output register.
UserOutput4	Select the bit 4 of the User Output register.
UserOutput5	Select the bit 5 of the User Output register.
UserOutput6	Select the bit 6 of the User Output register.
UserOutput7	Select the bit 7 of the User Output register.
UserOutput8	Select the bit 8 of the User Output register.

14.9 UserOutput Value

Name	UserOutputValue[UserOutputSelector]	Standard
Description	Sets the value of the bit selected by UserOutputSelector.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	True – The selected UserOutput bit set to 1 False – The selected UserOutput bit set to 0	
Default value	False	
Availability	NEO	
Notes	-	
Error behavior	See the device error code documentation.	

14.10 Trigger Activation

Name	IOAnalyzerTriggerActivation	Custom
Description	Selects the trigger condition for sampling.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Auto	
Availability	EVO	
Notes	-	
Error behavior	See the device error code documentation.	

Trigger Activation Enum Entries:

Name	Description
Auto	Auto
FallingEdgeChA	Falling Edge Channel A
RisingEdgeChA	Rising Edge Channel A
FallingEdgeChB	Falling Edge Channel B
RisingEdgeChB	Rising Edge Channel B
FallingEdgeChAorB	Falling Edge Channel A or Channel B
RisingEdgeChAorB	Rising Edge Channel A or Channel B

14.11 Source Channel A

Name	IOAnalyzerSourceChannelA	Custom
Description	Selects an analyzer source for channel A.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Off	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Source Channel A Enum Entries:

Name	Description
Off	Off
Line1	Line1
Line2	Line2
Line3	Line3
Line4	Line4
Line5	Line5
Line6	Line6
Line7	Line7
Line8	Line8
Line9	Line9
LinkTrigger0	LinkTrigger0
LinkTrigger1	LinkTrigger1

14.12 Source Channel B

Name	IOAnalyzerSourceChannelB	Custom
Description	Selects an analyzer source for channel B.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Off	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Source Channel B Enum Entries:

Name	Description
Off	Off
Line1	Line1
Line2	Line2
Line3	Line3
Line4	Line4
Line5	Line5
Line6	Line6
Line7	Line7
Line8	Line8
Line9	Line9
LinkTrigger0	LinkTrigger0
LinkTrigger1	LinkTrigger1

14.13 Start Sampling

Name	IOAnalyzerStartSampling	Custom
Description	Starts sampling for the selected trigger condition.	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	1	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

14.14 Stop Sampling

Name	IOAnalyzerStopSampling	Custom
Description	Stops sampling for the selected trigger condition.	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	1	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

14.15 Sample Rate Reduction

Name	IOAnalyzerSampleRateReduction	Custom
Description	Selects the sample rate reduction factor.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	ReductionFactor_1	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

Sample Rate Reduction Enum Entries:

Name	Description
ReductionFactor_1	No sample rate reduction
ReductionFactor_10	Sample rate reduction by factor 10
ReductionFactor_100	Sample rate reduction by factor 100
ReductionFactor_1000	Sample rate reduction by factor 1000

14.16 Sample Rate

Name	IOAnalyzerSampleRate	Custom
Description	Displays the sample rate in Hz.	
Interface	Float	
Access mode	Read Only	
Adjustable while grabbing	No	
Value range	-	
Default value	-	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

14.17 Trigger Position

Name	IOAnalyzerTriggerPosition	Custom
Description	Selects the trigger position for an io analyzer.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[0, 2047]	
Default value	0	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

14.18 IO Analyzer State

Name	IOAnalyzerState	Custom
Description	Displays the state of an IO analyzer.	
Interface	Enumeration	
Access mode	Read Only	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	PreEventSampling	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

IO Analyzer State Enum Entries:

Name	Description
PreEventSampling	An IO Analyzer is in pre-event sampling state.
WaitForTrigger	An IO Analyzer is waiting for the trigger.
Sampling	An IO Analyzer is sampling the signal.
Finished	An IO Analyzer is stopped manually, or the buffer is full.

14.19 IO Analyzer State

Name	IOAnalyzerState	Custom
Description	Displays the state of an IO analyzer.	
Interface	Enumeration	
Access mode	Read Only	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	PreEventSampling	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

IO Analyzer State Enum Entries:

Name	Description
PreEventSampling	An IO Analyzer is in pre-event sampling state.
WaitForTrigger	An IO Analyzer is waiting for the trigger.
Sampling	An IO Analyzer is sampling the signal.
Finished	An IO Analyzer is stopped manually, or the buffer is full.

14.20 IO Analyzer Status

Name	IOAnalyzerStatus	Custom
Description	Displays the status of an IO analyzer.	
Interface	Enumeration	
Access mode	Read Only	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	AnalyzerInactive	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

IO Analyzer Status Enum Entries:

Name	Description
AnalyzerInactive	Analyzer is not active.
AnalyzerInProgress	Analyzer is either waiting for trigger or sampling.
Success	Sampling finished successfully.
Warning	An IO Analyzer is finished with warning.
AliasingWarning	Could not sample all the signal transition.

14.21 Event Count

Name	IOAnalyzerEventCount	Custom
Description	Displays the valid IO analyzer events occurred.	
Interface	Integer	
Access mode	Read Only	
Adjustable while grabbing	No	
Value range	[0, 2048]	
Default value	2048	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

15 Encoder Control

15.1 Encoder Selector

Name	EncoderSelector	Standard
Description	Selects which Encoder to configure.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Encoder0	
Availability	ALL	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

Encoder Selector Enum Entries:

Name	Description
Encoder0	Selects Encoder0

15.2 Encoder Source A

Name	EncoderSourceA[EncoderSelector]	Standard
Description	Selects the signal which will be the source of the input A of the encoder.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	Off	
Availability	ALL	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

Encoder Source A Enum Entries:

Name	Description
Off	Encoder does not forward any input
Line1	Encoder forward input is taken from the I/O Line1
Line3	Encoder forward input is taken from the I/O Line3
Line4	Encoder forward input is taken from the I/O Line4

15.3 Encoder Source B

Name	EncoderSourceB[EncoderSelector]	Standard
Description	Selects the signal which will be the source of the input B of the encoder.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	Off	
Availability	ALL	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

Encoder Source B Enum Entries:

Name	Description
Off	Encoder does not forward any input
Line2	Encoder forward input is taken from the I/O Line2


15.4 Encoder Mode

Name	EncoderMode[EncoderSelector]	Standard
Description	Selects whether the count of encoder uses FourPhase mode or the HighResolution mode.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Default value	FourPhase	
Availability	ALL	
Notes	<p>A jitter filter is applied to the encoder sources for all encoder modes. To achieve higher jitter filtering use Encoder Average feature.</p> <p>The scan direction detection is based on Encoder Source B and independent of the encoder mode.</p> <p>This feature is not available if MasterSlaveMode is configured as Slave.</p>	
Error behavior	See the device error code documentation.	


Encoder Mode Enum Entries:

Name	Description
FourPhase	<p>The counter increments or decrements 1 for every full quadrature cycle.</p> <p><i>The chromasens FourPhase mode is deviating from standard because the state machine defined by SFNC is not implemented.</i></p>
HighResolution	<p>The counter increments or decrements every quadrature phase for high resolution counting.</p> <p><i>This mode is not recommended due to jitter of the encoder.</i></p>

Four Phase



High Resolution



15.5 Encoder Output Mode

Name	EncoderOutputMode[EncoderSelector]	Standard
Description	Selects the conditions for the encoder interface to generate a valid encoder output signal.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Motion	
Availability	ALL	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

Encoder Output Mode Enum Entries:

Name	Description
Motion	Output pulses are generated at all motion increments in both directions.
PositionUp	Output pulses are generated at all new positions in the positive direction. If encoder reverses no output pulse are generated until it has again passed the position where the reversal started.
PositionDown	Output pulses are generated at all new positions in the negative direction. If encoder reverses no output pulse are generated until it has again passed the position where the reversal started.

15.6 Encoder Divider Float

Name	EncoderDividerFloat[EncoderSelector]	Custom
Description	Specifies the number of encoder steps needed to generate an encoder output pulse	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	[0.02 , 255.999]	
Default value	1.0	
Availability	ALL	
Notes	This is the minimum divider value working in combination with other factors! This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

15.7 Encoder Average

Name	EncoderAverage[EncoderSelector]	Custom
Description	Specifies the number of averaged encoder input pulses.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	Average1	
Availability	ALL	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

Encoder Output Mode Enum Entries:

Name	Description
Average1	No averaged performed
Average2	Average 2

Average4	Average 4
Average8	Average 8
Average16	Average 16

15.8 Encoder Value

Name	EncoderValue[EncoderSelector]	Standard
Description	Reads the current value of the position counter of the selected counter.	
Interface	Integer	
Access mode	Read Only	
Adjustable while grabbing	-	
Value range	[0, 65535]	
Default value	0	
Availability	ALL	
Notes	This feature is available only if EncoderOutputMode is either PositionUp or PositionDown.	
Error behavior	See the device error code documentation.	

16 Led Flash Control

16.1 Led Flash Enable

Name	LedFlashEnable	Custom
Description	Enables Led flashing feature to support LED drivers with strobe signals for flashing	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	True – Led flash is enabled False – Led flash is disabled	
Default value	False	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

16.2 Led Flash Number of Pattern

Name	LedFlashNumberOfPattern	Custom
Description	Number of Led Flash pattern per flashing sequence	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	[1 , 4]	
Default value	1	
Availability	ALL	
Notes	-	
Error behavior	See the device error code documentation.	

16.3 Led Flash Pattern Selector

Name	LedFlashPatternSelector	Custom
Description	Selects which Led Flash Pattern to configure	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	Yes	
Value range	See enum entries table below.	
Default value	LedFlashPattern1	
Availability	ALL	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

Led Flash Pattern Selector Enum Entries:

Name	Description
LedFlashPattern1	Led Flash Pattern 1
LedFlashPattern2	Led Flash Pattern 2
LedFlashPattern3	Led Flash Pattern 3
LedFlashPattern4	Led Flash Pattern 4

16.4 Out1 OnTime

Name	LedFlashOut1OnTime[LedFlashPatternSelector]		Custom
Description	This controls the On time for Flash Output 1		
Interface	Float		
Access mode	Read/Write		
Adjustable while grabbing	No		
Value range	Variant	Value Range	
	ax_X	[0.0, 3495.04]	
	g8_X	[0.0, 3276.60]	
Default value	0.0		
Availability	ALL		
Notes	This feature is not available if MasterSlaveMode is configured as Slave.		
Error behavior	See the device error code documentation.		

16.5 Out2 OnTime

Name	LedFlashOut2OnTime[LedFlashPatternSelector]		Custom
Description	This controls the On time for Flash Output 2		
Interface	Float		
Access mode	Read/Write		
Adjustable while grabbing	No		
Value range	Variant	Value Range	
	ax_X	[0.0, 3495.04]	
	g8_X	[0.0, 3276.60]	
Default value	0.0		
Availability	ALL		
Notes	This feature is not available if MasterSlaveMode is configured as Slave.		
Error behavior	See the device error code documentation.		

16.6 Out3 OnTime

Name	LedFlashOut3OnTime[LedFlashPatternSelector]		Custom
Description	This controls the On time for Flash Output 3		
Interface	Float		
Access mode	Read/Write		
Adjustable while grabbing	No		
Value range	Variant	Value Range	
	ax_X	[0.0, 3495.04]	
	g8_X	[0.0, 3276.60]	
Default value	0.0		
Availability	ALL		
Notes	This feature is not available if MasterSlaveMode is configured as Slave.		
Error behavior	See the device error code documentation.		

16.7 Out4 OnTime

Name	LedFlashOut4OnTime[LedFlashPatternSelector]		Custom
Description	This controls the On time for Flash Output 4		
Interface	Float		
Access mode	Read/Write		
Adjustable while grabbing	No		
Value range	Variant	Value Range	
	ax_X	[0.0, 3495.04]	
	g8_X	[0.0, 3276.60]	
Default value	0.0		
Availability	ALL		
Notes	This feature is not available if MasterSlaveMode is configured as Slave.		
Error behavior	See the device error code documentation.		

16.8 Pattern Off Delay

Name	LedFlashPatternOffDelay[LedFlashPatternSelector]		Custom
Description	This increases the duration of the specified pattern		
Interface	Float		
Access mode	Read/Write		
Adjustable while grabbing	No		
Value range	Variant	Value Range	
	ax_X	[0.0, (3495.04 – MaxOutXOnTime)]	
	g8_X	[0.0, (3276.60 – MaxOutXOnTime)]	
	MaxOutXOnTime is the maximum of the flash out on time of the specified pattern.		
Default value	0.0		
Availability	ALL		
Notes	This feature is not available if MasterSlaveMode is configured as Slave.		
Error behavior	See the device error code documentation.		

16.9 Pattern duration

Name	LedFlashPatternDuration[LedFlashPatternSelector]		Custom
Description	This is the resulting duration of the specified pattern		
Interface	Float		
Access mode	Read Only		
Adjustable while grabbing	-		
Value range	The value depends on the minimum line time and on the maximum flash out on time of the specified pattern.		
Default value	-		
Availability	ALL		
Notes	This feature is not available if MasterSlaveMode is configured as Slave.		
Error behavior	-		

16.10 Led Flash Frame Control

Name	LedFlashFrameControl	Custom
Description	Determine if Led flash signals are generated continuously or only while image scan	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	See enum entries table below.	
Availability	ALL	
Default value	Continuous	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

Led Flash Frame Control Enum Entries:

Name	Description
Continuous	Flash pulses are generated continuously
ImageFrame	Flash pulses are generated only during image scan

16.11 Led Flash Sequence Time

Name	LedFlashSequenceTime	Custom
Description	This is the time to repeat all defined pattern in free-run mode.	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	No	
Value range	Variant	Value Range
	ax_X	$[(\text{MinLineTime} * \text{NoOfPattern}), 13980.8]$
	g8_X	$[(\text{MinLineTime} * \text{NoOfPattern}), 13107.0]$
	The minimum value depends on different factors like minimum line time of the system together with number of patterns.	
Default value	-	
Availability	ALL	
Notes	This feature is not available if MasterSlaveMode is configured as Slave.	
Error behavior	See the device error code documentation.	

17 Lighting Control – Not Available for AllPIXA-EVO

17.1 Light Controller Set Load

Name	LightControllerSetLoad	Custom
Description	Loads the Light Controller Set to the device and activates it.	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	1	
Default value	1	
Notes	-	
Error behavior	-	

17.2 Light Controller Set Save

Name	LightControllerSetSave	Custom
Description	Save the Light Controller Set to the non-volatile memory of the device.	
Interface	Command	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	1	
Default value	1	
Notes	-	
Error behavior	-	

17.3 Light Controller Scan Devices

Name	LightControlScanDevices	Custom
Description	Performs a scan for XLCs.	
Interface	Command	
Access mode	Write only	
Adjustable while grabbing	-	
Value range	1	
Default value	1	
Notes	-	
Error behavior	-	

17.4 Light Controller Scan Status

Name	LightControllerScanStatus	Custom
Description	Displays Light Controller scan status information.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	-	
Notes	-	
Error behavior	-	

Light Controller Scan Status Enum Entries:

Name	Description
NoScanExecuted	No scan executed
ScanInProgress	Scan in progress
ScanFinished	Scan finished

17.5 Light Controller Detected Devices

Name	LightControllerDetectedDevices	Custom
Description	The bit position represents the on/off state of the light controller.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	≥ 0	
Default value	-	
Notes	-	
Error behavior	-	

17.6 Light Controller General Error

Name	LightControllerGeneralError	Custom
Description	Displays Light Controller General Error Information.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	-	
Notes	-	
Error behavior	-	

Light Controller General Error Enum Entries:

Name	Description
No Error	NoError
Communication Not Enabled	CommunicationNotEnabled
No Device Available	NoDeviceAvailable
Device Not Available	DeviceNotAvailable
Invalid Controller Selector	InvalidControllerSelector
Invalid Channel Selector	InvalidChannelSelector
Link May Be Broken	LinkMayBeBroken
Invalid ID	InvalidID
ID Already Assigned	IDAlreadyAssigned

17.7 Light Controller Selector

Name	LightControllerSelector	Standard
Description	Selects the Light Controller to configure.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	-	
Notes	-	
Error behavior	-	

Light Controller Selector Enum Entries:

Name	Description
LightControllerBroadcast	Light Controller Broadcast
LightController2	Light Controller 2
LightController3	Light Controller 3
LightController4	Light Controller 4
LightController5	Light Controller 5
LightController6	Light Controller 6
LightController7	Light Controller 7
LightController8	Light Controller 8
LightController9	Light Controller 9
LightController10	Light Controller 10
LightController11	Light Controller 11
LightController12	Light Controller 12
LightController13	Light Controller 13
LightController14	Light Controller 14
LightController15	Light Controller 15

17.8 Light Connection Status

Name	LightConnectionStatus	Standard
Description	Status of a light connected to the controller's output line.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	-	
Notes	-	
Error behavior	-	

Light Connection Status Enum Entries:

Name	Description
Sensing	Sensing
Ready	Ready
NoConnect	No connect
ResponseError	Response error
Error	Error

17.9 Light Controller Reset

Name	LightControllerReset	Custom
Description	Resets the selected XLC.	
Interface	Command	
Access mode	Write only	
Adjustable while grabbing	-	
Value range	1	
Default value	1	
Notes	-	
Error behavior	-	

17.10 Light Controller Assign ID

Name	LightControllerAssignID	Custom
Description	Represents the current Light Controller ID and changes it if another one has been entered.	
Interface	Integer	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Notes	-	
Error behavior	-	

17.11 Light Controller Input Voltage

Name	LightControllerInputVoltage	Custom
Description	Displays the Light Controller input voltage.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Notes	The unit is mV.	
Error behavior	-	

17.12 Light Controller Detailed Error Information

Name	LightControllerDetailedErrorInformation	Custom
Description	Detailed error information about the selected light controller.	
Interface	Enumeration	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	-	
Notes	-	
Error behavior	-	

Light Controller Detailed Error Enum Entries:

Name	Description
NoError	No Error
InvalidCommando	Invalid Commando
InvalidParameter	Invalid Parameter
Parameter	Parameter
CommandNotSupported	Command Not Supported
InputVoltage	Input Voltage
AnalogVoltage	Analog Voltage
LedOutput	Led Output
FailNoSignal	Fail No Signal
TemperatureWarning	Temperature Warning
TemperatureError	Temperature Error
ShutdownSignal	Shutdown Signal
EepromWriteDriverUnit	EEPROM Write Driver Unit
EepromReadDriverUnit	EEPROM Read Driver Unit
EepromWriteLed	EEPROM Write LED
EepromReadLed	EEPROM Read LED
Fan	Fan
AnalogOutputVoltage	Analog Output Voltage
SeeGeneralError	See General Error

17.13 Light Controller Serial Number

Name	LightControllerSerialNumberReg	Custom
Description	Serial Number of the Light Controller	
Interface	String	
String Length	32	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Notes	-	
Error behavior	-	

17.14 Light Controller Channel Selector

Name	LightControllerChannelSelector	Custom
Description	Selects the Light Controller Channel to configure.	
Interface	Enumeration	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	See enum entries table below.	
Default value	-	
Notes	-	
Error behavior	-	

Light Controller Selector Enum Entries:

Name	Description
LightControllerChannelA	Light Controller Channel A
LightControllerChannelB	Light Controller Channel B
LightControllerChannelC	Light Controller Channel C
LightControllerChannelD	Light Controller Channel D
LightControllerChannelBroadcast	Light Controller Channel Broadcast

17.15Light Current Rating

Name	LightCurrentRating	Standard
Description	Set the current rating of the lighting output.	
Interface	Float	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	≥0	
Default value	-	
Notes	The unit is Amp.	
Error behavior	-	

17.16Light Enable

Name	LightEnable	Custom
Description	Controls the light for the selected Lighting Controller.	
Interface	Boolean	
Access mode	Read/Write	
Adjustable while grabbing	-	
Value range	True – Enables the selected lighting controller False – Disables the selected lighting controller	
Default value	-	
Notes	-	
Error behavior	-	

17.17Light Controller Driver Temperature

Name	LightControllerDriverTemperatureReg	Custom
Description	Light Controller Driver Temperature	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Notes	The unit is degrees Celsius.	
Error behavior	-	

17.18Light Controller Luminant Temperature

Name	LightControllerLuminantTemperatureReg	Custom
Description	Light Controller Luminant Temperature	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	-	
Default value	-	
Notes	The unit is degrees Celsius.	
Error behavior	-	

18 Device Error Code

The Device error code is organized in two parts. The upper two bytes define a category. The lower two bytes define the specific error that occurred in this category.

Example

If the region of interest exceeds the sensor boundaries, the following error code is provided by the DeviceErrorCode:

0x00010003

The yellow part defines the category and the green part the specific error. Use the category error number to figure out, in which section you need to search for the specific error code.

So 0x0001 is the category code of the image format control (IMF_ERROR_CATEGORY) group. In this category the code 0x0003 defines the specific error code for the case when the region of interest exceeds the sensor boundaries.

18.1 Error Category (Upper 2 bytes)

This section contains an overview of the categories error codes. This is the upper part of the DeviceErrorCode.

Definition	Value	Description
IMF_ERROR_CATEGORY	0x0001	Image format control error category
ALG_CTRL_ERROR_CATEGORY	0x0002	Analog control error category
ACQ_CTRL_ERROR_CATEGORY	0x0003	Acquisition control error category
DIG_IO_CTRL_ERROR_CATEGORY	0x0004	Digital I/O control error category
ENC_CTRL_ERROR_CATEGORY	0x0005	Encoder control error category
USER_SET_CTRL_ERROR_CATEGORY	0x0006	User set control error category
ICC_ERROR_CATEGORY	0x0007	Image calibration control error category
LUT_CTRL_ERROR_CATEGORY	0x0008	Look-up table control error category
CT_CTRL_ERROR_CATEGORY	0x0009	Color transformation control error category.
DEV_CTRL_ERROR_CATEGORY	0x000A	Device control error category
FAC_ERROR_CATEGORY	0x000B	File access control error category
LED_FLASH_CTRL_ERROR_CATEGORY	0x000C	Led flash control error category
IO_ANALYZER_ERROR_CATEGORY	0x000D	IO Analyzer error category

18.2 Specific Error (Lower 2 bytes)

This section contains the specific error codes (lower part of the DeviceErrorCode) grouped by the category. Check the [DeviceErrorMessage](#) feature to get a description of the error occurred.

18.2.1 Image Format Control (IMF_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the [IMF_ERROR_CATEGORY \(0x0001\)](#).

Definition	Value	Description
IMF_ERR_ROI_INVALID_WIDTH_OFFSET_MODULO	0x0001	The width or the offset is not a multiple of 8(RGB) or 24(Mono)
IMF_ERR_ROI_WIDTH_TOO_SMALL	0x0002	The region width is too small
IMF_ERR_ROI_EXCEEDS_SENSOR_BOUDARIES	0x0003	The region of interest exceeds the sensor boundaries. You need to use a smaller 139ffset or width.
IMF_ERR_WREF_IN_MULTIPLE_ROIS	0x0004	The complete gain control region is located in multiple regions. You need to use the gain control region only in one region
IMF_ERR_BV_MAX_LINE_WIDTH_EXCEEDED	0x0005	The sum of all active region widths and gain control region width (if not completely in one region) exceeds an internal limit of 15360
IMF_ERR_FAILED_TO_SET_ROI_AT_SENSOR	0x0006	An internal error occurred while setting the region parameters
IMF_ERR_FAILED_TO_SET_ROI_AT_TRANSPORT_LAYER	0x0007	An internal error occurred while setting the region parameters
IMF_ERR_INVALID_BINNING_PARAMETER	0x0008	The binning parameter is not supported. You need to use either 1 or 2 for binning parameter
IMF_ERR_INVALID_PIXEL_FORMAT	0x0009	Invalid value for pixel format. You need to use a supported pixel format
IMF_ERR_COULD_NOT_ADJUST_ROI_WIDTH_TO_PXFMT	0x000A	Could not adjust region width corresponding to pixel format. Increase the region width before changing the pixel format
IMF_ERR_COULD_NOT_ADJUST_WREF_OFFSET_WIDTH_TO_PXFMT	0x000B	Could not adjust gain control region width or 139ffset corresponding to pixel format. Increase the gain control region width or 139ffset before changing the pixel format
IMF_ERR_INVALID_ROI_WIDTH_OFFSET_MODULO_PXFMT	0x000C	Invalid region width or offsetX
IMF_ERR_INVALID_WREF_WIDTH_OFFSET_MODULO_PXFMT	0x000D	Invalid gain control region width or offsetX
IMF_ERR_FAILED_TO_SET_PIXEL_FORMAT_AT_SENSOR	0x000E	An internal error occurred while setting the pixel format
IMF_ERR_FAILED_TO_SET_PIXEL_FORMAT_AT_TRANSPORT_LAYER	0x000F	An internal error occurred while setting the pixel format
IMF_ERR_TRIGGER_SLAVE_DELAY_LINES_OUT_OF_RANGE	0x0010	The trigger or slave delay lines value is out of range
IMF_ERR_IMAGE_HEIGHT_OUT_OF_RANGE	0x0011	The image height is out of range
IMF_ERR_TRG_SLAVE_DEL_GCTRL_OFFSET_Y_TOO_SMALL	0x0012	The trigger or slave delay lines value is too small with respect to gain control region offset. The sum of trigger delay lines and gain control region 139ffset must be atleast 2
IMF_ERR_TRG_SLAVE_DEL_GCTRL_OFFSET_Y_TOO_LARGE	0x0013	The trigger or slave delay lines value is too large with respect to gain control region offset. The sum of trigger delay lines and gain control region 139ffset must be less than 32767
IMF_ERR_TESTPATTERN_VALUE_OUT_OF_RANGE	0x0014	The test pattern value is out of range
IMF_ERR_INVALID_PARAMETER	0x0015	Invalid Parameter

IMF_ERR_DECIMATION_HOR_OUT_OF_RANGE	0x0016	The Decimation Horizontal Float value is out of range!
IMF_ERR_INVALID_PIXEL_COLOR_FILTER	0x0017	Invalid pixel color filter!

18.2.2 Analog Control (ALG_CTRL_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the [ALG_CTRL_ERROR_CATEGORY \(0x0002\)](#).

Definition	Value	Description
ALG_CTRL_ERR_GAINCTRL_OFFSET_Y_RANGE	0x0001	The gain control region 140ffset is out of range
ALG_CTRL_ERR_GAINCTRL_WIDTH_RANGE	0x0002	The gain control region width is out of range
ALG_CTRL_ERR_GAINCTRL_HEIGHT_RANGE	0x0003	The gain control region height is out of range
ALG_CTRL_ERR_GAINCTRL_EXCEEDS_SENSOR_BOUNDARIES	0x0004	The gain control region exceeds the sensor boundaries. You need to use a smaller 140ffset or width
ALG_CTRL_ERR_GAINCTRL_OFFSET_X_RANGE	0x0005	The gain control region 140ffset is out of range
ALG_CTRL_ERR_GAINCTRL_INVALID_WIDTH_OFFSET_MODULO	0x0006	The width or the offset is not a multiple of 8(RGB) or 24(Mono)
ALG_CTRL_ERR_GAINCTRL_EXCEEDS_BV_WIDTH_LIMIT	0x0007	The sum of all active region widths and gain control region width (if not completely in one region) exceeds an internal limit of 15360
ALG_CTRL_ERR_GAINCTRL_IN_MULTIPLE_ROIS	0x0008	The complete gain control region is located in multiple regions. You need to use the gain control region only in one region
ALG_CTRL_ERR_FAILED_TO_SET_GAINCTRL_AT_SENSOR	0x0009	An internal error occurred while setting the gain control region parameters
ALG_CTRL_ERR_STOP_GAIN_FACTOR_OUT_OF_RANGE	0x000A	The stop gain factor is out of range
ALG_CTRL_ERR_GAINCTRL_OFFSET_Y_TOO_SMALL	0x000B	The gain control region 140ffset is too small! It must be larger than 2 when using no frame trigger. When using frame trigger the sum of trigger delay lines and gain control region 140ffset must be atleast 2.
ALG_CTRL_ERR_GAINCTRL_OFFSET_Y_TOO_LARGE	0x000C	The gain control region 140ffset is too large! It must be less than or equals to: Height – GainControlRegionHeight when using no frame trigger. When using frame trigger the sum of trigger delay lines and gain control region 140ffset must be less than 32767.
ALG_CTRL_ERR_GAINCTRL_TARGET_VALUE_OUT_OF_RANGE	0x000D	The gain control target value is out of range

ALG_CTRL_ERR_BRIGHTNESS_CONTRAST_GAIN_OUT_OF_RANGE	0x000E	The contrast (gain) value of the brightness contrast feature is out of range
ALG_CTRL_ERR_BRIGHTNESS_CONTRAST_OFFSET_OUT_OF_RANGE	0x000F	The brightness (offset) value of the brightness contrast feature is out of range
ALG_CTRL_ERR_GAIN_VALUE_OUT_OF_RANGE	0x0010	The gain value is out of range
ALG_CTRL_ERR_GAIN_AUTO_AVG_SAMPLES_OUT_OF_RANGE	0x0011	The average samples value is out of range
ALG_CTRL_ERR_GAMMA_VALUE_OUT_OF_RANGE	0x0012	The gamma value is out of range
ALG_CTRL_ERR_INVALID_PARAMETER	0x0013	The parameter is invalid!
ALG_CTRL_ERR_SENSOR_SENSITIVITY_VALUE_OUT_OF_RANGE	0x0014	The sensor sensitivity is out of range
ALG_CTRL_TIMEOUT_READING_VIDEOLEVEL	0x0015	Timeout occurred at reading video level
ALG_CTRL_ERROR_ADAPT_TARGETVALUE	0x0016	Error at adapting Target value for GainControlRegion

18.2.3 Acquisition Control (ACQ_CTRL_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the

[ACQ_CTRL_ERROR_CATEGORY \(0x0003\).](#)

Definition	Value	Description
ACQ_CTRL_ERR_FEATURE_CHANGE_DURING_IMG_ACQ	0x0001	The feature change is not allowed while grabbing
ACQ_CTRL_ERR_TRG_SELECTOR_INVALID	0x0002	The trigger selector is invalid
ACQ_CTRL_ERR_TRG_SIG_DETECTOR_MODE_NOT_AVAILABLE	0x0003	The trigger signal detection mode is invalid for LineStart. You need to use TriggerSignalDetectionMode feature only for Frame trigger
ACQ_CTRL_ERR_LINE_TRG_SRC_INVALID	0x0004	The selected source for line trigger is invalid
ACQ_CTRL_ERR_TRG_ACTIV_INVALID	0x0005	The trigger activation value is invalid
ACQ_CTRL_ERR_TRG_SRC_USED_BY_OTHER_TRIGGER	0x0006	The trigger source is already assigned for another trigger. You need to use different source for LineStart and Frame trigger
ACQ_CTRL_ERR_TRG_FRAME_START_ACTIV_INVALID	0x0007	The trigger activation is invalid for FrameStart/FrameBurstStart. You can use RisingEdge/FallingEdge for FrameStart/FrameBurstStart
ACQ_CTRL_ERR_TRG_FRAME_ACTIVE_ACTIV_INVALID	0x0008	The trigger activation is invalid for FrameActive. You can use LevelHigh/LevelLow for FrameActive
ACQ_CTRL_ERR_FRAME_TRG_SRC_INVALID	0x0009	The selected source for frame trigger is invalid
ACQ_CTRL_ERR_MASTER_TRG_SRC_INVALID	0x000A	The source (encoder0, Line1, Line2 and InternalLB) for SelectMaster_Input trigger is invalid
ACQ_CTRL_ERR_EXPOSURE_TIME_TOO_SMALL	0x000B	The exposure time is too small
ACQ_CTRL_ERR_EXPOSURE_TIME_TOO_LARGE	0x000C	The exposure time is too large
ACQ_CTRL_ERR_LINE_TIME_TOO_SMALL	0x000D	The line time is too small. It must be at least 1.5us larger than integration time
ACQ_CTRL_ERR_LINE_TIME_TOO_LARGE	0x000E	The line time is too large
ACQ_CTRL_ERR_LINE_TIME_TOO_SMALL_RUNTIME	0x000F	The line time is too small, when considering run time parameters
ACQ_CTRL_ERR_OTHER_FRAME_TRIGGER_MODE_ON	0x0010	Selected frame trigger mode cannot be made On because other frame trigger mode is already On

ACQ_CTRL_ERR_TRG_FRAME_END_SRC_INVALID	0x0011	Invalid FrameEnd source
ACQ_CTRL_ERR_DEBOUNCING_MODE_INVALID	0x0012	Invalid debouncing mode
ACQ_CTRL_ERR_TRIGGER_DIV_OUT_OF_RANGE	0x0013	The trigger divider value is out of range
ACQ_CTRL_ERR_TRIGGER_DIV_NOT_AVAILABLE	0x0014	The trigger divider is not available for any frame trigger
ACQ_CTRL_ERR_TRG_LINE_ACTIV_INVALID	0x0015	The trigger activation value is invalid for LineStart. You can use only RisingEdge for LineStart
ACQ_CTRL_ERR_TRG_DELAY_LINES_NOT_AVAILABLE	0x0016	The trigger delay lines is invalid for LineStart. You can use trigger delay lines only for any Frame trigger
ACQ_CTRL_ERR_LINE_START_DISABLE_INVALID	0x0017	Invalid LineStart Disable
ACQ_CTRL_ERR_INVALID_SELECTOR_TRIGGER_DISABLE	0x0018	The trigger disable is invalid for FrameStart/Active. You can use trigger disable only for LineStart
ACQ_CTRL_ERR_SELECTED_LINE_IS_OUTPUT	0x0019	The trigger source used is not configured correctly which is the line mode to output. You need to set the selected line mode to input
ACQ_CTRL_ERR_INVALID_PARAMETER	0x001A	The parameter is invalid!
ACQ_CTRL_ERR_FRAME_RATE_ENABLE	0x001B	The AcquisitionFrameRateEnable feature can be enabled only if the mode of all frame triggers is set to off!
ACQ_CTRL_ERR_FRAME_RATE_RANGE	0x001C	The acquisition frame rate value is out of range!
ACQ_CTRL_ERR_FEATURE_LOCKED	0x001D	The feature is currently locked and cannot be written.
ACQ_CTRL_ERR_TRG_FRAME_RATE_ENABLE_INVALID	0x001E	Enabling a frame trigger is not permitted if the AcquisitionFrameRateEnable feature is set.
ACQ_CTRL_ERR_MASTER_SLAVE_MODE_INVALID	0x001F	The master slave mode is invalid.
ACQ_CTRL_ERR_MASTER_SLAVE_INTERFACE_INVALID	0x0020	The master slave interface is invalid Or invalid interface with respect to master or slave.
ACQ_CTRL_ERR_MASTER_SLAVE_NOT_CONFIGURED	0x0021	Master slave is not configured properly. Enable any master slave interface.
ACQ_CTRL_ERR_MS_AUTOSELECT_LINE_USED_AS_TRIGGER_SOURCE	0x0022	Enabling AutoSelect mode is not permitted if MS Autoselect line is used as TriggerSource.
ACQ_CTRL_ERR_AUTOSELECT_MODE_ON	0x0023	Enabling the selected trigger is not allowed if trigger source is MS master or slave or autoselect line master slave configuration.
ACQ_CTRL_ERR_TDI_INVALID	0x0024	Invalid time delay integration value.
ACQ_CTRL_TDI_NOT_AVAILABLE	0x0025	TDI feature is not available for color sensor.
ACQ_CTRL_ERR_FRAME_ACTIVE_EXTEND_LINES_IS_OUT_RANGE	0x0026	Frame active extend lines is out of range.
ACQ_CTRL_ERR_EXTEND_LINES_NOT_AVAILABLE	0x0027	Frame Active Extend Lines feature is not available for FrameStart, frameBurstStart and LineStart trigger.
ACQ_CTRL_ERR_ACQ_START_DURING_IMG_CAL	0x0028	Acquisition cannot be started during internal DSNU or PRNU calibration process. Try again later.
ACQ_CTRL_ERR_TL_THROUGHPUT_TOO_LOW	0x0029	Too low transport layer throughput! Change the link configuration for an image acquisition.
ACQ_CTRL_ERR_MS_LINE_USED_AS_TRIGGER_SOURCE	0x002A	Enabling master or slave mode is not permitted if MS master or slave line is used as TriggerSource.
ACQ_CTRL_ERR_MS_MASTER_MODE_ON	0x002B	Enabling the selected trigger is not allowed if trigger source is MS master line of master slave configuration.
ACQ_CTRL_ERR_LED_FLASH_ON	0x002C	Enabling the selected trigger is not allowed if trigger source is flash out line during led flash is active
ACQ_CTRL_ERR_TL_ACQUISITION_START	0x002D	Error occurred during acquisition start at transport layer! Check the transport layer configuration

ACQ_CTRL_ERR_EXCEEDS_MAX_PAYLOAD_SIZE	0x002E	The calculated payload size exceeds the maximum limit
ACQ_CTRL_ERR_FRAME_END_MODE_ON_NOT_ALLOWED	0x002F	FrameBurstActive trigger must be ON to enable the FrameEnd trigger mode

18.2.4 Digital IO Control (DIG_IO_CTRL_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the

[DIG_IO_CTRL_ERROR_CATEGORY \(0x0004\).](#)

Definition	Value	Description
DIG_IO_CTRL_ERR_LINE_SELECTOR_INVALID	0x0001	The line selector is invalid
DIG_IO_CTRL_ERR_USEROUTPUT_SELECTOR_INVALID	0x0002	The user output selector is invalid
DIG_IO_CTRL_ERR_LINE_INVALID_MODE	0x0003	The line mode is invalid with respect to the line format.
DIG_IO_CTRL_ERR_INVALID_LINE_MODE_SOURCE	0x0004	The selected line mode is not valid with respect to the line source. You need to use the selected line mode to output or line source to off
DIG_IO_CTRL_ERR_LINE_MODE_SRC_CHANGE_NOT_ALLOWED	0x0005	The selected line mode or source change is not allowed. The selected line is used either as a trigger source or as an encoder source or MS mode is on
DIG_IO_CTRL_ERR_LINE_INVERTER_NOT_SUPPORTED	0x0006	The selected line does not support enabling or disabling line inverter
DIG_IO_CTRL_ERR_INVALID_LINE_SOURCE	0x0007	Invalid line source
DIG_IO_CTRL_ERR_LINE_SOURCE_NOT_AVAILABLE	0x0008	The line source is not available for the selected line
DIG_IO_CTRL_ERR_LINE_MODE_SOURCE_INVALID	0x0009	The selected line cannot be used as trigger source or Master/slave mode. You need to configure the line mode to Input and line source to Off.
DIG_IO_CTRL_ERR_LINE_FORMAT_INVALID	0x000A	Invalid line format.

18.2.5 Encoder Control (ENC_CTRL_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the

[ENC_CTRL_ERROR_CATEGORY \(0x0005\).](#)

Definition	Value	Description
ENC_CTRL_ERR_ENC_SELECTOR_INVALID	0x0001	The encoder selector is invalid
ENC_CTRL_ERR_SRC_A_INVALID	0x0002	The encoder source A is invalid
ENC_CTRL_ERR_SRC_B_INVALID	0x0003	The encoder source B is invalid
ENC_CTRL_ERR_ENC_MODE_INVALID	0x0004	The encoder mode is invalid
ENC_CTRL_ERR_ENC_AVG_INC_OUT_OF_RANGE	0x0005	The encoder average is out of range
ENC_CTRL_ERR_OUT_MODE_INVALID	0x0006	The encoder output mode is invalid
ENC_CTRL_ERR_SRC_IN_USE_BY_OTHER_INPUT	0x0007	The source is already assigned to other input of the selected encoder. You need to use different source for input A and input B
ENC_CTRL_ERR_ENC_DIV_OUT_OF_RANGE	0x0008	The encoder divider value is out of range
ENC_CTRL_ERR_SELECTED_LINE_IS_OUTPUT	0x0009	The encoder source A or B used is not configured correctly. You need to set the selected line mode to input.
ENC_CTRL_ERR_ENC_SRC_B_INVALID_CONFIG	0x000A	Invalid configuration. You need to set some source for input A
ENC_CTRL_ERR_SRC_IN_USE_BY_INPUTA_OR_INPUTB	0x000B	The source is already assigned for either encoder source input A or B

ENC_CTRL_ERR_ENCODER_SOURCE_NOT_CONFIGURED	0x000C	Encoder source is not configured. Set Encoder source input A to any line.
--------------------------------------------	--------	---------------------------------------------------------------------------

18.2.6 User Set Control (USER_SET_CTRL_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the

[USER_SET_CTRL_ERROR_CATEGORY \(0x0006\)](#).

Definition	Value	Description
USER_SET_CTRL_ERR_SELECTOR_INVALID	0x0001	Invalid user set selector
USER_SET_CTRL_ERR_DEFAULT_READ_ONLY	0x0002	The default user set modification is not allowed
USER_SET_CTRL_ERR_LOAD_USER_SET_FAILED	0x0003	An error occurred while loading the user set
USER_SET_CTRL_ERR_LOAD_USER_SET_CMD_VAL_INVALID	0x0004	Invalid load user set command value

18.2.7 Image Calibration Control (ICC_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the [ICC_ERROR_CATEGORY \(0x0007\)](#).

Definition	Value	Description
ICC_ERR_LINE_DISTANCE_OUT_OF_RANGE	0x0001	The line distance is out of range
ICC_IMG_CALMODE_ERR_INVALID_PARAMETER	0x0002	ImageCalibrationMode is out of range
ICC_IMG_CALAUTO_ERR_INVALID_PARAMETER	0x0003	ImageCalibrationAuto is out of range
ICC_IMG_CAL_FEATURES_LOCKED	0x0004	The selected feature is locked due to an image calibration mode is active
ICC_IMG_CALPRNU_NODSNULUT_ACTIVE	0x0005	For PRNU calibration a valid and loaded DSNU is needed
ICC_ERR_SCAN_DIR_CHANGE_NOT_ALLOWED	0x0006	Scan direction is read only when scan direction source is not internal
ICC_ERR_SCAN_DIR_EXT_SRC_NOT_CONFIGURED	0x0007	The Encoder0 is not configured properly for the use of ScanDirectionSource. You need to configure EncoderSourceA and EncoderSourceB

18.2.8 LUT Control (LUT_CTRL_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the [LUT_CTRL_ERROR_CATEGORY \(0x0008\)](#).

Definition	Value	Description
LUT_CTRL_ERR_FFC_LUT_COULD_NOT_LOAD_DATA	0x0001	An error occurred while loading the LUT's data from flash
LUT_CTRL_ERR_INVALID_FFC_LUT	0x0002	The LUT does not contain valid data according to the pixel format
LUT_CTRL_ERR_INVALID_PARAMETER	0x0003	The parameter is invalid!
LUT_CTRL_ERR_IMG_CALAUTO_TIMEOUT	0x0004	Timeout at Internal ImageCalibration
LUT_CTRL_ERR_IMG_CALAUTO_INTERNALERROR	0x0005	Error at Internal ImageCalibration

18.2.9 Color Transformation Control (CT_CTRL_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the [CT_CTRL_ERROR_CATEGORY \(0x0009\)](#).

Definition	Value	Description
CT_CTRL_ERR_SELECTOR_INVALID	0x0001	Invalid color transformation module selector.
CT_CTRL_VALUE_SELECTOR_INVALID	0x0002	Invalid color transformation value (gain or offset) selector.
CT_CTRL_ERR_ENABLING_NOT_ALLOWED	0x0003	Already other color transformation module is active.
CT_CTRL_ERR_GAIN_OUT_OF_RANGE	0x0004	Color transformation module gain value is out of range.

CT_CTRL_ERR_OFFSET_OUT_OF_RANGE	0x0005	Color transformation module offset value is out of range.
CT_CTRL_ERR_MODIFICATION_NOT_ALLOWED	0x0006	
CT_CTRL_ERR_PIXELFORMAT_INVALID_WRT_SRGB	0x0007	Invalid pixel format to activate sRGB. Set the pixel format to RGB8

18.2.10 Device Control (DEV_CTRL_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the

[DEV_CTRL_ERROR_CATEGORY \(0x000A\)](#).

Definition	Value	Description
DEV_CTRL_ERROR_COULD_NOT_GET_TEMPERATURE	0x0001	An internal error occurred while getting the temperature
DEV_CTRL_ERROR_INVALID_VALUE	0x0002	Invalid value set.

18.2.11 File Access Control (FAC_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the [FAC_ERROR_CATEGORY \(0x000B\)](#).

Definition	Value	Description
FAC_ERROR_FILE_ALREADY_OPEN	0x0001	A file is already open
FAC_ERROR_INVALID_FILE_SELECTOR	0x0002	Invalid file selector
FAC_ERROR_INVALID_FILE_OPERATION_SELECTOR	0x0003	Invalid file operation selector
FAC_ERROR_INVALID_FILE_OPERATION_EXEC_VAL	0x0004	Invalid file operation execute command value
FAC_ERROR_FILE_OPERATION_IN_PROGRESS	0x0005	File operation is in progress
FAC_ERROR_NO_FILE_OPEN	0x0006	No file is open
FAC_ERROR_FILE_NOT_OPEN_OR_INVALID_OPEN_MODE	0x0007	Either file is not open or file open mode is not write operation
FAC_ERROR_NO_FILE_SELECTED	0x0008	No file is selected. Select any one file
FAC_ERROR_INVALID_FILE_CONTENT	0x0009	Invalid file content
FAC_ERROR_CHECKSUM_CALCULATION_FAILED	0x000A	Calculation of file checksum failed
FAC_ERROR_CHECKSUM_ERROR	0x000B	Comparison of calculated checksum is not matching with the given checksum
FAC_ERROR_INVALID_OPEN_MODE	0x000C	File open mode is not according to the set operation (read, write)
FAC_ERROR_EXCESS_FILE_SIZE	0x000D	File access (read, write) exceeds the file size(max size for writing)
FAC_ERROR_EXCESS_FILE_ACCESS_BUFFER_SIZE	0x000E	File read access exceeds the file access buffer size
FAC_ERROR_COPY_DATA_TO_FILE_ACCESS_BUF_FAILED	0x000F	An error occurred while copying data to the file access buffer
FAC_ERROR_INVALID_FILE_ACCESS_OFFSET	0x0010	Invalid file access offset
FAC_ERROR_FLASH_ACCESS_ERROR	0x0011	An error occurred during flash access like erase, write
FAC_ERROR_INVALID_OPEN_MODE_SELECTOR	0x0012	Invalid file open mode selector
FAC_ERROR_FILE_ACCESS_BUFFER_OVERRUN	0x0013	File access buffer overrun
FAC_ERROR_CLOSE	0x0014	Error during file close operation. The file has not been updated. The file might be invalid.
FAC_ERROR_CLOSE_FATAL	0x0015	Fatal error during file close operation. Avoid switching off camera! Redo the update! Otherwise, the camera might refuse to boot or problems while connecting might occur.

18.2.12 Led Flash Control (LED_FLASH_CTRL_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the [LED_FLASH_CTRL_ERROR_CATEGORY \(0x000C\)](#).

Definition	Value	Description
LED_FLASH_CTRL_ERR_NO_OF_PATTERN_INVALID	0x0001	Number of pattern value is invalid
LED_FLASH_CTRL_ERR_PATTERN_SELECTOR_INVALID	0x0002	Invalid pattern selector
LED_FLASH_CTRL_ERR_INVALID_FRAME_CONTROL	0x0003	Frame control is invalid
LED_FLASH_CTRL_ERR_SEQUENCE_TIME_INVALID	0x0004	Sequence time is less than the sum of all active pattern on time
LED_FLASH_CTRL_ERR_FLASH_OUT_ON_TIME_INVALID	0x0005	Flash out on time of the selected pattern is invalid
LED_FLASH_CTRL_ERR_FLASH_OUT_OFF_DELAY_INVALID	0x0006	Flash out off delay of the selected pattern is invalid

18.2.13 IO Analyzer (IO_ANALYZER_ERROR_CATEGORY)

The below table contains the details of specific error belongs to the [IO_ANALYZER_ERROR_CATEGORY \(0x000D\)](#).

Definition	Value	Description
IO_ANALYZER_ERR_TRIGGER_ACTIVATION_INVALID	0x0001	The trigger activation is invalid
IO_ANALYZER_ERR_SOURCE_CHA_INVALID	0x0002	Invalid source channel A
IO_ANALYZER_ERR_TRIG_POSITION_OUT_OF_RANGE	0x0003	The trigger position is out of range
IO_ANALYZER_ERR_INVALID_SRC_CH_CONFIG	0x0004	Invalid source channel configuration. Either use both source channel or only channel A
IO_ANALYZER_ERR_SOURCE_CHB_INVALID	0x0005	Invalid source channel B
IO_ANALYZER_ERR_SAMPLE_RATE_REDUCTION_INVALID	0x0006	Invalid sample rate reduction

19 Device Status Code

The Device status code is organized in two parts. The upper two bytes define a status category. The lower two bytes define the specific status that occurred in this category.

19.1 Device Status Category (Upper 2 bytes)

This section contains an overview of the status categories codes. This is again divided into 2 parts. The upper 1 byte contain the error category.

Definition	Value	Description
NO_ERROR	0x00	No error status category
WARNING	0x01	Warning status category
ERROR	0x02	Error status category

The lower 1 byte contain the component code:

Definition	Value	Description
SYSTEM	0x00	System status category
ILLUMINATION	0x01	Illumination status category
SENSOR	0x02	Sensor status category
TRANSPORT LAYER	0x03	Transport layer status category

19.2 Specific status (Lower 2 bytes)

This section contains the specific status codes (lower part of the [DeviceStatusCode](#)) grouped by the category. This again divided into 2 parts. The upper 1 byte for the specific component id and lower 1 byte for the error code.

1. System and Illumination

Definition	Value	Description
DEV_STATUS_OK	0x0000	OK
DEV_STATUS_WARNING_TEMPERATURE_TOO_HIGH	0x0001	Warning: Device temperature high.
DEV_STATUS_ERROR_TEMPERATURE_TOO_HIGH	0x0002	Error: Device temperature too high.
DEV_STATUS_ERROR_ILLUM_TEMPERATURE_TOO_HIGH	0x0003	Error: Illumination temperature too high.
DEV_STATUS_ERROR_ILLUM_LED_ERROR	0x0004	Error: Illumination Error.

2. Sensor

- G8

Definition	Value	Description
SENSOR_STATUS_G8_PGOOD_ERROR	0x0101	Error: g8 sensor PGOOD error.
SENSOR_STATUS_G8_TRAINING_DONE_ERROR	0x0102	Error: g8 sensor training done error.

- P6

Definition	Value	Description
SENSOR_STATUS_P6_TRAINING_DONE_ERROR	0x0201	Error: p6 sensor training done error.
SENSOR_STATUS_P6_INIT_ERROR	0x0202	Error: p6 sensor initialization error

3. Transport layer

- Cxp

Definition	Value	Description
TL_STATUS_WARNING_CXP_LINK_CONFIGURATION	0x0301	Warning: Cxp link configuration invalid.

- Gige

Definition	Value	Description
TL_STATUS_WARNING_LICENSING_AUTHENTICATION_FAILED	0x0401	Warning: License authentication failed. It is in evaluation mode, the stream channel will be closed after 20-30min.

20 Debug Control

This feature might be removed in future releases!

20.1 Full-Flag

Name	FullFlag	Custom
Description	Indicates an internal framebuffer FIFO overflow.	
Interface	Integer	
Access mode	Read only	
Adjustable while grabbing	-	
Value range	0: No overflow 1: An overflow occurred	
Default value	-	
Notes	-	
Error behavior	-	

21 Document History

Date	Version	Author	Changes
5 th February 2020	1.0.0	-	Prepared document for initial release.
29 th April 2020	1.2.0	FG	Introduced RGB10p32 pixel format. Adapted the maximum exposure time and min line time .
20 th May 2020	1.3.0	FG	Set the maximum Image Height to 1015811.
8 th June 2020	1.4.0	FG	Added Decimation Horizontal Float . It is not available in this version.
8 th June 2020	1.4.0	HR	Chapter Sensor Resync Counter removed
10 th June 2020	1.5.0	FG	Added the Stream Region Width feature.
8 th July 2020	1.6.0	FG	Removed the Stream Region Width Feature. It's not required anymore from sphinx library version 2.4.1 and later.
16 th July 2020	1.7.0	AB	Added CDS Gain , FullWellCapacity and LedFlashControl
24 st August 2020	1.9.0	FG	Reduced the value range of GainControlRegionOffsetY . Minimum value is now set to 3 (If no frame trigger is used) Adapted description of DecimationHorizontalFloat and BinningHorizontal . Added note that the Region parameters will be scaled. Adapted range of BinningHorizontal feature and added a note regarding the value range. Added new error code IMF_ERR_DECIMATION_HOR_OUT_OF_RANGE Adapted value range of Gain Control Region Width . It is independent of binning now. The GainControlRegionOffsetX value range depends on the SensorWidth now and not on the WidthMax feature anymore.
12 th October 2020	2.0.0	AB	Removed CDS Gain, FullWellCapacity and FileValidateCommand Added SensorSensitivityChannelSelector and SensorSensitivity Replaced cds gain error code with sensor sensitivity error code
13 th October 2020	2.0.0	AB	Introduced Frame Active Extend Lines feature
14 th October 2020	2.0.0	FG	Added features Sensor Offset X and Sensor Region Width
29 th October 2020	2.1.0	FG	Extended description for All entry of sensor sensitivity channel selector .
17 th November 2020	2.2.0	FG	Introduced GainAutoStatus feature. Adapted description of GainSelector as well as Gain feature for analog and digital gain. Added hint in GainAuto to check GainAutoStatus after performing Once gain calibration.

24 th November 2020	2.3.0	AB	Introduced ExposureTimeMode and ExposureTimeSelector feature.
1 st December 2020	2.4.0	FG	Added list of locked features in description of Image Calibration Mode .
10 th December 2020	2.5.0	FG	<ul style="list-style-type: none"> - Revised Document (Adaptions from PK inserted) - Updated the ExposureTime value range description. - Added information concerning the Digital Gain to ImageCalibrationMode.
11 th December 2020	2.5.0	AB	<ul style="list-style-type: none"> - Added new device error code - Added DeviceErrorMessage feature
14 th December 2020	2.5.0	FG	<ul style="list-style-type: none"> - Adapted description of DeviceErrorMessage feature. - Added some additional information to DeviceErrorCode feature. - Reference DeviceErrorMessage feature in section 6.2 now.
14 th December 2020	2.5.0	AB	<ul style="list-style-type: none"> - Removed extra rows from the specific error code table of Digital IO control
2 nd February 2021	2.6.0	UB	<ul style="list-style-type: none"> - AdjustTargetValueToMaxVideo added to Gain Auto - Enums added to Gain Auto Status - Enum "All" added to Gain Control Region Channel Selector - Enums changed and new added to Image Calibration Mode - Some Items added to DeviceErrorCode
10 th February 2021	2.6.0	FG	<ul style="list-style-type: none"> - Removed EEPROM file from File Selector. - Added some device error codes for File Access Control - Adapted the File Operation Status fatal error description. - Added some general note to File Access Control section. - Removed timeout description from File Operation Execute - Added section for timeout parameters Connection Timeouts
24 th February 2021	2.7.0	HR	<ul style="list-style-type: none"> - Added new feature Infoblock Mode
18 th March 2021	2.8.0	AB	<ul style="list-style-type: none"> - Added features of CoaxPress in Transport Layer category - Added new feature DeviceTapGeometry
4 th June 2021	2.11.0	AB	<ul style="list-style-type: none"> - Added new feature ScanDirectionSource - Added some note for ScanDirection feature. - Increased document version
10 th June 2021	2.12.0	FG	<ul style="list-style-type: none"> - Added SingleFrame entry to AcquisitionMode feature. - Revised AcquisitionStart and AcquisitionStop description.
14 th June 2021	2.12.0	AB	<ul style="list-style-type: none"> - Added AcquisitionAbort and TLParamsLocked features
16 th June 2021	2.13.0	FG	<ul style="list-style-type: none"> - Extended description for GainAuto AdjustTargetValueToMaxVideo
16 th June 2021	2.13.0	AB	<ul style="list-style-type: none"> - Extended the description for AutoSelect in MasterSlaveMode - Adopted 'note' for AcquisitionAbort
18 th June 2021	2.13.0	AB	<ul style="list-style-type: none"> - Added CxpLinkConfigurationPreferred feature.

			<ul style="list-style-type: none"> - Removed Auto enum entry from CxpLinkConfiguration
21 st June 2021	2.13.0	FG	<ul style="list-style-type: none"> - Added new device error code to Acquisition Control (ACQ_CTRL_ERROR_CATEGORY)
25 th June 2021	2.15.0	AB	<ul style="list-style-type: none"> - Changed Minimum value of EncoderDividerFloat
29 th June 2021 1 st July 2021	3.0.0	FG/AB	<ul style="list-style-type: none"> - Added Feature Availability overview. - Change heading levels - Change format to match more to allPIXA evo manual. - Moved Light Controller section more to end. - Removed Special Feature section TLParamsLocked is part from Transport Layer Control. - Grouped transport layer into GigE Vision and CoaXPress features. - Extended the features and linking, depending on their selector. - Some bug fixes, cleaning, and minor changes.
19 th August 2021	3.5.0	AB	<ul style="list-style-type: none"> - Added value range for MeasuredLineTime feature
23 rd August 2021	3.6.0	AB	<ul style="list-style-type: none"> - Added PixelColorFilter feature - Added Availability row in all features table to indicate for which camera variants is available - Added RGBa enum entry in PixelFormat feature - Adopted value range and default value for SensorSensitivity, ExposureTimeMode, ExposureTimeSelector, LineDistance and BinningHorizontal.
28 th September 2021	3.7.0	AB	<ul style="list-style-type: none"> - Increased xml and document version
22 nd October 2021	3.8.0	FG	<ul style="list-style-type: none"> - Adapted the encoder mode feature description.
28 th October 2021	3.9.0	FG	<ul style="list-style-type: none"> - Updated the feature availability matrix.
November 2021	3.10.0	AB/FG	<ul style="list-style-type: none"> - Adapted description of some features: <ul style="list-style-type: none"> o Synchronization Mode Enable o Gain Control Region Offset X o Gain Control Region Channel Selector o Gamma - Corrected some page breaks - Adapted description of Color Transformation Features regarding availability. - Added Notes for AcquisitionLineRate, AcquisitionLineTime, AcquisitionFrameRateEnable, AcquisitionFrameRate and all the TriggerSelector features - Reworked Color Transformation Value Selector a little. Added transformation matrices to Color Transformation Selector - Added Notes for ScanDirectionSource and ScanDirection features
26 th November 2021	3.11.0	FG	<ul style="list-style-type: none"> - Added note to create new DSNU/PRNU references in Gain, Sensor Sensitivity
November/December	3.12.0	FG/AB	<ul style="list-style-type: none"> - Extended the info block mode description and fixed some error there. - Adapted the LineDistance and AcquisitionLineTime/AcquisitionLineRate default values. - Refactored document. Updated and extended some entries and fixed some bugs. - Updated the valid range for Out1OnTime, Out2OnTime, Out3OnTime, Out4OnTime,

			PatternOffDelay and LedFlashSequenceTime for different variants. - Added some Info to Led Flash Enable regarding Master Slave Mode
December 2021	3.13.0	FG	- Fixed some typos in Infoblock Mode
January 2022	3.14.0	FG	- Removed outdated information in Color Transformation Enable
19 th January 2022	3.15.0	FG	- Added notes to Master Slave Mode concerning operating speed.
21 st January 2022	3.15.0	AB	- Added notes to EncoderControl and LedFlashControl regarding the availability of these features - Adapted the Maximum Acquisition line time depending on the camera variants - In MasterSlaveMode , extended the notes for features not available when mode is set to Slave
01 st February 2022	3.15.0	AB	- Added notes to BinnigHorizontal and DecimationHorizontalFloat regarding the maximum value. - Removed notes from LedFlashEnable and LedFlashNumberOfPattern regarding the availability. - Adapted the value range for TriggerDelayLines and SlaveDelayLines - Added missing error codes
04 th February 2022	3.15.0	AB	- Updated device error code for ACQ_CTRL category - Adapt the MasterSlaveInterface for available interfaces and notes
10 th February 2022	3.16.0	AB	- Increased the version to 3.16.0 and xml version - Updated the FeatureAvailability for DecimationHorizontalFloat feature
11 th February 2022	3.16.0	HR	- added description of DeviceHWCalibFileVersion feature Device Hardware Calibration File Version .
24 th February 2022	3.17.0	HR	- added feature Device Fan Enable .
01 st March 2022	3.18.0	AB	- Updated the device error code for AcquisitionControl and DigitalIOControl specific error
04 th March 2022	3.18.0	AB	- Updated the error code for AcquisitionControl and EncoderControl category
07 th March 2022	3.18.0	AB	- Update the error code for EncoderControl category
22 nd March 2022	3.18.0	AB	- Update the error code for DigitalIOControl category
23 rd March 2022	3.18.0	AB	- LineMode Output and LineSource are made available
27 th April 2022	3.18.0	HR	- Changes in chapter Device Control (DEV_CTRL_ERROR_CATEGORY) - Renamed Device Control error code - New Device Control error code introduced
28 th April 2022	3.18.0	AB	- Updated device error coder ACQ_CTRL_ERROR_CATEGORY - Extended LineSource for MSOut
6 th May 2022	4.0.0	FG	- Reworked the Image Calibration Mode feature. Added some information about canceling the calibration process.
16 th May 2022	4.1.0	FG	- Introduced new feature for xml extra version part Device Manifest XML Extra Version . - Added note to the the xml version features.

30 th May 2022	4.1.0	FG	<ul style="list-style-type: none"> - Extended description for Info block concerning future package 2.1.2 in line time calculation. - Updated feature availability.
1 st June 2022	4.1.0	FG	<ul style="list-style-type: none"> - Fixed/Adapted description of Acquisition Abort
3 rd June 2022	4.1.0	AB	<ul style="list-style-type: none"> - Added DeviceStatusMessage feature and DeviceStatusCode. - Updated the Device Control specific error codes
7 th June 2022	4.1.0	AB	<ul style="list-style-type: none"> - Added new enum entry in FileSelector for MemoryFile
29 th July 2022	4.1.0	AB	<ul style="list-style-type: none"> - Added DeviceLinkSpeed feature
26 th August 2022	4.2.0	FG	<ul style="list-style-type: none"> - Updated Feature Availability table
30 th August 2022	4.3.0	FG	<ul style="list-style-type: none"> - Corrected the minimum width value to 128
7 th September 2022	4.3.0	AB	<ul style="list-style-type: none"> - Added LineFormat, UserOutputSelector and UserOutputValue features - Extended the LineSource enum entries - Added CameraTypes with the model name and DigitalIOCompatibilitiesEvo and DigitalIOCompatibilitiesNeo - Updated the DigitalIOControl error codes
8 th September 2022	4.3.0	AB	<ul style="list-style-type: none"> - Renamed DigitalIOCompatibilities to allPIXA evo and neo. Separated the table for line and LineSource
20 th September 2022	4.3.0	AB	<ul style="list-style-type: none"> - Adapted the SensorColorType feature
21 st September 2022	4.3.0	AB	<ul style="list-style-type: none"> - Adapted the DeviceStatus feature - Updated the DeviceStatusCode
26 th September 2022	4.3.0	AB	<ul style="list-style-type: none"> - Added FrameCount feature
17 th October 2022	4.3.0	AB	<ul style="list-style-type: none"> - Added AcquisitionBurstFrameCount - Extended the TriggerSelector for FrameBurstStart entry - Updated the device error code in AcquisitionControl
29 th November 2022	6.0.0	FG	<ul style="list-style-type: none"> - Versioning of the feature reference has changed. The version corresponds to the Firmware/XML version from now.
15 th February 2023	6.1.0	AB	<ul style="list-style-type: none"> - Added IOAnalyzer features in DigitalIOControl - Added device error code category for IO Analyzer - Updated the FeatureAvailability table - Updated FileSelector entries for IOAnalyzerEventFile
9 th March 2023	6.1.0	FG	<ul style="list-style-type: none"> - Added new Device Status Codes for p6 sensor
25 th April 2023	6.1.0	FG	<ul style="list-style-type: none"> - Added note concerning the Sensor Sensitivity of the g8 sensor. - Added description for Line Status and Scan-Direction of the Infoblock Mode - Added hint, that the ScanDirectionSource Encoder is currently only for EncoderSourceB=Line2
18 th August 2023	6.1.0	AB	<ul style="list-style-type: none"> - Added Gige TL device status code. - Adapted value range for LineDistance feature
23 rd August 2023	6.2.0	AB/FG	<ul style="list-style-type: none"> - Adapted digital IO function scope for Line10 and Line11 - Added Time Delay Integration Mode feature - Marked Master Slave Interface and Master Slave Interface Enable as deprecated - Added MasterSlaveSource and AutoSelectSource features - Updated LineSelector for Line10 and Line11 - Updated LineFormat for Misc - Updated LineSource for Fan and UART0

13 th September 2023	6.2.0	AB	<ul style="list-style-type: none"> - Added new flat field correction features <ul style="list-style-type: none"> o Flat Field Correction Selector o Enable o DataSet Description o Avaialble Planes o First Valid Pixel o Last valid Pixel o Display Reference o Start Calibration o Stop Calibration o Calibration Status - Marked few features in Image Calibration control category as deprecated
5 th October 2023	6.2.0	AB	<ul style="list-style-type: none"> - Updated pixel format and pixel color filter availability for the camera variants - Update FeatureAvialability for p6_nxge and added new column for p16_cxp
6 th October 2023	6.2.0	AB	<ul style="list-style-type: none"> - Updated SensorColorFilter enum entry
10 th October 2023	6.3.0	AB	<ul style="list-style-type: none"> - IO analyzer features are not available for p6_nxge camera
31 st October 2023	6.3.0	AB	<ul style="list-style-type: none"> - Added DeviceLogLevel and FlatFieldCorrectionCalibrationMode features - Marked ImageCalibrationMode as deprecated feature
15 th November 2023	6.4.0	AB	<ul style="list-style-type: none"> - Added EncoderValue and enum entries of EncoderOutputMode